## AD-A280 472



## NAVAL POSTGRADUATE SCHOOL Monterey, California



## **THESIS**

SACS: A CACHE SIMULATOR INCORPORATING TIMING ANALYSIS WITH BUFFER AND

by

**MEMORY MANAGEMENT** 

William G. Smith

March, 1994

Thesis Advisor:

Douglas J. Fouts

Approved for public release; distribution is unlimited.

# Best Available Copy

#### REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704

Public reporting burden for this collection of information is estimated to average I hour per response, including the time for reviewing instruction, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information, including suggestions for reducing this burden, to Washington headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, State 1204, Artington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188) Washington IX 20503

2. REPORT DATE March, 1994	1		ATES COVERED
	• • •	5. FUNDING	NUMBERS
S) AND ADDRESS(ES)			MING ORGANIZATION NUMBER
AME(S) AND ADDRESS(ES)			RING/MONITORING Y REPORT NUMBER
	do not reflect the offi	cial policy o	r position of the
EMENT		12b. DISTRI	BUTION CODE
oution unlimited			
es. The SACS model inclu f buffer and data forwardin	des read and write buing policies, as well as	ffers, main r the traditior	nemory, and cache memory. In half block replacement, write, and
			15. NUMBER OF PAGES
· · · · · · · · · · · · · · · · · · ·	er Architecture,		264 16. PRICE CODE
	19. SECURITY CLASS OF ABSTRACT	IFICATION	20. LIMITATION OF ABSTRACT
	March, 1994  INCORPORATING TIMID MEMORY MANAGEN  S) AND ADDRESS(ES)  are those of the author and divergence of the author and divergence ovides the user with a wide of buffer and data forwarding udes a self-testing mode with a self-testing mode w	March, 1994  Master  INCORPORATING TIMING D MEMORY MANAGEMENT  S) AND ADDRESS(ES)  are those of the author and do not reflect the offi. Giovernment.  EMENT  Dution unlimited  ovides the user with a wide range of timing inforces. The SACS model includes read and write but of buffer and data forwarding policies, as well as udes a self-testing mode which can be used to describe the serior of the side of the serior of the	March, 1994  Master's Thesis  S. FUNDING  MEMORY MANAGEMENT  S. AND ADDRESS(ES)  8. PERFORT  REPORT  NAME(S) AND ADDRESS(ES)  10. SPONSO AGENCY  are those of the author and do not reflect the official policy of the content.  EMENT  Duttion unlimited  12b. DISTRIP  Duttion unlimited  12b. DISTRIP  Duttion unlimited  15c. The SAC'S model includes read and write buffers, main in the buffer and data forwarding policies, as well as the tradition undes a self-testing mode which can be used to debug the programmy Simulation, Computer Architecture,  15c. TURITY CLASSIFICATION  19. SECURITY CLASSIFICATION  19. SECURITY CLASSIFICATION

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89) Prescribed by ANSI Std. 239-18 Approved for public release; distribution is unlimited.

SACS: A Cache Simulator Incorporating Timing Analysis with Buffer and Memory Management

by

William G. Smith
Lieutenant, United States Naval Reserve
B.S., Saint Bonaventure University, Saint Bonaventure, New York, 1984

Submitted in partial fulfillment of the requirements for the degree of

MASTER OF SCIENCE IN ELECTRICAL ENGINEERING

from the

NAVAL POSTGRADUATE SCHOOL March 1994

Author:

William G. Smith

Approved by:

Douglas J. Touts

Douglas J. Fouts, Thesis Advisor

Amr M. Zaky, Second Reader

Michael A. Morgan, Chairman, Department of Electrical and Computer Engineering

Michael a. Man

#### **ABSTRACT**

SACS is a cache simulator that provides the user with a wide range of timing information, in addition to providing typical information such as hit and miss rates. The SACS model includes read and write buffers, main memory, and cache memory. In addition, SACS supports a number of buffer and data forwarding policies, as well as the traditional block replacement, write, and write miss policies. SACS also includes a self-testing mode which can be used to debug the program after source-code modification.

Accesio	n For	
NTIS DTIC Unanno Justific	TAB ounced	<b>A</b>
By Distribu	ition /	
А	vailabilit	y Codes
Dist	Avail a Spe	and <b>/ or</b> cial
A-1		\$

## **TABLE OF CONTENTS**

ł.	INTR	ODUCTION	1
	A.	CACHE MEMORIES	1
	В.	PROBLEMS OF CACHE MEMORIES	3
	C.	EXISTING CACHE SIMULATORS	4
	D.	PROBLEMS WITH EXISTING CACHE SIMULATORS	4
II.	INTR	ODUCTION TO SACS	6
	A.	THE NEED FOR STILL ANOTHER CACHE SIMULATOR	6
	В.	COMPARING SACS TO OTHER CACHE SIMULATORS	6
	C.	THE CAPABILITIES OF SACS	7
III.	SACS	S INPUT PARAMETERS	8
	A.	INTRODUCTION	8
	В.	SIZE ARGUMENTS	9
	C.	CACHE ACCESS, HIT, AND MISS ARGUMENTS	9
	D.	MEMORY ACCESS AND TRANSFER TIME ARGUMENTS	9
	E.	BUFFER ARGUMENTS	9
	F.	CACHE POLICY ARGUMENTS	10
	G.	SEARCH BUFFERS AND UPDATE BUFFER ARGUMENTS	11
	Н.	REMOVE READ DUPLICATES AND WRITE DUPLICATES ARGUMENTS	11
	I.	PRIORITY ARGUMENTS	11
	J.	SACS CONTROL ARGUMENTS	11
IV.	SACS	S DISPLAYS	15
	A.	TRACE DISPLAY	15
	В.	RESULTS DISPLAY	20
	C.	STALL DISPLAY	21
	D.	CACHE ARGUMENTS DISPLAY	22
	E.	GO TO A SPECIFIC TIME	22
	F.	INCREMENT TIME	23
	G.	DECREMENT TIME	23
	Н.	HELP DISPLAY	23

V.	SAC	S DESIGN	25
	A.	OVERALL STRUCTURE OF SACS	25
	В.	MAIN EVENT LOOP	
	C.	CACHE MODEL	26
	D.	MEMORY MODEL	
	E.	TIME ESTIMATES	
VI.	PRO	GRAM VALIDATION	40
	A.	TESTING SACS	40
	В.	CHECKING COMPLETION TIME	42
	C.	CHECKING GLOBAL VARIABLES	43
VII.	SAM	PLE RUNS	44
	A.	EXAMPLE SACS SIMULATION RUN	44
VIII.	CON	ICLUSION	55
LIST	OF RE	EFERENCES	57
APPE	NDIX	(SOURCE CODE FOR SACS)	58
BIBL	IOGRA	АРНҮ	256
INITI	AL DI	STRIBUTION LIST	257

#### I. INTRODUCTION

#### A. CACHE MEMORIES


Cache memories are usually small memories that contain blocks of data and/or instructions [Ref. 1]. Each block is a copy of consecutive data and/or instruction bytes from main memory. Caches are usually much faster than their main memory counter parts. They are, in effect, short term memory. The cache contains a set of blocks recently accessed by the CPU. The cache can provide the most recently used data and/or instructions to the CPU in less time than it would have taken to get the information from main memory. However, if the cache fails to provide the information, then it fetches the information from main memory and, depending on its design, may choose to enter the information into the cache. The cache also performs memory updates in the form of writes. Memory updates can occur when the CPU makes a write request, or the cache can store new data in the cache blocks and wait until later to write the data to memory [Ref. 2:p. 197]. A dirty block is a cache block which contains data that is more current than memory because of a recent write request.

The concept of the cache storing recently used memory blocks is very simple. In fact, many early cache designs were simple implementations of the concept. However, the task of building an optimized cache is not trivial. The difficulty comes from trying to provide the CPU with the correct data or instruction as soon as it is available. For example,

if a block read is in progress and there is enough data available to satisfy the pending load, the data should be forwarded to the CPU rather than waiting for the block read and cache update. The cache often performs block management between requests. One example of block management is writing dirty data to memory. Another example is reading data that was not part of the CPU request, but located in the same block. This allows the cache to contain all the data that was in the block. An optimized cache performs block management only after completing the CPU request. Complications arise when the CPU makes another request before the block management for the last request is complete. If this happens, the cache has to search for data in the control sections of the cache as well as the cache memory.

More and more cache designs incorporate read and write buffers in their control sections. These buffers allow the cache to perform block management while minimizing the effect on the CPU request [Ref. 3]. For example, if a CPU read request results in a miss and the block victim has a dirty sub block, then writing the dirty sub block to memory may occur after reading the replacement block. This allows the cache to forward the read data to the CPU before writing the old data to memory. Figure 1 provides a simplified data flow diagram that illustrates buffer use in modern cache designs.

Scoreboarding is a term that has been used to describe the process of searching, and choosing the correct value of a register argument. Scoreboarding in a cache represents the act of searching and altering buffers based on new CPU requests. One example of scoreboarding is searching a buffer for CPU requested data. Searching block and write



buffers may provide data that is not available in the cache memory. Searching the read buffer ensures that no duplicate read requests are placed in the buffer. However, it will not provide any new data. Another example of scoreboarding is updating read requests in the read buffer with data provided by CPU write requests.

#### B. PROBLEMS OF CACHE MEMORIES

Cache memories can cause more problems than they solve and they can significantly complicate the memory model. The most obvious problem with a cache memory is that it does not always contain the data that the CPU requests. This is defined as a read miss. A write miss is when the CPU makes a write request and the correct block is not in the cache. Conversely, a read hit is when the data is available, and a write hit is when the block is available. There are three types of cache misses [Ref. 4:p. 419]. First,

the compulsory miss results when data is accessed for the first time. Second, the capacity miss, occurs when the cache is not big enough to carry all the blocks required. The third type, collision misses, occurs when the cache requires several main memory blocks that map to the same set of cache blocks. This causes a form of thrashing similar to that seen in virtual memories.

In some numerical calculations, the cache makes the average access time greater than the main memory access and transfer times. This is often due to matrix operations that access elements across rows and force the cache to enter an entire block of data for each element read. Depending on the size of the matrix, it may not be possible to save enough blocks to ensure that the next block accessed was not selected as a victim and replaced. As a result, many architectures support special load and store instructions that bypass the cache.

#### C. EXISTING CACHE SIMULATORS

There are a number of cache simulators. Two examples include Dinero III, and Tyco [Ref. 5]. Dinero III provides hit and miss data for a wide range of input arguments. Dinero III will also simulate either a unified cache, or separate data and instruction caches. Tyco, on the other hand, simulates several different cache options simultaneously for comparison.

#### D. PROBLEMS WITH EXISTING CACHE SIMULATORS

Unfortunately, both Dinero III and Tyco limit their simulations to hit-miss calculations. With nothing but hit-miss information, the designer cannot optimize his cache

for the lowest average access time. Most caches are designed to have low average access times rather than high hit rates [Ref. 4:p. 405]. Since Dinero III and Tyco do not perform the time analysis, they may mislead the designer. Dinero III and Tyco also do not provide any buffer simulations because they assume that the cache has all the time it needs between loads and stores to complete all of its block management. Since buffer management and scoreboarding have such a large effect on the average access time, there is an obvious need for a simulator that can perform accurate timing analysis, buffer management, and scoreboarding.

#### II. INTRODUCTION TO SACS

#### A. THE NEED FOR STILL ANOTHER CACHE SIMULATOR

A cache simulator should not only simulate the cache memory, it should simulate main memory and any buffers it uses. As discussed earlier, neither Dinero III nor Tyco provide any means for simulating buffers or memory.

Without timing analysis, the designer is unable to determine the effect of scoreboarding protocols. These protocols, which are usually very difficult to implement, can be avoided by delaying any read requests until all writes are completed and the last read block has been entered into the cache. Timing analysis allows the designer to choose the scoreboarding technique that best suites his or her resources and architectural requirements. A hit-miss cache simulator reduces this process to guess work.

#### B. COMPARING SACS TO OTHER CACHE SIMULATORS

As previously discussed, other cache simulators provide hit-miss results, while SACS provides the all important average access time. However, in addition to the correct performance measurements, a simulator should illustrate a cache's strengths and weaknesses. It should give the user a clear understanding of how to improve the cache's design. With Dinero III, the user could only guess on how to improve his/her cache design. Tyco attempted to correct this problem by allowing the user to simulate several caches simultaneously. However, given the number of different variables and policy choices.

exhausting all possible combinations is not the best way to design a cache. SACS is unique because it provides the user with a detailed analysis of exactly what the cache was doing during a simulation run. The user can then identify and correct specific problems with a cache design.

#### C. THE CAPABILITIES OF SACS

SACS allows the designer to experiment with different policies while measuring their affect on the average access time. SACS provides the user with more detailed information because it maintains a log of how every clock cycle is spent. This log is kept in the form of a histogram. It allows the user to see exactly how much time is spent performing read or write requests. It also records how many times a request was completed within a given time period. With these details, the user can easily evaluate the cache's performance. A second histogram is available which details the amount of time spent performing cache accesses, memory accesses, and waiting for full buffers. With this histogram, the designer can target specific weaknesses. It also provides a good comparison of the effect of different scoreboarding policies between runs.

#### III. SACS INPUT PARAMETERS

#### A. INTRODUCTION

SACS provides a wide range of input parameters to model various different functionally diverse caches. While it is impossible to imagine what kinds of caches designers might build in the future, every effort was made to allow the designer to simulate, or most nearly approximate, his or her design. Table 1 lists arguments that SACS supports.

## TABLE 1. SACS INPUT ARGUMENTS

Cache Size (-cs n) Blocks Size (-bs n) Sub Block Size (-sbs n) Associativity (-a n) Word Size (-ws n) Read Cache Access Time (-rcat n) Read Cache Hit Time (-rcht n) Read Cache Miss Time (-rcmt n) Write Cache Access Time (-wcat n) Write Cache Hit Time (-wcht n) Write Cache Miss Time (-wcmt n) Memory Access Time (-mat n) Memory Transfer Time (-mtt n) Buffer Cache Access Time (-bcat n) Read Buffer Size (-rbs n) Write Buffer Size (-wbs n) Block Replacement Policy (-brp e1) Write Policy (-wp e2) Write Miss Policy (-wmp e3)

Read Forward (-rf -drf) CPU Waits For Cache Writes (-cwfcw -dcwfcw) Search Block Buffer (-sbb, -dsbb) Update Read Buffer (-urb, -durb) Remove Read Duplicates (-rrd, -drrd) Remove Write Duplicates (-rwd, -drwd) Read Priority (-rpr n) Write Priority (-wpr n) Read For Write Allocate Priority (-rfwapr n) Write Dirty Block Priority (-wdbpr n) No Priority (-npr n) Trace (-t, -dt) Check (-c, -dc) Test (-test) Key Board IO (-kbio, -fio) Data File Name (-f "File Name") Screen Histogram Max Index (-shmi n) File Histogram Max Index (-fhmi n)

- n . Unsigned Integer
- el : enumeration type (LRU, FIFO, RAND)
- e2 enumeration type (Write Through, Write Back) e3 enumeration type (Write Around, Write Allocate)

#### B. SIZE ARGUMENTS

All sizes are entered in bytes. Cache Size must be an even multiple of both Block Size and Associativity. Block size must be an even multiple of Sub Block Size, and Sub Block Size must be an even multiple of Word Size. Word Size may be any positive integer that does not force an integer overflow in Cache Size or Block Size.

#### C. CACHE ACCESS, HIT, AND MISS ARGUMENTS

Cache Access Times represent the time required for a request to access the cache, providing the cache is not busy. At the end of this time it is determined whether the request is a hit or a miss. The Cache Hit Time represents the time required to complete a request once the cache access time has expired and the request has been identified as a hit. If the request was a miss, then the Cache Miss Time is used instead.

#### D. MEMORY ACCESS AND TRANSFER TIME ARGUMENTS

The Memory Access Time is the time required for a buffer to access, and then transfer, the first word of a request from memory. Memory Transfer Time is the time required for a buffer to transfer each consecutive word following the first access.

#### E. BUFFER ARGUMENTS

After a memory read, the *Block Buffer* contains the new data that must be entered into the cache. The time that the *Block Buffer* takes to access the cache is called the *Buffer Cache Access Time*. The *Block Buffer* may have to wait longer because the cache is busy. The buffer cache access will not occur if a read or write cache access is required during the same clock cycle. However, once the access begins, the read and write cache accesses are

locked out until the cache is updated. The *Read* and *Write Buffer* sizes can be any positive non zero integer (<100).

#### F. CACHE POLICY ARGUMENTS

Block replacement policy determines the method used to choose the location of a new block in the cache. SACS supports three block replacement policies: Least Recently Used (LRU), First In First Out (FIFO), and Random (RAND). There are two write policies: Write Through, and Write Back. The Write Through policy forwards the data to memory immediately after a write request. However, in the Write Back policy, the data is saved in the cache until the block that contained the data is selected as a victim. Dirty bits indicate which sub blocks have new data that must be written to main memory.

SACS can easily be modified to support new write, or write miss policies by adding the new policy name to Write Policy Types, or the Write Miss Policy Types in SACS.h.

The code to simulate these new policies must be placed in the procedures Write Hit, and/or Write Miss which are both located in Cache.c. New block replacement policies may also be added by modifying Replacement Policy Types in SACS.h, and Select Block Victim in Cache.c.

If CPU Waits For Cache Writes is asserted the CPU will wait after a write request until the cache is complete with the write. Otherwise, it is assumed that the cache can carry out the write while the CPU continues with other instructions.

If Read Forward is asserted, then a read miss is complete once the data required arrives in the block buffer. Otherwise, the read must wait until the block updates the cache.

#### G. SEARCH BUFFERS AND UPDATE BUFFER ARGUMENTS

Search Block Buffer allows the cache to search the block buffer in case the read data was already received from memory. If any part of the data is found in the buffer, then the size of the request will be appropriately reduced. Update Read Buffer allows a write memory request to provide data required by a read request. If any read request needs the data provided by the write memory request, then the size of the read request will be reduced appropriately, and the data is not read from memory.

### H. REMOVE READ DUPLICATES AND WRITE DUPLICATES

#### **ARGUMENTS**

Removing read and write duplicates means that requests that have intersecting or concurrent data will get spliced together into one request. Otherwise, a buffer may contain multiple requests to the same memory location.

#### I. PRIORITY ARGUMENTS

In SACS, the user specifies the priority of requests. The lowest numbers represent the highest priority. This allows the designer to simulate a cache that must finish all writes before starting a read. It also allows the designer to delay reads for write allocated blocks, and the writing of dirty blocks.

#### J. SACS CONTROL ARGUMENTS

#### 1. Introduction

SACS has control arguments that allow the user to select one of several modes of operation.

#### 2. Trace Argument

The trace mode permits the user to step through a trace, one clock cycle at a time, viewing the contents of the cache and buffers, and obtain statistical results.

#### 3. Check Argument

When SACS is in the check mode, it performs a self check of all of its global variables. These checks include checking to see that all the global variables that should remain constant, do in fact remain constant. Global variables that are not constant are checked to see that they are within prescribed bounds. This form of checking can occur while the program is in any other mode (i.e., Trace, Test, or Key Board I/O). This check can be performed during normal data runs. This kind of checking helps to identify errors that might have gone unnoticed. It also assures the user that the program did not catastrophically fail during a run.

#### 4. Test Argument

When SACS is in its test mode it can do nothing else. It will automatically generate its own input data. The data is generated by randomly selecting a finite number of test cases to use. Each test case has a combination of seven load/store instructions. The expected number of read and write hits for each test case is known. Therefore, the total number of read and write hits for the trace can be determined. The actual addresses used for each test case are chosen randomly. However, all the loads for a particular test case will map to the same block. Similarly, all stores will also map to the same block. SACS will randomly select its own set of input parameters, ignoring any other arguments entered.

It will then run the main routine on the test trace as if it was a user defined file. Once the trace is complete, SACS will compare the results with what it expected from the random trace. If no errors have been detected, then SACS will repeat the process of randomly generating its input file and input parameters. The test mode places SACS into an infinite testing loop. The only way to terminate the process is to kill the process. The decision not to give the user a more graceful way out of the test mode was made because C does not provide a way to trap IO. While there are operating system methods of trapping IO, they would have made the program system dependent and, therefore, non-portable. The current version of SACS has been compiled and run on both a PC running DOS and a SPARC station running Sun -OS without any changes to the source code.

#### 5. Key Board IO Argument

SACS normally accepts its inputs from a data file. However, it can accept inputs directly from the user. This input mode can be used with the trace and checking modes if desired. SACS will ask for each request from the terminal as required. The trace display will appear each time a new request is made. However, it will not stop every clock cycle unless the user selects the trace mode.

#### 6. Data File Name Argument

SACS normally assumes that the data file is named "SACS.Dat", however the user can specify the name of the file he or she wishes to trace using the data file name argument.

#### 7. Histogram Max. Index Arguments

SACS provides the user with two timing histograms. One provides timing analysis for read and write requests. The first histogram illustrates how many requests were completed during the designated time. The second histogram provides timing analysis for the number of times the cache waited to complete a particular task in the designated time. The maximum index for these histograms is the maximum number of time bins. Since there may be data out of the maximum index range, the last bin is used to total all events with times greater than or equal to the maximum index. The screen histogram maximum index is the number used for screen displays. The screen maximum histogram index has a default value of 4, which allows all displays to fit on a standard 80 column screen. However, if a Unix window is available, the designer may want to raisc this number to get more detailed displays. The file histogram maximum index is used for the output file generated by SACS. This file may have a much larger range because it does not have to be printed on a screen. The output file is compatible with MATLAB script files. This allows results to be read and processed by MATLAB for statistical analysis and plotting purposes.

#### IV. SACS DISPLAYS

#### A. TRACE DISPLAY

#### 1. Introduction

SACS includes a trace mode that allows users to monitor the behavior of the simulated cache and the implemented policies and scoreboarding techniques. The user may also need to debug any modifications made to SACS. The trace mode is also very useful in identifying any programming errors. The trace mode allows the designer to review the status of the cache at the end of each clock cycle. A trace display is shown in Figure 2.

Current Reque Address:	est: Read 2AF7	59 <b>F</b> 9			Time: Next Requ	est Ti	46 me: 49		
Size:	07				TOA:		49		
Cache Waiting	•				_				
Memory Waiti	-	-			Cache Hit	•	No		
Block Waiting	For: Memo:	ry Blo	ck Tra	nsfer	Buffer Hi	t:	No		
Set Block	Address V/	מ/ע כ	V/D	V/D					
00031 00124	25E379F0 0	0 0	0 0	1 0					
00125	2AF769F0 0	0 0	0 0	0 0					
00126	00000000	0 0	0 0	0 0					
00127	00000000 0	0 0	0 0	0 0					
Read Buffer	Address	Size	Req.	Block	Priority	Time :	Req.	Comp.	Tim
	2 <b>AF</b> 769 <b>F</b> 9	16	07	00125	00	7		53	
Write Buffer	Address	Size	Req.	Block	Priority	Time :	Req.	Comp.	Tim
	25 <b>E</b> 37A10	10	00	00000	11	5		58	
Block Buffer	Address	Size	Req.	Block	Priority	Time :	Req.	Соптр.	Tim
	2 <b>AF</b> 769 <b>F</b> 8	00	00	00125	00	7		53	
Next Command	Please [ T,	R, S,	C, G	<b>#</b> , <b>#</b> , <b>-#</b> ,	Help] >>>	נ			
		Fig	ure 2	Trace D	isplay				

#### 2. Currat Request Fields

The trace display contains the last CPU request, as well as the request address and size. SACS can only process requests that are contained within the same block. If a request spans across two or more blocks, then the request is split up into block size requests and processed separately.

#### 3. Cache Waiting For Field

Whatever is holding up the last CPU request is shown in the Cache Waiting For field. In Table 2, we can see all the things that the cache might have to wait for. If the cache is waiting for nothing, then the request has been satisfied. If the cache is waiting for a read or write cache request, then the cache is being accessed. If the cache is waiting for a memory request, then some part of the request must be retrieved from memory and the data is not available. If the request can not proceed because one of the buffers is full, then Cache Waiting For will indicate whether the request is waiting for the full read buffer or the full write buffer. Note that a read miss request may have to wait for dirty blocks to be written to memory, making it possible for a read request to wait on a full write buffer.

#### 4. Memory Waiting For Field

Memory Waiting For identifies which memory function is in progress.

When a new memory access begins, Memory Waiting For indicates whether it is a memory read request or a memory write request. Once the access of the first word is in progress, then Memory Waiting For will indicate either read access or write access. However, once the first word has been received, then Memory Waiting For will switch to indicate either a

read transfer or a write transfer. If a memory read request needs to begin and the block buffer is busy because it has not updated the cache from the last request, then *Memory Waiting For* will indicate cache update.

#### 5. Block Waiting For Field

Block Waiting For describes what the block buffer is doing. It will indicate memory block transfer when a memory read access or transfer is in progress. However, once the transfer is complete, the block buffer must update the cache. If the cache is busy, then Block Waiting For will indicate that it's waiting for cache access. When the cache is not busy and the cache update begins, then Block Waiting For will switch to indicate block cache transfer.

v	TABLE 2. VAIT FOR CONDITIONS	
Cache Wait For Conditions	Memory Wait For Conditions	Block Buffer Wait For Conditions
Nothing Read Cache Request Read Memory Request Write Cache Request Write Memory Request Full Read Buffer Full Write Buffer CPU Cache Access	Nothing Memory Read Request Memory Read Transfer Memory Write Request Memory Write Access Memory Write Transfer Cache Update	Nothing Memory Block Transfer Block Cache Access Block Cache Transfer

#### 6. Timing Data Fields

The trace display shown in Figure 2 includes a time field that indicates how many clock cycles have passed since the start of the run. The Next Request Time is the

time at which the CPU either has, or will make, another request. The TOA field indicates when the next memory word will arrive into the Block Buffer. However, if a write was in progress, this field would be a TOD field, and would indicate the time that the next word will leave the Write Buffer.

#### 7. Cache Hit and Buffer Hit Fields

The cache hit field indicates whether a request is a hit or not. The buffer hit for a read request indicates whether the data requested is in the *Block Buffer*. A buffer hit for a write request indicates that the *Write Buffer* needed to write the data to memory anyway. A buffer hit will only occur during a cache miss. Buffer hits allow the designer to determine how many times the scoreboarding was used during a run to avoid a memory access. However, the true measurement of a cache's performance is its average access time.

#### 8. Address Block Selection Display

During a trace run it is helpful to see the cache set that the request address got mapped to. This includes all the blocks that the cache had to work with to satisfy the request. If the request is a hit, the block that it hit on has to be in this set. If a block victim is chosen, it has to be chosen from this set.

#### 9. Buffer Displays

The contents of all the buffers are displayed so that the designer may see what the memory is working on. The *Request Size* is the number of bytes that have to be read in order for the current request to have all the data originally asked for. This number

might be reduced from the original request size if part of the data is in the cache or if *Block Buffer* is allowed to contribute data to the request. During the trace, the address, size, and request size will constantly change as CPU requests, and memory accesses and transfers. are made. The block field indicates which cache block the read data will be placed in. The priority field indicates the priority of the memory request. A zero priority indicates that the request is in progress. The next lowest number will be serviced next, unless a new memory request is made. If more than one request has the same priority number, then the read buffer will take priority. If the read buffer has more than one request with the same priority, then the priority will switch to FIFO.

#### 10. Time Required and Completion Time Fields

Every memory request has a *Time Required* to complete and a *Completion Time*. The *Time Required* to complete is the time that memory will have to service the request. The *Completion Time* is the time that the request is expected to be removed from the buffer.

#### 11. Next Command Please

The next command line includes a prompt for the user of all the available commands. Shown in Table 3 is a list of all the commands. In the following paragraphs, these commands are discussed in detail.

## TABLE 3. TRACE COMMANDS

Trace Display (T)
Results Display (R)
Stall Timing Display (S)
Cache Arguments Display (C)
Go To A Specific Time (G #)
Increment Time (#)
Decrement Time (-#)
Help (H)

#### B. RESULTS DISPLAY

The Results Display. shown in Figure 2, provides the user with the number of requests, cache hits, and buffer hits. The hit rates are a combination of both the cache hits and the buffer hits. The Request Time Histogram gives the number of requests that were completed in the prescribed time. The total amount of time spent on each request, and the average access times, are also displayed. As discussed previously, the average access time is the ultimate measure of cache performance.

			Requests I	reak Dow	n		
		mber	Number	Ишть	<b>e</b> r		
Request		of	of	of		Hit	Miss
Types	Req	wests	Cache Hits	Buffer	Hits	Rates	Rates
Read		4	1	1		50.00%	75.00%
Write		7	4	0		57.14%	42.86%
Total		11	5	1		54.55%	45.45%
		1	Request Tir	⊯ Histog	ram.		
			_	-			Ave Access
	Time=00	Time=01	Time=02	Time=03	Time>=04	Total	Time
Read	0	2	0	0	2	11	2.750000
Write	3	4	0	0	0	4	0.571429
Idle	0	21	0	0	0	21	
Next Command P	lease [ T	, R, S, C	C, G #, #,	-#, Help	} >>>□		
		-	gure 3 Re	. 5.	-		


#### C. STALL DISPLAY

The stall display provides the designer with an exact account of where the cache spent all its time. As shown in Figure 4, the stall time histogram lists all the events that the cache has ever waited for, and the number of times that the cache waited for an event within a designated period.

	St	all Time	Histogram	ı		
	Time=00	Time=01	Time=02	Time>=03	Total	
Nothing	4	0	1	3	21	
Read Cache Request	0	4	0	0	4	
Write Cache Request		4	0	0	4	
Read Memory Request	0	0	0	2	7	
Write Memory Request	. 0	0	0	0	0	
Full Read Burffer	0	0	0	0	0	
Full Write Buffer	0	0	0	0	0	
CPU Cache Access	0	0	0	0	0	
Next Command Please	[T, R, S	s, c, <b>G#</b> ,	#, -#, He	lp] >>>C		
	Fion	ire 4 Stal	ll Timina	Display		

#### D. CACHE ARGUMENTS DISPLAY

The cache arguments display allows the user to review the arguments used by the simulator. Figure 5 shows an example of the cache arguments display.



#### E. GO TO A SPECIFIC TIME

Because data traces are usually very long, SACS was given the ability to run to a specific time. This allows the user to begin a long trace and inspect the results after a reasonable amount of time. If the user is debugging SACS because of a modification or, God forbid, there is an original error in SACS, this command will allow the user to advance to the last time the error occurred. If the time specified is earlier than the current time, then

SACS will temporally turn off the trace, restart the run from the beginning, and stop at the desired time. Once SACS is at the desired time, it will turn the trace mode back on. To the user, it will appear that SACS went backwards. However, in fact, SACS can not run its simulations in reverse. Obviously, if the *Desired Time* is vary large, then this process could take a great deal of time.

#### F. INCREMENT TIME

Increment time allows the user to adjust the time using a relative step size instead of an absolute desired time.

#### G. DECREMENT TIME

Decrement time allows the user to adjust the time using a relative step size instead of an absolute desired time. Again, SACS must restart the run from the beginning to stop at the desired time.

#### H. HELP DISPLAY

The help menu, shown in Figure 5, gives the user simple descriptions of what all the trace commands can do.

#### Help Menu

- [T] Trace Display: Displays current request, status of memory, and contents of buffers.
- [R] Results Display Displays a break down of read and write cache hits, and buffer hits, including a timing analysis.
- [S] Stall Timing Display:
  Displays histogram of the time spent on each stall. Stalls represent time delays in completing a request.
- [C] Cache Arguments Display: Display input arguments to SACS.

Go to end of run. Go to Time #. [G] Go:

[G #] Go To:

[#] Step: Increment Time By #. [-#] Back Step: Decrement Time By #. (H) Help: Displays this help menu.

Next Command Please [T, R, S, C, G #, #, -#, Help] >>>□

#### Figure 5 Help Display

#### V. SACS DESIGN

#### A. OVERALL STRUCTURE OF SACS

SACS simulates all events one clock cycle at a time using a global variable named *Time*. Normally, it is preferable to perform timing simulations using event queues so that time can advance to the next event. However, in most cache simulations, so many events happen in one clock cycle that an event queue would probably not improve the performance of the simulator.

#### B. MAIN EVENT LOOP

In the main event loop of SACS, *Time* is incremented one clock cycle at a time.

Time is never changed by any other procedure. The requests are entered into the simulation from Get Next Request. Simulation of all events is performed by the Main Event Loop calling Cache Model, Memory Model, and Update Cache.

SACS insures that all events that can be started during a particular clock cycle are started, and that all events that can complete during a particular clock cycle do. CPU accesses to the cache are given priority over the block buffer cache updates.

SACS's main loop includes the source code to control testing, checking, and tracing. The *Desired Time* variable is controlled entirely by the *Main Event Loop*. *Desired Time* represents a user request to advance the simulation to a particular time with the trace off. SACS can not run *Time* backwards. However, if the *Desired Time* is less than *Time*,

then *Time* is reset back to zero and the run is repeated up to the *Desired Time*. The user can make time requests using arguments "G #", "#", or "-#".

Nothing. This indicates that the last request has been serviced and that the cache is ready for the next request. The procedures that model specific events as Read Hit, Read Miss, and Access Cache are called repeatedly during their simulations. They utilize Cache Waiting For and Time to determine what to do next. If any of these procedures need to wait for a period, either to simulate an access or because a resource is not available, then they will set Cache Waiting For to the appropriate value. The modeling procedures in Memory Model work the same way using Memory Waiting For.

Whenever SACS finds an error or a discrepancy then the boolean variable

Discrepancy Found is set to Yes. This forces SACS into a trace mode so that the user may try to identify the cause of the error. In test mode, a discrepancy forces SACS out of test mode so that the trace file that caused the error is not erased by a new file.

#### C. CACHE MODEL

Cache Model makes all the necessary calls to simulate cache memory. Cache Model decides which calls to make based on the values of Cache Hit and Request. This function is called every time Time is incremented. If there are no read or write requests waiting to be completed, the function does nothing. The value of Cache Hit will remain Unknown until the appropriate cache access time has expired. Then, Cache Model will call Is Request A Hit to determine if the request is a hit or a miss.

#### 1. Is Request A Hit

Is Request A Hit determines if the request is a hit or a miss, and sets Cache

Hit to the appropriate value. Is Request A Hit will find the Set Number that the data is

supposed to be in. Then, all Cache Block Addresses in that set will be checked to see if

they equal the Block Address for that request. If the correct block is found, then all sub

blocks that are required to satisfy the request will be inspected for validity. If they are valid
then Cache Hit will equal Yes.

#### 2. Read Hit

Read Hit is called to simulate a cache hit during a read request. Read Hit simply finishes simulating the cache access for the hit. Read Cache Hit Time is the time required to send the data from the cache to the CPU. Note that the time to locate the block in the cache is simulated in Cache Model. Read Hit is called repeatedly while Time is incremented until Access Cache returns with Cache Waiting For equal to Nothing. Access Cache will return Cache Waiting For equal to Read Cache Request until the Read Cache Hit Time has expired.

#### 3. Read Miss

Read Miss is called to simulate a cache miss during a read request. Read Miss first simulates the time it would take to perform all the block management for a read miss. This time is called Read Cache Miss Time. Once that time has expired, Read Miss will call Select Block Victim to pick a block in the set. When Select Block Victim returns

with Cache Waiting For equal to Nothing the Request Block Number will contain the new block number where the data will be placed.

Once the new block has been chosen, Read Miss will call Add To Read Buffer. If Read Forward is selected, then Required Size for the memory request will be equal to the Request Size. However, if it is not, then Required Size for the memory request will equal Block Size. The Required Size in read memory request tells the Memory Model how much of the requested data must be read into the Block Buffer before resetting Cache Waiting For back to Nothing. By setting Required Size equal to Block Size, Read Miss is forcing Memory Model to read in the entire block before setting Cache Waiting For back to Nothing. Once the Memory Model has received the data, it is assumed to be available to the CPU during that clock cycle.

#### 4. Write Hit

Write Hit is called to simulate a cache hit during a write request. Write Hit will first simulate the time to write the data to the Request Block Number in the cache. The time to locate the block was simulated by Cache Model. Once Write Cache Hit Time has expired then Write Hit will perform the block management for the request. The block management is dictated by the Write Policy. For a Write Back policy, the sub blocks written to must have their dirty bits set. This is done by Set Dirty Bit. For a Write Through policy, the memory request must be entered into the write buffer. This is done by Add To Write Buffer.

#### 5. Write Miss

Write Miss is called to simulate a cache miss during a write request. Write Miss will first simulate the time needed to make all memory requests. This time is called Write Cache Miss Time. This is only the time required to make the requests, not the time required to complete them. The time to determine that the correct block was not in the cache memory was simulated by Cache Model. The memory requests are entered into the buffers after the Write Cache Miss Time expires. The memory requests are dictated by the Write Miss Policy. The simplest policy is Write Around. For a Write Around policy, the write data is placed in the Write Buffer by Add To Write Buffer. Write Allocate, however, is the toughest simulation in SACS. Write Miss must first choose a block to put the new data in. This is done by Select Block Victim. Block data not provided by the write request has to be read in. This read request is made by Add To Read Buffer. The read address is calculated by adding the request size to the address. Because new address may be in the next block, the Block Size may have to be subtracted to make the addition modulo. Sub blocks that were written to in there entirety will have there valid bits set to reflect the presence of the data provided by the CPU. However, if only part of a sub block was written to, then the Cache Valid Bit will not be set.

Write Miss uses the Write Policy to dictate how the write data is to update the memory. For a Write Back policy, dirty bits are set by Set Dirty Bits. For a Write Through, the data is added to the Write Buffer by Add To Write Buffer.

#### 6. Access Cache

Access Cache is called to simulate the CPU accessing the cache. Access Cache first waits for the cache not to be busy. The only reason it could be busy is if the Block Buffer is in the process of updating the cache. During this time, Access Cache will return Cache Waiting For equal to CPU Cache Access. Once the cache is not busy then Cache Busy is set to Yes. locking out the Block Buffer from accessing the cache. Then, Cache Waiting For will be set equal to Waiting For Request. This is a local variable passed by the caller. It will either be equal to Read Cache Access or Write Cache Access. Then, Cache Busy is set for the time specified by Request Time. Request Time is a local variable. It could equal any of the hit, miss, or access times. Once Request Time has expired then Access Cache will set Cache Busy equal to No, and Cache Waiting For equal to Nothing.

#### 7. Select Block Victim

Select Block Victim chooses the next block to be used and writes the dirty sub blocks out to the Write Buffer. Select Block Victim first surveys the cache set that the Request Address maps to. The survey includes finding the block that was least recently accessed. This Block Number is stored in LRUBlock. Once the set has been surveyed then the Replacement Policy dictates how the block is chosen. For the LRU policy, Request Block Number is set equal to LRUBlock. For the FIFO policy, Cache Next Block keeps track of the next victim block for each set. Cache Next Block is initialized to all zeros during the beginning of a run. Therefore, it must be checked to see if it is between the first

and last blocks for the set. If it is not, then Cache Next Block for Set Number is reset to

First Block. Once Select Block Victim knows it has a valid Cache Next Block then Request

Block is set equal to it. Then, Cache Next Block for the Set Number is incremented. For

RAND policy, the block number is chosen randomly from all the blocks in the set.

Select Block Victim writes all dirty sub blocks to the write buffer using Write Dirty Sub Blocks. Write Dirty Sub Blocks takes care of clearing the dirty and valid bits in the block. Once Select Block Victim is called and it gets to the bottom of the function with Cache Waiting For equal to Nothing, then the Cache Block Address for the Request Block Number is set equal to the block address of Request Address.

## 8. Set Dirty Bits

Set Dirty Bits sets the dirty bits for all sub blocks that contain data that was modified by a write request.

### 9. Write Dirty Sub Blocks

Write Dirty Sub Blocks is called to simulate writing all the dirty sub blocks in the Request Block. Write Dirty Sub Blocks not only clears all the dirty bits, it also clears all the valid bits. Write Dirty Sub Blocks prepares a block to receive new data, and is called after a block has been selected as a victim. Write Dirty Sub Blocks will search the block for consecutive dirty blocks and splice them together into one write request. The write request is then added to the Write Buffer. All of the sub blocks that make up the request will have their dirty and valid bits cleared. This process of searching and writing is repeated until all the bits are not dirty. Then, all the valid bits are cleared.

#### 10. Add To Read Buffer

Add To Read Buffer takes the elements of a request and adds the request to the *Read Buffer*. It will perform all of the searches and updates necessary to support the appropriate scoreboarding protocols.

Add To Read Buffer will begin by searching the cache and Block Buffer for each byte in the request, starting at the beginning of the request. Every time a byte is found in one or the other, the Address is incremented while Size and Required Size are decremented. This simulates removing the available data from the front of the request. Then, Add To Read Buffer will search the cache and Block Buffer for the data at the end of the request. Every time a byte is found, the Size of the request is decremented by one. If the byte was a required byte then the Required Size is also decremented. This simulates removing any data available from the end of the request. Add To Read Buffer is either left with a request that has a Size equal to zero or the end points are both needed from memory. If the Required Size is zero then the request is a buffer hit, otherwise the request is a buffer miss. If the request is already a cache hit then the buffer hit is for some block management request. These kinds of buffer hits are not recorded because it would confuse the Results Display by making it possible to get a hit rate greater than 100%. If the Size is not zero and Remove Read Duplicates is equal to No then the request is added to the end of the Read Buffer using Append. Append is a buffer utility that adds the request to the end of the buffer. The request must be added to the end of the buffer in order not to interfere with Memory Model, which may be in the middle of a memory read. If Remove Read

Duplicates is equal to Yes then the first byte in the request will be spliced into the Read Buffer.

Splice is another buffer utility. Splice will first search the Read Buffer for the byte. If it can't find a request in the buffer that contains the byte then it will search for a memory request that is getting data from the same block. If one is found then the request is modified to include the new read byte request. If no suitable request can be found then Splice will add a one byte request to the Read Buffer. The Address is then incremented while Size and Required Size are decremented. Then, the cache and Block Buffer are searched for the next byte. If it is not found then the next byte is spliced into the Read Buffer. This process is repeated until all of the bytes of the request have either been spliced into the Read Buffer or found.

The Buffer Hit is normally defined as when the data is available but not in the cache. However, in order to support the testing of SACS, the definition of a buffer hit is revised to mean that a request was found to have accrued recently, and that given time to complete all block management requested data would have been in the cache. This allows Test SACS to predict the hits of a test run without taking into account the time it takes to perform the block management.

Every time a request is spliced into the read or write buffers, the *Time To Execute* and *Completion Time Estimate* must be recalculated. The new time estimates are performed by *Calculate Time Estimates*.

### 11. Search Cache

Search Cache is called by Add To Read Buffer to find any parts of the request that may already be located in the cache. This must be done because if a read request follows a write request using a write allocate policy, then part of the read may be in the cache while the rest may still need to be read from memory. Search Cache checks all Cache Block Addresses in the cache set. If any of the cache block addresses equal the block address of the byte, then Search Cache checks the Cache Valid Bit for the sub block that the byte is located in. If the sub block is valid then Search Cache returns Yes.

#### 12. Add To Write Buffer

Add To Write Buffer adds one record to the write buffer. It also updates the Read Buffer if the Update Read Buffer argument is asserted. The process of updating the Read Buffer is simply changing the requests so that data made available by the write request is not requested from memory. Update Read Buffer should not be used unless the word and sub-block sizes are equal. This is because a write request may reduce a read request to where the read request will not be large enough to validate a sub-block. The write request may also be unable to set any valid bits because of sub-block alignment. The result is that a sub-block that was suppose to be read in is not.

### D. MEMORY MODEL

Memory Model makes all the necessary calls to simulate main memory. Memory

Model decides which calls to make based on Memory Waiting For. This function is called every time Time is incremented. If there are no read or write requests waiting to be

completed, the function does nothing. *Memory Model* contains a loop that forces the procedure to continue modeling until *TOA* and *TOD* are not equal to *Time*. This insures that if there are any events that occur in zero clock cycles then the next event is allowed to start.

Memory Model calls Select Memory Request to choose a request from either the read or the write buffers. Memory Model calls Start Reads and Start Writes to simulate accessing memory and receiving the first word of a memory request. Continue Reads and Continue Writes are then called to simulate the memory transfer of the following words of data.

# 1. Select Memory Request

Select Memory Request is called when memory is waiting for nothing.

Select Memory Request chooses a request from either the read or write buffers based on priority. The request is not returned however, and the request is left at the top of the buffer with its Priority set to zeros and Access In Progress set equal to Yes. If a request is found, then Memory Waiting For is set to Memory Read Request or Memory Write Request, depending on whether the request was found in the read or write buffer.

#### 2. Start Reads

Start Reads begins a read request, simulating the first word read from memory. The time to complete this read is called Memory Access Time. The Block Buffer is initialized in preparation to receive the new data words. If Block Waiting For is not equal to Nothing then Start Reads will have to wait before allowing the new memory read

request to start. If Start Reads does have to wait for the cache then Memory Waiting For is set equal to Cache Update, otherwise Memory Waiting For is set to Memory Read Access. The new block record is equal to the Read Buffer with its sizes set to zero. This gives the Block Memory Request the same block number as the Read Memory Request. The Address is aligned to Word Size. The Address must be aligned because the words read in will be aligned to Word Size. The new Block Memory Request is simply pushed onto the Block Buffer. Block Waiting For is set equal to Memory Block Transfer to indicate that data is being transferred from memory to the Block Buffer.

### 3. Continue Reads

Start Memory Reads. It simulates every read from memory other than the first word, which is simulated by Start Memory Reads. The time to complete each word transfer is equal to Memory Transfer Time. The block and read buffers are altered every time a word is read from memory. Once a request is complete, it is removed from the Read Buffer and Memory Waiting For is reset to Nothing. Block Waiting For is set to Block Cache Access in preparation to transfer the new data to the cache. If the Completion Time Estimate for the memory read request is not equal to Time then a time prediction error is raised.

## 4. Start Memory Writes

Start Memory Writes begins a memory write request, simulating the first word written to memory. The time to complete this one word write is called Memory Access Time. Memory Waiting For is set to Memory Write Access.

## 5. Continue Memory Writes

Start Memory Writes. Like Continue Memory Reads, it simulates every write to memory other than the first word, which is simulated by Start Memory Writes. The time to complete each word transfer is equal to Memory Transfer Time. The Write Buffer is altered every time a word is written to memory. Once the memory write request is complete, it is removed from the Write Buffer, and Memory Waiting For is reset to Nothing. If the Completion Time Estimate for the memory read request is not equal to Time when the request is completed then a time prediction error is raised.

## 6. Update Cache

Update Cache simulates entering data form the Block Buffer into the cache.

Update Cache first checks whether or not the cache is busy. If it is not, then Cache Busy is asserted and Block Waiting For is set equal to Block Cache Transfer. The Block TOA is calculated to enable Calculate Time Estimates to predict the completion times for additional memory read requests in the buffer. If the cache is busy then the previous memory request time completions may be wrong. That is because all of the last estimates counted on the old Block TOA. Therefore they all must be recalculated.

Once the Buffer Cache Access Time has expired then Block Waiting For is set equal to Nothing and the Cache Busy is deasserted. The read data must then be removed from the Block Buffer. The appropriate sub blocks in the cache will then have their dirty bits cleared and valid bits set.

# 7. Add A Word To Memory Request

Add A Word To Memory Request adds a word to a Memory Request as if it had been read in from memory. The address is first aligned to Word Size. Then, the size is incremented by Word Size. This simulates the data being added to the request.

#### 8. Remove A Word From Memory Request

Remove A Word Form Memory Request removes a word from a Memory
Request as if it had been written to memory. A copy of the Address is first stored in Old
Address. Then, the Address is word aligned and incremented by Word Size. The Required
Size and Size are then decremented by the difference of the new Address and the Old
Address. Finally, if the Address is outside the range of the original block, then Address is
decremented by Block Size to simulate modulo addition. This simulates removing a word
from the memory request, taking into account word and block alignment constraints.

### E. TIME ESTIMATES

Time estimates are performed to provide a method of testing Cache Model, and Memory Model's handling of the read and write buffers. These two procedures are located in "TimeEst.c"

## 1. Update Time To Execute

Update Time To Execute calculates the time to complete a memory transfer given Memory Request. Memory Request could be a read or write request in a buffer.

Update Time To Execute changes the Time To Execute field to the new value. Time To Execute is calculated by first finding the number of Words To Be Transferred. If the

Memory Request is not being accessed then the Time To Execute is simply the Access Time plus the Transfer Time multiplied by one less than Words To Be Written. If the Memory Request is in progress then the new Time To Execute is dependent on TOA or TOD of the next word. Memory Waiting For dictates whether to use the TOA or TOD. If Memory Waiting For is equal to Cache Update then the request has not actually begun transferring data. Therefore, the Time To Execute can be calculated as if the read request is not in progress.

#### 2. Calculate Time Estimates

request in both the read and write buffers. This function is called whenever the Cache Model adds to the read or write buffers. Calculate Time Estimates must be called every time new data is entered into the buffers. This is because all previous estimates did not take into account the new data requested. Calculate Time Estimates first orders all entries in both the Read Buffer and the Write Buffer by priority. Then, Calculate Time Estimates steps though both buffers simultaneously, each time picking the request that has the highest priority and adding the time to execute to the Time Estimate. The Time Estimate becomes that requests Completion Time Estimate. This process is repeated until all requests have a new Completion Time Estimate. Time To Execute, for cache request, is updated before it is used to calculate the Time Estimate.

#### VI. PROGRAM VALIDATION

### A. TESTING SACS

Program validation was considered to be a paramount issue in designing and implementing SACS. The debugging techniques for SACS were engineered during the early planning phases, before any code was written. In fact, there was a great deal of energy spent trying to make SACS a general event simulator. Not only would this have made it easier for the user to alter the protocols, but more importantly, it would have been easier to test the program. It would have been easier because the number of different kinds of event transitions would have been less than the number of different cache argument permutations. This method was aborted because data that was stored in the cache and the buffers was completely different. Another problem that plagued this method was that the scoreboarding techniques were unique for each buffer. Having abandoned the previous method, and recognizing that SACS would have dozens of input parameters (37 to date), a great deal of concern developed over how the program could be tested. It was decided that hand testing would prove to be ineffective in eliminating most or all of the programming errors. Therefore, an automated testing routine was developed. The testing routine was incorporated into the source code of SACS and can be activated using the -test argument. When the program is in the test mode, it goes into an infinite loop generating pseudo-random load and store instructions. Each trace is processed using the same code as if the trace was generated by a designer. Each time a new trace run is executed, the input parameters are randomized. This testing method is the backbone of all other validation methods for SACS. Other error checking is performed during this process. However, the random trace and random argument testing is the best method to ensure that all lines of code in SACS get executed during the test phase of SACS. This prevents SACS from experiencing a catastrophic failure during an actual simulation because almost all instructions are executed during the testing phase. SACS tries to predict the number of read and write hits for each run. These predictions are compared to the number of cache and buffer hits if the input arguments are expected to make the cache and buffer hits reflect the predictions. An example of when the input arguments would make it impossible to predict a hit or a miss is when the rand block replacement policy is used. A block of data that has just been read into the cache may be selected as a victim. This makes it impossible to predict which blocks will be in the cache at the beginning of the next request. Another example is when a read forward policy is used and the block buffer is not searched. Data expected to be in the cache may be in the Block Buffer, or in the Read Buffer, waiting to complete the block transfer. This requires that the predicted hits only be compared when the block and read buffers are searched. It also requires that during the test mode, buffer hits will include the read buffer. Policies that can not be checked for predicted hits are allowed in the test because they can be checked for other things including the simple, yet important requirement that the program does not spontaneously abort.

The instructions that are randomly generated for a test trace are seeded from 64 test vectors. These test vectors each have 7 read or write instructions. The number of these vectors to be used to generate a trace is randomly chosen. The actual test vectors to be used are also randomly chosen. Each test vector is assigned a random set of block addresses. Each of the block addresses for a particular test vector will map to the same set in the cache. The actual data address for each request is formed by taking the block address and adding a random number such that the data address is still in the same block. The size is also chosen randomly in such a way that the request does not violate block alignment.

Once all the test instructions have been created, they are randomly shuffled in such a way that the final number of hits and misses will remain the same as predicted.

#### B. CHECKING COMPLETION TIME

The timing analysis of SACS is so important that it was decided that every timing test that could be performed would be performed. SACS simulates events based on the current time only because some events can be predicted, such as the time that a buffer request would be removed from a buffer. A good timing test would be to calculate the estimated time of completion. Then, check to see if that estimated time is the same as the time that the request is removed from the buffer. If they do not match then an error is indicated. This kind of error checking goes on during every run whether it's a test run or a user's run.

## C. CHECKING GLOBAL VARIABLES

SACS uses 82 global variables. Approximately half of the global variables are constant during a single run. These variables mostly represent input parameters, and although they are changed in between test runs, they remain constant for the rest of the trace run. SACS was written in C, a powerful language that permits the programmer to create some powerful and elusive bugs. Specifically, C allows assignments to be buried in logical expressions. This capability could easily result in altering input parameters instead of checking a parameters value. To avoid this kind of error and others like it, copies of all constant global variables are made before the beginning of the trace run. At the end of every simulated clock cycle these variables are compared to their original copies. If a discrepancy is found then an error is indicated.

Global variables that are not constant are also inspected. They are inspected to ensure that they are all within acceptable boundaries. These boundaries are not always constant. For example, histogram index and total time should always exceed Time.

#### VII. SAMPLE RUNS

### A. EXAMPLE SACS SIMULATION RUN

In the first simulation run for SACS the default parameters were used. This run will demonstrate a write allocation miss and a write through hit. This run will also demonstrate a read miss that takes advantage of removing duplicates, and how a write request can update the read buffer. Table 4 shows the trace data used for the simulation run.

T	Table 4 TRACE DATA FOR RUN						
Reduent Type	Request Address	Size	Time Until Next Request				
W	x00000100	4	1				
W	x00000108	н	l				
ľ	x00000104	با	1				

v Indicates a write request


The Request Type is either a read or a write request. Read requests are indicated with a lower case "r". Write requests are indicated with a lower case "w". The address is read as a long hexadecimal integer. The Request Size is a long unsigned decimal integer. It represents the size in bytes. Time Until Next Request is the time between when the CPU's current request is complete and when the CPU makes the next request. The simulation run was performed by loading the trace data from Table 4 into an ASCII data

file named "SACS.Dat". Then, SACS was started with the trace mode on. The first trace display that SACS produced is shown in Figure 6.

Current Requesc: Write Time: 00000100 Address: Next Request Time: Size: 04 Cache Waiting For: Write Cache Request Memory Waiting For: Nothing Cache Hit: Unknown Block Waiting For: Nothing Buffer Hit: Unknown Set Block Address V/D V/D V/D V/D 00016 00000 00000000 0 0 0 0 0 00000 00000000 0 0 0 0 0 0.0 00000 00000000 0 0 0 0 0 0 0 0 00000 000000000 0 0 0 0 0 Read Buffer Address Block Priority Time Req. Comp. Time Write Buffer Address Block Priority Comp. Time Block Buffer Address Size Req. Block Priority Time Req. Comp. Time Next Command Please [ T, R, S, C, G #, #, -#, Help] >>> Figure 6 Trace Display For Time=1

Figure 6 shows the status of SACS after the first clock cycle. The Cache Waiting For field shows that SACS is modeling the cache access. Memory Waiting For is Nothing because the cache does not know if the request is a hit or a miss. Block Waiting For is Nothing because no read requests have started. The Next Request Time indicates that the CPU will send another request at Time equal to 2. Cache Hit and Buffer Hit are Unknown because the cache block still has not been accessed. The request will be mapped to set number 16, block 64.

The trace display for *Time* equal to 2 is shown in Figure 7. This display shows that the CPU has made the second write request. Again, the *Cache Waiting For* indicates that the cache is accessing block 64. The *Memory Waiting For* indicates that memory is accessing the first word in memory for the last write request. The *TOD* indicates that the first word will be written to memory at *Time* equal to 5. Cache and buffer hits are again *Unknown* because block 64 has not been accessed. The set data indicates that the last write request at 100 validated the first sub block. The *Read Buffer* has the remaining data needed for block 64. The *Req*. field is the number of bytes required to satisfy the CPU request. None are required in this case because the data was only needed to fulfill a block management requirement. The *Write Buffer* shows the last write request. It also predicts that the memory write request will be complete at *Time* equal to 5.




The next display is for *Time* equal to 3, and is shown in Figure 8. This display shows that cache is still working on the last write request. *Cache Waiting For* still indicates *Write Cache Request* because the default for a write hit requires one clock cycle after the cache has been accessed to update the cache. The memory is still waiting for the memory access of the first write memory request. The *Next Request Time* indicates that the CPU is waiting for the cache to finish with the last write request.

Current Request: Write Address: 00000108 Next Request Time: 3 TOD: Size: 08 Cache Waiting For: Write Cache Request Memory Waiting For: Memory Write Access Cache Hit: Yes Block Waiting For: Nothing Buffer Hit: No Set Block Address V/D V/D V/D V/D 00000100 1 0 00016 00064 0 0 0 0 00065 00000000 0 0 0 0 0 0 0 0 00066 00000000 0 0 0 0 0 0 0 0 00067 00000000 0 0 0 0 0 0 Time Req. Read Buffer Address Size Block Req. Priority Comp. Time 00000104 12 00 00064 12 5 10 Write Buffer Address Time Req. Comp. Time Size Req. Block Priority 00000100 04 00 00000 00 Block Buffer Address Reg. Time Reg. Comp. Time Size Block Priority Next Command Please [ T, R, S, C, G #, #, -#, Help] >>> Figure 8 Trace Display For Time=3

Figure 9 shows the display for *Time* is equal to 4. The last write request has completed and the data provided by the rite request was placed in block 64. As a result, the last two sub blocks are valid. The data was also placed into the *Write Buffer*. At first, it seems as though the two write memory requests should have been combined. The

resulting request would have had an address of 108 and a size of 12. Because words are accessed in memory in modulo form, the data for the first sub block would have been accessed last. However, because the last memory write request was in progress, the request could not modify its starting address. Therefore, two different requests resulted, and the *Read Buffer's* memory request size has been reduced by 8 bytes. This is an example of updating the Read Buffer with write data. This scoreboarding policy is a default for SACS, and can be disabled. The result is that the read request does not have to



48

Figure 10 shows the trace display for Time equal to 5. The last read request has turned out to be a miss. The buffers were also no help. At first glance, it might seem as though the read buffer should have provided a buffer hit. This would have been true if SACS were in a test mode. However, in a non test mode, the read buffer is not searched because the data is not really available. It still has to be read in from memory. The first write memory request starting at address 100 has completed, as predicted at *Time* equal to 5. The next memory request was chosen to be the write request because it had a high priority of 11, versus the read memory request with a priority of 12. Unfortunately, the request began before the cache could raise the priority to 10. Once the write request began, the priority went to 0 to prevent interruption.

Current Request: Read Time: Address: 00000104 Next Request Time: Size: 02 TOD: Cache Waiting For: Read Memory Request Memory Waiting For: Memory Write Access Cache Hit: No Block Waiting For: Nothing Buffer Hit: No Set Block Address V/D V/D V/D V/D 00016 00064 00000100 1 0 0 0 1 0 1 0 00000000 0 0 0 0 00065 0 0 00000000 0 0 0 0 0 0 00066 0 0 00067 00000000 0 0 0 0 0 0 0 0 Time Req. Read Buffer Req. Address Size Block Priority Comp. Time 00000104 04 02 00064 10 3 12 Write Buffer Address Size Req. Block Priority Time Req. Comp. Time 00000108 08 00 00000 00 Block Buffer Address Block Time Req. Comp. Time Req. Priority Next Command Please [ T, R, S, C, G #, #, -#, Help] >>> Figure 10 Trace Display For Run #1, Time=5

From the *TOD* in Figure 10, it is obvious that little will happen until at least the first word is written to memory. The display trace for *Time* equal to 8, when the first word is written to memory, is shown in Figure 11. It shows how SACS adjusts its buffers to represent individual words sent or received from memory. The *Memory Waiting For* switched to *Memory Write Transfer*, illustrating the transition from memory access to memory transfer. The *TOD* shows that the write will be complete at *Time* equal to 9, which is a lot better than the 3 clock cycles normally used to access memory.

Current Request: Read Time: Address: 00000104 Next Request Time: 10 Size: 02 TOD: Cache Waiting For: Read Memory Request Memory Waiting For: Memory Write Transfer Cache Hit: Block Waiting For: Nothing Buffer Hit: No Set Block Address V/D V/D V/D V/D 00016 00064 00000100 1 0 0 0 1 0 00065 00000000 0 0 0 0 0 0 0 00000000 0 0 0 0 0 0 00066 0 0 00067 0 0 00000000 0 0 0 0 0 Read Buffer Address Block Size Req. Priority Time Req. Comp. Time 00000104 04 02 00064 10 3 12 Write Buffer Address Size Req. Block Priority Time Req. Comp. Time 0000010C 04 00 00000 00 Block Buffer Address Time Req. Comp. Time Size Reg. Block Priority Next Command Please [ T, R, S, C, G #, #, -#, Help] >>>□ Figure 11 Trace Display For Time=8

Figure 12 shows the completion of the write memory request, and the beginning of the read memory request at Time equal to 9. The Block Buffer has also been prepared to receive the read memory data. The Block Waiting For indicates that the Block Buffer is busy receiving read data from memory. The TOA shows that Time 12 is when the read memory request will be complete.

Current Request: Read Time: Address: 00000104 Next Request Time: 11 Size: 02 TOD: Cache Waiting For: Read Memory Request Memory Waiting For: Memory Read Access Cache Hit: Block Waiting For: Memory Block Transfer Buffer Hit: No Set Block Address V/D V/D V/D V/D 00016 00064 00000100 1 0 0 0 00065 00000000 0 0 0 0 0 0 0 00066 00000000 0 0 0 0 0 0 0 00067 00000000 0 0 0 0 0 0 0 Read Buffer Address Size Req. Block Time Req. Priority Comp. Time 00000104 04 02 00064 10 3 12 Write Buffer Address Size Req. Block Priority Time Reg. Comp. Time Time Req. Comp. Time Block Buffer Address Size Req. Block Priority 00000104 00 00 00064 00 3 12 Next Command Please [ T, R, S, C, G #, #, -#, Help] >>> Figure 12 Trace Display For Time=9

Figure 13 shows the completion of the read memory request at Time equal to 12. The Cache Waiting For indicates Nothing because the request was satisfied when the required bytes arrived in the block buffer. The memory has nothing to do because both the read and the write buffers are empty. The simulation is not finished however, because the block buffer still has to update the cache with the new block data. *Block Waiting For* shows that the transfer is in progress.

Last Request: Read Time: 12 00000104 Address: Next Request Time: 02 Cache Waiting For: Nothing Memory Waiting For: Nothing Cache Hit: No Block Waiting For: Block Cache Transfer Buffer Hit: No Set Block Address V/D V/D V/D 00016 00064 00000100 1 0 0 0 1 0 1 0 00065 00000000 0 0 0 0 0 0 0 00066 00000000 0 0 0 0 0 0 0 00067 00000000 0 0 0 0 0 0 0 0 Read Buffer Address Size Block Priority Time Req. Comp. Time Write Buffer Address Time Req. Size Req. Block Priority Comp. Time Time Req. Comp. Time Block Buffer Address Size Req. Block Priority 00000104 00064 00 13 04 00 1 Next Command Please [ T, R, S, C, G #, #, -#, Help] >>> Figure 13 Trace Display For Time=12

Figure 14 shows the trace display for Time equal to 13. This display shows how the block buffer updated block 64. One word of data was provided at address 104, making the second sub block valid. Once the block transfer was completed, SACS removed the memory request from the block buffer.

Read Time: 13 Last Request: 00000104 Address: Next Request Time: Size: 02 Cache Waiting For: Nothing Cache Hit: Memory Waiting For: Nothing Unknown Block Waiting For: Nothing Buffer Hit: Unknown Set Block Address V/D V/D V/D V/D 00016 00064 00000100 1 0 1 0 1 0 1 0 00065 00000000 0 0 0 0 0 0 0 00066 00000000 0 0 0 0 0 0 0 0 00067 00000000 0 0 0 0 0 0 0 0 Read Buffer Address Block Priority Time Req. Comp. Time Write Buffer Address Block Time Req. Comp. Time Size Priority Block Buffer Address Block Time Req. Comp. Time Priority Next Command Please [ T, R, S, C, G #, #, -#, Help] >>>

Figure 14 Trace Display For Time=13

Figure 15 shows the results display. This display is always shown at the end of the run. It is interesting to note that even with the SACS default parameters, which lean toward providing the fastest response time to all CPU requests, the average access time for the one read miss was 8 clock cycles. Had this simulation been done with Dinero III, the user could only have assumed that a 2 byte read would have taken the memory access time of 3 clock cycles.

			Requests B	reak Dow	n		
	Nu	mber	ber Number		Number		
Request		of	o£	of		Hit	Miss
Types	Req	uests	Cache Hits	Buffer	Hits	Rates	Rates
Read		1	0	0		0.00%	100.00%
Write		2	1	0		50.00%	50.00%
Total		3	1	0		33.33%	66.67%
		3	Request Tim	m Histog	ram.		
							Ave Access
	Time=00	Time=01	Time=02	Time=03	Time>=04	Total	Time
Read	0	0	0	0	1	8	8.000000
Write	0	1	1	0	0	3	1.500000
Ideal	2	0	1	0	0	2	
Next Command P	lease [ T	, R, S, C	c, g #, #,	-#, Help	) >>>C		

#### VIII. CONCLUSION

For more than a decade, caches have been designed and built. Despite the time and effort spent on cache designs, there seems to be no one design that has emerged as the best cache design. Even the most basic choices, such as associativity, block size, and whether to use a unified cache or two separate data and instruction caches, has not been a clear choice, or at least the correct choice was not agreed upon by all concerned.

The diversity of cache designs has been caused by budget constraints, changing memory technology, and changing CPU bandwidth requirements. Without proper timing information, matching the correct cache to the architecture is more of an art than a science. SACS offers a powerful tool in the early planning phase of a cache design. Its large set of scoreboarding, block management, and cache memory arguments allow the designer to survey different designs quickly. SACS is well documented and provides the designer with a number of debugging tools, including self-testing and global variable bounds checking. This makes modifying SACS to simulate a unique design feature extremely easy compared to other programs.

As mentioned throughout this paper, the most critical aspect of SACS is its ability to provide the designer with the average access time. Since the ultimate purpose of the cache is to minimize the average access time, any simulator that does not provide this number can only hope to provide the designer with superficial and misleading data.

Future developments of SACS will include more elaborate timing information. The number of histograms will expand to include what the CPU, memory, and block buffer were waiting for during a run. A new stall histogram will be introduced that will allow the user to easily modify SACS to analyze any combination of conditions. For example, how many times does a read request wait for access to the cache memory while an old write miss request updates the allocated block. A new global variable will allow the user to change all the histogram displays to probability density tables.

### LIST OF REFERENCES

- 1. Patterson, D. A., and Hennessy, J. L., Computer Organization & Design The Hardware/Software Interface, p. 458-481, Morgan Kaufmann Publishers, Inc., 1994.
- Jouppi, N. P., "Cache Write Policies and Performance," Proceedings of the 20th Annual International Symposium on Computer Architecture, p. 191-201, May 1993.
- 3. Smith, A. J., "Cache Memories," *Computing Surveys*, vol. 14-3, p. 473-530, September 1982.
- 4. Hennessy, J. L., and Patterson, D. A., Computer Architecture, A Quantitative Approach, p. 403-425, Morgan Kaufmann Publishers, Inc., 1990.
- 5. Hill, M. D., and others, "Wisconsin Architectural Research Tool Set," Computer Architecture News. v. 21-4, p. 8-10, September 1993.

# **APPENDIX**

# **SOURCE CODE FOR SACS**

Page 1-0 \*\* SACS.h Part Of SACS 1.0 (StillAnother Cache Simulator) Program Modified: 3/17/94 3/17/94 File Modified: \*\* Author: William G. Smith Address: Electrical Engineering Department Naval Postgraduate School Monterey, CA 93940 \*\* Copyright 1994, William G. Smith \*\* Permission to use, copy, modify, and distribute this software and \*\* its documentation for any purpose and without fee is hereby granted \*\* provided that the above copyright notice appears in all copies. No modified version of this program should be redistributed without the \*\* \*\* authors consent. William G. Smith makes no warranty or representation, promise of guarantee, either expressed or implied, \*\* with respect to this software's ability to produce valid results. \* \* This program is provided "as is" any financial, personal or property \*\* damage caused by the use of this program is the responsibility of the \*\*

user.

\*\*

•

	Page 1- 1
	SACS.h
	Still Another Cache Simulator
	Still Another Cache Simulator
	Description:
	SACS.h defines all enumeration types. It Contains forward
	declarations of all functions used in SACS, (not just SACS.c). SACS.h
	also includes a list of all inline functions (macros).
	Table of Contents
•	Cover Page Page 1- 1
	Enumeration Definitions Page 1- 2
	Type Definitions Page 1- 4
	Inline Function Definitions
	SubBlock (Address) Page 1-5
	Set (Address) Page 1-5
	BlockAddress (Address) Page 1-5
	WordAddress(Address) Page 1-5
	SubBlockAddress (Address) Page 1-5
	·
	Complete List of Function Declarations within SACS
	SACS.c Page 1- 6
	Cache.c Page 1- 7
	Memory.c Page 1-8
	TimeEst.c Page 1- 9
	Get.c
	Display.c Page 1-11
	Record.c Page 1-12
	Buffer.c
	Array.c Page 1-14
	TestingSACS.c Page 1-15
	Checking.c

#ifndef \_\_CACHE.H

#define \_\_CACHE.H

#define ClearScreen "ClearScr"

```
Page 1-2 **
                             SACS.h
                                                              **
                      Enumeration Definitions
** Description:
                                                              **
       Listed below are the enumerations used in the SACS environment.
**
** WaitingForTypes, and MemoryWaitingForTypes are on listed on the
** following page.
*****************
enum YesNoTypes
                           No,
                           Yes,
                           Unknown
                           };
enum RequestTypes
                           None,
                           Read,
                           Write,
                           NumberOfRequestsAvailable
enum BlockReplacementPolicyTypes
                           LRU,
                           FIFO,
                           RAND,
                           NumberOfReplacementPoliciesAvailable
enum WritePolicyTypes
                           WriteThrough,
                           WriteBack,
                           NumberOfWritePoliciesAvailable
                           };
enum WriteMissPolicyTypes
                           WriteAround,
                           WriteAllocate,
                           NumberOfWriteMissPoliciesAvailable
                           };
```

```
Page 1- 3
                                  SACS.h
                          Enumeration Definitions
                                 continued
       *******************
enum CacheWaitingForTypes
                                Nothing,
                                CacheWaitingForReadCacheRequest,
                                CacheWaitingForWriteCacheRequest,
                                CacheWaitingForReadMemoryRequest,
                                CacheWaitingForWriteMemoryRequest,
                                CacheWaitingForFullReadBuffer,
                                CacheWaitingForFullWriteBuffer,
                                CacheWaitingForCPUCacheAccess,
                                NumberOfCacheWaitingForsAvailable
                                };
enum MemoryWaitingForTypes
                                NothingTwo,
                                MemoryWaitingForMemoryReadRequest,
                                MemoryWaitingForMemoryReadAccess,
                                MemoryWaitingForMemoryReadTransfer,
                                MemoryWaitingForMemoryWriteRequest,
                                MemoryWaitingForMemoryWriteAccess,
                                MemoryWaitingForMemoryWriteTransfer,
                                MemoryWaitingForCacheUpdate,
                                NumberOfMemoryWaitingForsAvailable
                                };
enum BlockWaitingForTypes
                                NothingThree,
                                MemoryBlockTransfer,
                                BlockCacheAccess.
                                BlockCacheTransfer,
                                NumberOfBlockWaitingForsAvailable
                                 };
```

\*\*\*\*\*\*\*\*\*

---

```
Page 1- 4
                                  SACS.h
                             Type Definitions
  Description:
        These are all of the type definitions used in the SACS
   environment, excluding enumeration types which are listed on the last
   two pages.
           **********
typedef unsigned long int TimeType;
typedef unsigned long int ScoreType;
typedef unsigned long int AddressType;
typedef unsigned long int CacheSizeType;
typedef unsigned int SizeType;
typedef unsigned
                   int BufferSizeType;
typedef unsigned
                   int PriorityType;
typedef unsigned
                   int AssociativityType;
typedef unsigned
                   int HistogramIndexType;
typedef enum YesNoTypes
                                       YesNoType;
typedef enum RequestTypes
                                       RequestType;
typedef enum BlockReplacementPolicyTypes BlockReplacementPolicyType;
typedef enum WriteMissPolicyTypes WriteMissPolicyType;
typedef enum WritePolicyTypes
                                       WritePolicyType;
typedef enum CacheWaitingForTypes
                                      CacheWaitingForType;
typedef enum MemoryWaitingForTypes
                                      MemoryWaitingForType;
typedef enum BlockWaitingForTypes
                                      BlockWaitingForType;
struct MemoryRequestStructType
  AddressType
               Address;
  SizeType
               Size;
              RequiredSize;
  SizeType
  SizeType
              Block;
  PriorityType Priority;
  YesNoType
              AccessInProgress;
                TimeToExecute;
  TimeType
                CompletionTimeEstimate;
  TimeType
typedef struct MemoryRequestStructType MemoryRequestType;
struct BufferStructType
                     MemoryRequest[10];
  MemoryRequestType
  YesNoType
                      Full;
  YesNoType
                     Empty;
  BufferSizeType
                      Next;
  BufferSizeType
  CacheWaitingForType WaitingForFlag;
typedef struct BufferStructType BufferType;
```

/*************************************	**************************************	1- 5	**
**	SACS.h	_ •	**
**			**
** Inline:		**	
**			**
** Description:			**
**			**
** These macros act as inl	ine functions. They are the only		**
** macros which act as inline f	unctions within the SACS environment,		**
** except those located in "Tes	tSACS.c".		**
**			**
********	**********	****	***/
#define SubBlock (Address)	(((Address)%BlockSize)/SubBlockSize)		
#define Set(Address)	(((Address)/BlockSize)%NumberOfSets)		
#define BlockAddress(Address)	(((Address)/BlockSize)*BlockSize)		
#define WordAddress(Address)	(((Address)/WordSize)*WordSize)		
	(((Address)/SubBlockSize)*SubBlockSiz	۵)	

.

```
/***********************
**
                                                    Page 1-6 **
                              SACS.h
                                                               **
                 List of SACS.c Function Declarations
** Description:
      This is a list of function declarations within the file scope
** of "SACS.c".
/* Page 2- 8 */
/* Page 2-11 */
/* Page 2-14 */
extern int extern void
extern int
                   main();
LoadArguments();
                                             /* Page 2-15 */
                      InitializeBuffers();
                                                  /* Page 2-16 */
extern void
                                                 /* Page 2-10 */
/* Page 2-18 */
/* Page 2-19 */
/* Page 2-20 */
/* Page 2-21 */
/* Page 2-23 */
                      DefineArrays();
extern void
extern void
                      FreeArrays();
extern void
                     OpenDataFile();
                     CloseDataFile();
PauseForCommand();
Pause();
extern void
extern void
extern void
```

```
Page 1-7 **
**
                          SACS.h
                                                     . **
**
                                                       **
**
              List of Cache.c Function Declarations
++
** Description:
**
**
      This is a list of function declarations within the file scope
                                                       **
** of "Cache.c".
                                                       **
                                                       ++
CacheModel();
extern void
                                             /* Page 4-3 */
             IsRequestAHit();
extern void
                                             /* Page 4-4 */
                                             /* Page 4-5 */
extern void
             ReadHit();
extern void
             ReadMiss();
                                             /* Page 4-6 */
extern void
             WriteHit();
                                             /* Page 4-7 */
extern void
             WriteMiss();
                                             /* Page 4-8 */
                                             /* Page 4-10 */
extern void
             AccessCache();
/* Page 4-11 */
                                             /* Page 4-13 */
                                             /* Page 4-14 */
                                             /* Page 4-16 */
                                             /* Page 4-20 */
extern YesNoType SearchCache();
extern void AddToWriteBuffer();
                                             /* Page 4-21 */
```

```
/****************************
**
                                                    Page 1-8 **
                              SACS.h
**
                                                                **
               List of Memory.c Function Declarations
** Description:
       This is a list of function declarations within the file scope
** of Memory.c
                                                                **
/* Page 5- 3 */
extern void MemoryModel();
extern void SelectMemoryRequest();
                                                    /* Page 5- 4 */
extern void StartMemoryReads();
                                                    /* Page 5-5 */
extern void ContinueMemoryReads();
                                                   /* Page 5-6 */
extern void StartMemoryWrites();
extern void ContinueMemoryWrites();
                                                   /* Page 5-8 */
                                                   /* Page 5-9 */
extern void UpdateCache();
                                                   /* Page 5-11 */
extern void AddAWordToMemoryRequest();
                                                   /* Page 5-13 */
extern void RemoveAWordFromMemoryRequest();
                                                   /* Page 5-14 */
```

```
/*************************************
**
                                                                                                                          Page 1-11 **
**
                                                                     SACS.h
                                                                                                                                                **
**
**
                                  List of Display.c Function Declarations
** Description:
**
                 This is a list of function declarations within the file scope
** of "Display.c".
 ***********************
                           DisplayTrace();
                                                                                                                      /* Page 8-3 */
extern void
                                                                                                                     /* Page 8-4 */
                                   DisplayCurrentRequest();
extern void
                                    DisplayWaitingFors();
                                                                                                                     /* Page 8-5 */
extern void
                                                                                                                    /* Page 8- 6 */
/* Page 8- 7 */
/* Page 8- 8 */
                                    DisplayBlock();
extern void
extern void
                                     DisplayBuffers();
                                            DisplayBuffer();
extern void
extern void DisplayRequestsBreakDown();
                                                                                                                    /* Page 8- 9 */
                                      DisplayRequestHistogram();
extern void
                                                                                                                    /* Page 8-11 */
extern void DisplayStallHistogram();
                                                                                                                    /* Page 8-13 */
extern ScoreType
                                    LastScreenHistogramScore();
                                                                                                                    /* Page 8-14 */
extern void DisplayCacheArguments();
                                                                                                                     /* Page 8-15 */
extern void
                                DisplayHelp();
                                                                                                                     /* Page 8-17 */
extern void
                               DisplayTestingHeader();
                                                                                                                      /* Page 8-18 */
                                                                                                                      /* Page 8-19 */
extern void
                              PrintYesNo();
extern void
                                                                                                                     /* Page 8-19 */
                                                                                                                     /* Page 8-19 */
extern void PrintTime();
extern void PrintTimeCentered();
extern void PrintScoreCentered();
extern void PrintAddress();
extern void PrintCacheSize();
extern void PrintSize();
extern void PrintSize2();
extern void PrintBufferSize();
extern void PrintPriority();
extern void PrintAssociativity();
extern void PrintHistogramIndex();
                                                                                                                      /* Page 8-20 */
                                                                                                                     /* Page 8-20 */
/* Page 8-20 */
/* Page 8-20 */
                                                                                                                      /* Page 8-20 */
                                                                                                                      /* Page 8-20 */
                                                                                                                      /* Page 8-20 */
                                                                                                                      /* Page 8-21 */
                                                                                                                      /* Page 8-21 */
                                                                                                                      /* Page 8-21 */
                                                                                                                      /* Page 8-21 */
extern void
                                                                                                                      /* Page 8-22 */
                              PrintBit();
extern void extern void
                              PrintPercent();
                                                                                                                      /* Page 8-22 */
                                                                                                                       /* Page 8-22 */
                               PrintAwcAccess();
```

٠.

```
Page 1-13 **
                             SACS, h
                List of Buffer.c Function Declarations
                                                              **
** Description:
       This is a list of functions declarations within the file scope
  of "Buffer.c".
                                                              **
                                                              **
extern void
                    Push();
                                                   /* Page 10- 3 */
                                                  /* Page 10- 4 */
extern MemoryRequestType Pop();
                                                  /* Page 10- 5 */
extern void extern void
                    ChangeTopMemoryRequest();
                                                  /* Page 10- 6 */
                   Append();
extern MemoryRequestType View();
                                                  /* Page 10- 7 */
            Clear();
extern void
                                                  /* Page 10- 8 */
extern void extern void
                   Order();
                                                  /* Page 10- 9 */
                  Splice();
Search();
UpdatingReadBuffer();
                                                  /* Page 10-10 */
                                                  /* Page 10-12 */
extern YesNoType
                                                  /* Page 10-13 */
extern YesNoType
                  RemoveZeroSizes();
NoRequestsLeft();
                                                  /* Page 10-15 */
extern void
                                                  /* Page 10-16 */
extern YesNoType
```

• •

```
/***********************
                                                     Page 1-14 **
                               SACS.h
                                                                 **
                 List of Array.c Function Declarations
** Description:
**
                                                                **
       This is a list of function declarations within the file scope
** of "Array.c".
                                                                 **
                                                                 **
extern int *DefineArray1D();
                                                     /* Page 11- 3 */
extern int **DefineArray2D();
                                                     /* Page 11- 4 */
extern void FreeArray1D();
                                                     /* Page 11- 5 */
                                                     /* Page 11- 6 */
extern void FreeArray2D();
```

\_

```
/***********************
**
                                            Page 1-15 **
                         SACS.h
**
            List of TestSACS.c Function Declarations
**
** Description:
**
     This is a list of functions declarations within the file scope
** of "TestSACS.c".
************************************
/* Page 12- 6 */
                                           /* Page 12- 8 */
/* Page 12- 8 */
/* Page 12-12 */
/* Page 12-14 */
/* Page 12-15 */
```

\_

```
/******************************
**
                                                                                          Page 1-16 **
                                                    SACS.h
                                                                                                              **
**
                            List of Checking.c Function Declarations
                                                                                                              **
                                                                                                            * **
** Description:
                                                                                                              **
**
                                                                                                              **
**
                                                                                                             **
             This is a list of function declarations within the file scope
** of "Checking.c".
                                                                                                             **
                                                                                                             **
**
/* Page 13- 3 */
extern void Checking();
extern void Checking();

extern void PrintConstError();

extern void CheckingForValuesOutOfBounds();

extern void PrintTimeBoundaryError();

extern void PrintScoreBoundaryError();

extern void PrintSizeBoundaryError();

extern void PrintEnumBoundaryError();

extern void CheckingForTaconsistencies();
                                                                                        /* Page 13- 4 */
                                                                                    /* Page 13-4 */
/* Page 13-11 */
/* Page 13-12 */
/* Page 13-15 */
/* Page 13-16 */
/* Page 13-17 */
/* Page 13-19 */
/* Page 13-21 */
/* Page 13-22 */
extern void CheckingForInconsistencies();
extern void PrintTotalTimeError();
extern void PrintTotalScoreError();
                                                                                        /* Page 13-22 */
                                                                                        /* Page 13-23 */
extern void CheckingPredictions();
                                                                                        /* Page 13-24 */
extern void PrintScorePredictionError();
                                                                                        /* Page 13-25 */
extern void PrintTimePredictionError();
```

#endif

\*\*\*\*\*\*\*\*\*\*\*\* Page 2- 0 SACS.c Part Of SACS 1.0 \*\* (StillAnother Cache Simulator) \*\* \*\* Program Modified: 3/17/94 \*\* File Modified: 3/17/94 \*\* \*\* Author: William G. Smith \*\* Address: Electrical Engineering Department \*\* Naval Postgraduate School \*\* \*\* \*\* Monterey, CA 93940 \*\* \*\* \*\* Copyright 1994, William G. Smith \*\* \*\* \*\* Permission to use, copy, modify, and distribute this software and \*\* its documentation for any purpose and without fee is hereby granted \*\* \*\* \*\* provided that the above copyright notice appears in all copies. No \*\* modified version of this program should be redistributed without the \*\* \*\* \*\* authors consent. William G. Smith makes no warranty or \*\* representation, promise of guarantee, either expressed or implied, \*\* with respect to this software's ability to produce valid results. \*\* \*\* This program is provided "as is" any financial, personal or property \*\* \*\* damage caused by the use of this program is the responsibility of the \*\* \*\* \*\* 

\_

\*\*

\* \*

\* \*

## SACS.c

## Still Another Cache Simulator

Description:

\*\*

\*\*

\*\* \*\*

> \* \* \* \*

SACS simulates all functions one clock cycle at a time using a \*\* global variable named Time. Normally it is preserred to preform timing \*\* simulations using event queues so that time can advance to the next event. However, in most cache simulations so many things happen in one \*\* clock cycle that en event queue would probably not improve the preformance of the simulator

In the main event loop of SACS, Time is incremented one clock \*\* cycle at a time. Time is never changed by any other procedure. \*\* The requests are entered into the simulation from GetNextRequest. Simulation of all events is performed by the Main Event Loop calling \*\* CacheModel, MemoryModel, and UpdateCache.

The main procedure of SACS seems to call simulations in a fairly strange order. This is because SACS is insuring that all events that can be started, during a particular clock cycle are started, and that all events that can bomplete during a particular clock cycle do. It also gives an inherent priority to the cache access events. Specifically accesses from the CPU to the cache are given higher priority that accesses from the BlockBuffer. This is why the Update Cache procedure is found in three different places in the main loop. \*\* Memory Model calls are found before and after the CacheModel. This allows memory events that are to complete during a clock cycle to do so. The Cache Model will then have the benefit of the newly arrived \*\* data. The MemoryModel call after the CacheModel call insures that any new memory request made by the cache are started that clock cycle.

SACS's main loop includes the source code to control testing, checking, and tracing. The DesiredTime variable is controlled entirely \*\* by the MainEventLoop. DesiredTime represents a user request to advance \*\* the simulation to a particular time without the trace on. SACS can not \*\* run Time backwards. However if the Desired Time. The user can make time requests using arguments "G #", "#", "-#".

Throughout MainEventLoop, CacheWaitingFor is checked to see if it's equal to Nothing. This indicates that the last request has been serviced and that the cache is ready for the next request. The procedures that model pecific events as ReadHit, ReadMiss, and AccessCache are called . Peatedly during their simulations they use Cache Waiting For and Time to determine what to do next. If any of these procedures needs to wait for a period either to simulate an access or because a resource is not available, then they will set Cache \*\* Waiting For to the appropriace value. The modeling procedures in Memory Model work the same way using Memory Waiting For.

Whenever SACS finds an error or a discrepancy then the boolean \*\* va jable Discrepancy Found is set to Yes. This forces SACS into a \*\* trace mode so that the user may try to identify the cause of the error. \*\* \*\* In test mode a discrepancy forces SACS out of test mode so that the \*\* trace file that caused the error is not erased by a new file.

/		
**	Page 2-2	*
* * * *	SACS.c	*1
**	Still Another Cache Simulator	# T
**	continued	*:
**	Concluded	* 1
**		*1
**	SACS.c contains the source code for main(), which contains the	*
**	main loop. All initialization of global variables, array definitions,	*
**	and file management are done inside "SACS.c".	* 1
**		Á.
**	For information on what SACS does see the User's Guide.	*
**		**
**	For information on how to run SACS see the User's Guide.	*
**	For information on how to modify SACS see the Programmer's Guide.	*
**	For information on now to modify sacs see the Frogrammer's Guide.	*
**	For information on how SACS works see the Programmer's Guide.	*
**		*
**	Table of Contents	*
**		*
**	Cover Page Page 2- 1	*
**	User Defined Global Variables Page 2-3	*
**	Programmer Defined Global Variables Page 2- 1	*
**	Enumerator Strings	*
**	List of SACS.c Function Declarations Page 2-7 main() Page 2-8	*
**	LoadArguments() Page 2-11	*
**	ScanArgument() Page 2-14	*
**	InitializeProgrammersGlobalVariables() . Page 2-15	*
**	InitializeBuffers() Page 2-16	*
**	DefineArrays() Page 2-17	*
**	FreeArrays() Page 2-18	*
**	OpenDataFile() Page 2-19	*
**	CloseDataFile() Page 2-20	*
**	PauseForCommand()	*
**	Pause() Page 2-23	*
		<b>₩</b> '

#include <stdlib.h>
#include <stdio.h>

#include "SACS.h"

```
Page 2-3 **
                                                                SACS.c
                                             User Defined Global Variables
 ** Description:
                These variables represent the programs input parameters.
**
**
 **************************
                                  CacheSize
BlockSize
SubBlockSize
Associativity
WordSize
CacheSizeType
SizeType
SizeType
                                                                                                                    /* -cs */
                                                                                        = 8192;
                                                                                     = 16;
= 4;
= 4;
= 4;
                                                                                                                    /* -bs */
/* -sbs */
AssociativityType
                                                                                                                     /* -a
                                                                                                                                        */
                                              WordSize
                                                                                                                      /* -ws */
SizeType

      ReadCacheAccessTime
      =
      1;
      /* -rcat */

      ReadCacheHitTime
      =
      0;
      /* -rcht */

      ReadCacheMissTime
      =
      0;
      /* -rcmt */

      WriteCacheAccessTime
      =
      1;
      /* -wcat */

      WriteCacheHitTime
      =
      1;
      /* -wcht */

      WriteCacheMissTime
      =
      0;
      /* -wcmt */

TimeType
TimeType
TimeType
TimeType
TimeType
TimeType
                                      MemoryAccessTime = 3;  /* -mat */
MemoryTransferTime = 1;  /* -mtt */
BufferCacheAccessTime = 1;  /* -bcat */
TimeType
TimeType
TimeType
BufferSizeType ReadBufferSize = 4;
BufferSizeType WriteBufferSize = 4;
                                                                                                                    /* -rbs */
                                                                                                                      /* -wbs */
BlockReplacementPolicyType BlockReplacementPolicy = LRU; /* -brp */
WritePolicyType WritePolicy = WriteThrough; /* -wp */
WriteMissPolicyType WriteMissPolicy = WriteAllocate;/* -wmp */
YesNoType ReadForward = Yes; /* -rf -drf */
YesNoType CPUWaitsForCacheWrites = No; /* -cwfcw -dcwfcw */
YesNoType SearchBlockBuffer = Yes; /* -sbb -dsbb */
YesNoType UpdateReadBuffer = Yes; /* -urb -durb */
YesNoType RemoveReadDuplicates = Yes; /* -rrd -drrd */
YesNoType RemoveWriteDuplicates = Yes; /* -rwd -drwd */
PriorityType ReadPriority = 1; /* -rpr
PriorityType WritePriority = 2; /* -wpr
PriorityType ReadForWriteAllocatePriority = 3; /* -rfwapr
PriorityType WriteDirtyBlockPriority = 4; /* -wdbpr
PriorityType NoPriority = 100; /* -npr
                                                                                   = No;  /* -t -dt */

= Yes;  /* -c -dc */

= No;  /* -test */
YesNoType Trace
YesNoType Check
 YesNoType
                                Test
                                                                                KeyBoardIO
 YesNoType
                               *DataFileName
HistogramIndexType ScreenHistogramMaxIndex = 5; /* -shmi
HistogramIndexType FileHistogramMaxIndex = 10; /* -fhmi
                                                                                                                                    */
```

```
/***********************
                                                               Page 2-4 **
                                    SACS.c
                                                                            **
                     Programmer Defined Global Variables.
TimeType
                     Time;
TimeType
                    DesiredTime;
CacheWaitingForType CacheWaitingFor;
MemoryWaitingForType MemoryWaitingFor;
BlockWaitingForType BlockWaitingFor;
                   DiscrepancyFound;
YesNoType
                   CacheHit;
YesNoType
YesNoType
                   BufferHit;
YesNoType
                   CacheBusy;
                  Request;
LastRequest;
RequestType
RequestType
                  RequestAddress;
RequestSize;
RequestBlockNumber;
AddressType
SizeType
SizeType
                     TimeOfNextRequest;
TimeType
SizeType
                  NumberOfBlocks;
NumberOfSubBloc
SizeType
                    NumberOfSubBlocks;
                   NumberOfSets;
SizeType
                   *CacheBlockAddress; /* [NumberOfBlocks]
AddressType
                                                                            */
                     *LastCacheBlockAccessTime;
TimeType
                                                                            */
                     *CacheNextBlock; /* [NumberOfSets]
SizeType
                                           /* [NumberOfBlocks]
                     **CacheValidBit;
YesNoType
                     **CacheDirtyBit;
                                           /* [NumberOfSubBlocks]
                                                                            */
YesNoType
                     **RequestTimeHistogram; /* [NumberOfRequestsAvailable] */
TimeType
                                             /* [FileHistogramMaxIndex]
                     **StallTimeHistogram; /* [NumberOfWaitingForsAvailable]*/
TimeType
                                         /* [FileHistogramMaxIndex]
                     *TotalRequestTime; /* [NumberOfRequestsAvailable] */
*TotalStallTime; /* [NumberOfWaitingForsAvailable] */
*NumberOfAccesses; /* [NumberOfRequestsAvailable] */
TimeType
TimeType
ScoreType
                     *NumberOfCacheHits;
ScoreType
                     *NumberOfBufferHits;
ScoreType
                    *PredictedNumberOfAccesses;
ScoreType
                    *PredictedNumberOfHits;
ScoreType
ScoreType
                     TotalNumberOfAccesses = 0; /* Not reset during test */
                     TotalNumberOfWordsReadFromMemory;
ScoreType
                     TotalNumberOfWordsWrittenToMemory;
ScoreType
ScoreType
                     TotalNumberOfWordsWrittenToCache;
BufferType
                     ReadBuffer;
BufferType
                     WriteBuffer;
BufferType
                     BlockBuffer;
AddressTyce
                     MAR;
TimeType
                     TOA;
TimeType
                     TOD;
TimeType
                     BlockTOA;
FILE
                     *DataFile;
YesNoType
                     EndOfDataFile;
```

```
Page 2- 5 **
                                    SACS.c
                      Programmer Defined Global Variables
                                  continued
**
                              Enumerator Strings
**
** Description:
**
**
        Enumerator strings are string copies of enumeration types. These **
** are used for display purposes.
char *YesNoString[3]=
      "No
      "Yes
      "Unknown"
      };
char *RequestString[NumberOfRequestsAvailable]=
      "None ",
      "Read "
      "Write"
char *ReplacementPolicyString[NumberOfReplacementPoliciesAvailable] =
      "LRU ".
      "FIFO",
      "RAND"
char *WritePolicyString[NumberOfWritePoliciesAvailable] =
      "Write Though",
      "Write Back "
char *WriteMissPolicyString[NumberOfWriteMissPoliciesAvailable] =
      "Write Around ",
      "Write Allocate"
      };
```

```
Page 2- 6 **
                                  SACS.c
                                                                        **
                    Programmer Defined Global Variables
                                continued
                            Enumerator Strings
                                continued
** Description:
         numerator strings are string copies of enumeration types. These **
** are used for display purposes.
*****************************
char *CacheWaitingForString[NumberOfCacheWaitingForsAvailable] =
     "Nothing
     "Read Cache Request ",
     "Write Cache Request ",
     "Read Memory Request ",
     "Write Memory Request",
     "Full Read Buffer
     "Full Write Buffer
     "CPU Cache Access
     };
char *MemoryWaitingForString[NumberOfMemoryWaitingForsAvailable] =
     "Nothing
     "Memory Read Request ",
     "Memory Read Access ",
     "Memory Read Transfer ",
     "Memory Write Request ",
     "Memory Write Access ",
     "Memory Write Transfer",
     "Cache Update
     };
char *ilcckWaitingForString[NumberOfBlockWaitingForsAvailable] =
     "Nothing
     "Memory Block Transfer",
     "Block Cache Access ",
     "Block Cache Transfer "
     };
```

```
/******************************
                                                                Page 2-7 **
**
                                     SACS.c
                                                                             **
**
                                                                              **
**
                    List of SACS.c Function Declarations
** Description:
                                                                              **
**
         This is a list of function declarations within the file scope
                                                                              **
** of "SACS.c".
                                                                              **
                                                                              **
/* Page 2-8 */
int
                 main();
void
                   LoadArguments();
                                                               /* Page 2-11 */
unsigned long int ScanArgument(); /* Page 2-14 */
void InitializeProgrammersGlobalVariables(); /* Page 2-15 */
void InitializeBuffers(); /* Page 2-16 */
                                                               /* Page 2-16 */
                   DefineArrays();
                                                              /* Page 2-17 */
void
                  FreeArrays();
OpenDataFile();
CloseDataFile();
PauseForCommand();
Pause();
                                                               /* Page 2-18 */
void
                                                              /* Page 2-19 */
void
                                                              /* Page 2-20 */
/* Page 2-21 */
/* Page 2-23 */
void
void
void
```

```
Page 2-8 **
                                     SACS.c
                                     main
                                                                             **
main(argc, argv)
   int argc;
   char *argv[];
   {
   LoadArguments (argc, argv);
   if (KeyBoardIO==No || Test==Yes) OpenDataFile();
   Time=0;
   while (Time==0 || Test==Yes)
      if (Test==Yes) ChangeArguments();
      InitializeProgrammersGlobalVariables();
      InitializeBuffers();
      DefineArrays();
      if (Test==Yes) TestSACS(PredictedNumberOfAccesses, PredictedNumberOfHits);
      RecordRequest (NumberOfRequestsAvailable); /* Reseting LastTimes */
      RecordStall(NumberOfCacheWaitingForsAvailable);
      CheckingConstants(Yes);
      GetNextRequest();
      CacheHit=Unknown;
      BufferHit=Unknown;
```

```
/**
* *
                                                               Page 2-9
                                   SACS.c
                                                                           **
                                                                           **
**
                                                                           **
                              Main Event Loop.
                                                                           **
        *********************
     while ((Request+CacheWaitingFor+MemoryWaitingFor>Nothing ||
             Time<=TimeOfNextRequest) &&
            DiscrepancyFound==No
                                      8.8
            Time>0
        {
        if (BlockWaitingFor==BlockCacheTransfer) UpdateCache();
        MemoryModel();
        CacheModel();
        if (BlockWaitingFor==BlockCacheAccess && BufferCacheAccessTime==0)
           UpdateCache();
        MemoryModel();
        RecordRequest (Request);
        if (CacheWaitingFor==Nothing) Request=None;
        RecordRequest (Request);
        RecordStall(CacheWaitingFor);
        if (Time==DesiredTime) { Trace=Yes; DesiredTime=0; }
         if (CacheWaitingFor!=Nothing &&
            ((CPUWaitsForCacheWrites && Request==Write) || Request==Read))
           TimeOfNextRequest++;
         if (Time>=TimeOfNextRequest && CacheWaitingFor==Nothing)
           GetNextRequest();
           CacheHit=Unknown; BufferHit=Unknown;
            if (Request==None)
              if (BlockWaitingFor==BlockCacheAccess) UpdateCache();
              Time++;
              RecordStall(CacheWaitingFor);
              RecordRequest (Request);
              Time--;
              if (Check) Checking();
              if (Trace) PauseForCommand();
              Time++;
        else
           if (BlockWaitingFor==BlockCacheAccess) UpdateCache();
           RecordStall(CacheWaitingFor);
           RecordRequest (Request);
           Time--;
            if (Check) Checking();
            if (Trace) PauseForCommand();
           Time++;
         if (Time>DesiredTime && DesiredTime!=0) Time=0;
```

```
/************************
                                                      Page 2-10 **
                               SACS.c
                       End Of Main Event Loop.
       ************************
     if (Test==Yes && DiscrepancyFound==No)
       CheckingPredictions();
       TotalNumberOfAccesses+=NumberOfAccesses[Read]
                          +NumberOfAccesses[Write];
       }
/*if (TotalNumberOfAccesses>=11270) {Trace=Yes; Test=No;}*/
     if (DiscrepancyFound==Yes)
       Pause();
       Trace=Yes;
       Test=No;
       DesiredTime=0;
       Time=0;
       }
     if (DiscrepancyFound==No && Test==No && Time!=0)
       DisplayRequestsBreakDown();
       RecordForMatlab();
    FreeArrays();
     rewind(DataFile);
     EndOfDataFile=No;
     }
  if (KeyBoardIO==No) CloseDataFile();
  return(0);
  }
```

```
**
                                                              Page 2-11 **
                                   SACS.c
                                                                          **
                                LoadArguments
                                                                          * *
                                                                          * *
   Description:
**
                                                                          **
**
        LoadArguments takes the argument list argv and changes the
                                                                          **
                                                                          **
   user defined global variables (See Page 2-3).
*************************
void LoadArguments(argc,argv)
  int argc;
  char *argv[];
  int i, j;
   for (i=1; i<argc; i++)
     {
      if (!(strcmp(argv[i],"-cs"
                                  )))
        CacheSize
                                  = ScanArgument(argv[++i]);
      if (!(strcmp(argv[i], "-bs"
                                  )))
                                  = ScanArgument(argv[++i]);
        BlockSize
      if (!(strcmp(argv[i], "-sbs"
                                  )))
        SubBlockSize
                                  = ScanArgument(argv[++i]);
      if (!(strcmp(argv[i],"-a"
                                  )))
                                  = ScanArgument(argv[++i]);
        Associativity
      if (!(strcmp(argv[i],"-ws"
                                  )))
        WordSize
                                  = ScanArgument (argv[++i]);
      if (!(strcmp(arqv[i], "-rcat")))
        ReadCacheAccessTime
                                 = ScanArgument(argv[++i]);
      if (!(strcmp(argv[i], "-rcht")))
        ReadCacheHitTime
                                  = ScanArgument(argv[++i]);
      if (!(strcmp(argv[i], "-rcmt")))
        ReadCacheMissTime
                                  = ScanArgument(argv[++i]);
      if (!(strcmp(argv[i], "-wcat")))
        WriteCacheAccessTime
                                 = ScanArgument(argv[++i]);
      if (!(strcmp(argv[i], "-wcht")))
         WriteCacheHitTime
                                  = ScanArgument (argv[++i]);
      if (!(strcmp(argv[i], "-wcmt")))
         WriteCacheMissTime
                                  = ScanArgument(argv[++i]);
      if (!(strcmp(argv[i], "-mat"
                                  )))
                                  = ScanArgument(argv[++i]);
        MemoryAccessTime
      if (!(strcmp(argv[i],"-mtt"))
                                  )))
        MemoryTransferTime
                                  = ScanArgument(argv[++i]);
      if (!(strcmp(argv[i], "-bcat")))
        BufferCacheAccessTime
                                  = ScanArgument(argv[++i]);
      if (!(strcmp(argv[i],"-rbs"))
        ReadBufferSize
                                  = ScanArgument(argv[++i]);
      if (!(strcmp(argv[i], "-wbs"
                                  )))
        WriteBufferSize
                                  = ScanArgument(argv[++i]);
```

```
/************************
                                                               Page 2-12 **
                                   SACS.c
                                                                           **
                                LoadArguments
                                                                           **
                                  Continued
                                                                           **
     if (!(strcmp(argv[i],"-brp")))
        BlockReplacementPolicy=-1;
        for (j=0; j<NumberOfReplacementPoliciesAvailable; j++)</pre>
           if (!(strcmp(argv[i],ReplacementPolicyString[j])))
              BlockReplacementPolicy=j;
        if (BlockReplacementPolicy<0)
           printf("Invalid Block Replacement Policy");
           exit(1);
           }
     if (!(strcmp(argv[i], "-wp")))
        WritePolicy=-1;
        for (j=0; j<NumberOfWritePoliciesAvailable; j++)</pre>
           if (!(strcmp(argv[i], WritePolicyString[j])))
              WritePolicy=j;
         if (WritePolicy<0)
           printf("Invalid Write Policy");
           exit(1);
         }
      if (!(strcmp(argv[i], "-wmp")))
        WriteMissPolicy=-1;
         for (j=0; j<NumberOfWriteMissPoliciesAvailable; j++)</pre>
            if (!(strcmp(argv[i], WriteMissPolicyString[j])))
              WriteMissPolicy=j;
         if (WriteMissPolicy<0)</pre>
           printf("Invalid Write Miss Policy");
           exit(1);
```

}

```
Page 2-13
                               SACS.c
                                                                         **
                            LoadArguments
                                                                         **
                              Continued
   ************
if (!(strcmp(argv[i],"-rf" ))) ReadForward
if (!(strcmp(argv[i],"-drf" ))) ReadForward
                                                            = Yes;
                                                            = No;
if (!(strcmp(argv[i], "-cwfcw" ))) CPUWaitsForCacheWrites = Yes;
if (!(strcmp(argv[i], "-dcwfcw"))) CPUWaitsForCacheWrites = No;
if (!(strcmp(argv[i], "-sbb" ))) SearchBlockBuffer = Yes;
if (!(strcmp(argv[i],"-dsbb" ))) SearchBlockBuffer
if (!(strcmp(argv[i],"-urb" ))) UpdateReadBuffer
                                                            = No;
                               ))) UpdateReadBuffer = Yes
))) UpdateReadBuffer = No;
                                                           = Yes;
if (!(strcmp(argv[i], "-durb"
if (!(strcmp(argv[i],"-rrd"
                               ))) RemoveReadDuplicates = Yes;
if (!(strcmp(argv[i],"-drrd"
                               ))) RemoveReadDuplicates = No;
if (!(strcmp(arqv[i], "-rwd"))
                               ))) RemoveWriteDuplicates = Yes;
if (!(strcmp(argv[i], "-drwd"))
                               ))) RemoveWriteDuplicates = No;
if (!(strcmp(argv[i], "-rpr"
                               )))
   ReadPriority
                                = ScanArgument(argv[++i]);
if (!(strcmp(argv[i], "-wpr"
                               )))
                                 = ScanArgument(argv[++i]);
   WritePriority
if (!(strcmp(argv[i], "-rfwapr")))
   ReadForWriteAllocatePriority = ScanArgument(argv[++i]);
if (!(strcmp(arqv[i], "-wdbpr")))
   WriteDirtyBlockPriority = ScanArgument(argv[++i]);
if (!(strcmp(argv[i],"-npr")))
   WriteDirtyBlockPriority = ScanArgument(argv[++i]);
if (!(strcmp(argv[i],"-t"))) Trace
                                                            = Yes;
if (!(strcmp(argv[i], "-dt" ))) Trace
if (!(strcmp(argv[i], "-c" ))) Check
if (!(strcmp(argv[i], "-dc" ))) Check
                                                            = No:
                                                           = Yes:
                                                            = No:
if (!(strcmp(argv[i], "-test"))) Test
                                                           = Yes;
if (!(strcmp(argv[i], "-kbio" ))) KeyBoardIO
                                                         = Yes;
if (!(strcmp(argv[i], "-fio" ))) KeyBoardIO
                                                          = No;
if (!(strcmp(argv[i],"-f" ))) DataFileName
                                                          = argv[++i];
if (!(strcmp(argv[i], "-shmi")))
   ScreenHistogramMaxIndex = ScanArgument(argv[++i]);
if (!(strcmp(argv[i],"-fhmi")))
   FileHistogramMaxIndex = ScanArgument(argv[++i]);
}
```

}

```
/***************************
                                                  Page 2-14 **
                            SACS.c
                         ScanArgument
** Description:
                                                              **
* *
       ScanArgument scans the input string for an unsigned long int,
                                                             **
** if one is not found an error is raised.
                                                              **
******************************
unsigned long int ScanArgument (Argument)
  char *Argument;
  unsigned long int Temp;
  if (sscanf(Argument, "%U", &Temp)!=1)
    printf("Error unsigned integer expected [%s].", Argument);
     };
  return (Temp);
  }
```

```
Page 2-15 **
                                   SACS.C
                                                                          **
                                                                          **
                     InitializeProgrammersGlobalVariables
                                                                          **
                                                                          * *
** Description:
                                                                          * *
**
        InitializeProgrammersGlobalVariables takes the user defined global **
** variables and calculates programmer defined global variables, which are **
** constant, once the input paramaters are determined, and reinitializes **
                                                                          **
** the global variables what will change.
**************************************
void InitializeProgrammersGlobalVariables()
   {
                                    = 1;
   Time
   CacheWaitingFor
                                   = Nothing;
  MemoryWaitingFor
                                   = Nothing;
  BlockWaitingFor
                                   = Nothing;
  DiscrepancyFound
                                   = No;
   CacheHit
                                   = Unknown;
                                   = Unknown;
   BufferHit
                                    = No;
   CacheBusy
  Request
                                    = None;
   LastRequest
                                    = None;
                                   = 0;
  RequestAddress
                                   = 0;
  RequestBlockNumber
                                   = 0;
   RequestSize
   RequestBlockNumber
                                    = 0;
                                    = 0;
   TimeOfNextRequest
   NumberOfBlocks
                                   = CacheSize/BlockSize;
   NumberOfSubBlocks
                                   = BlockSize/SubBlockSize;
   NumberOfSets
                                   = NumberOfBlocks/Associativity;
   TotalNumberOfWordsReadFromMemory = 0;
   TotalNumberOfWordsWrittenToMemory = 0;
   TotalNumberOfWordsWrittenToCache = 0;
   ReadsLeftForBlock
                                    = 0;
                                   = 0;
   ReadsLeftForRequest
   WritesLeftForBlock
                                   = 0;
   WritesLeftForRequest
                                    = 0;
*/
   MAR
                                    = 0;
   TOA
                                    = 0;
   TOD
                                    = 0;
   BlockTOA
                                    = 0;
   EndOfDataFile
                                    = No;
   }
```

```
/**********************************
                                                         Page 2-16 **
                                SACS.c
                           InitializeBuffers
** Description:
       InitializeBuffers places the buffers in an empty state, with
  their Max values set to the appropriate size.
                                                                    **
*****************************
void InitializeBuffers()
  {
  ReadBuffer.Full = No;
  ReadBuffer.Empty = Yes;
  ReadBuffer.Next = 0;
  WriteBuffer = ReadBuffer;
BlockBuffer = ReadBuffer;
  ReadBuffer.Max = ReadBufferSize-1;
  WriteBuffer.Max = WriteBufferSize-1;
  BlockBuffer.Max = 0;
  ReadBuffer.WaitingForFlag = CacheWaitingForFullReadBuffer;
  WriteBuffer.WaitingForFlag = CacheWaitingForFullWriteBuffer;
  BlockBuffer.WaitingForFlag = Nothing;
  ł
```

```
/*********************************
                                                              Page 2-17
                                   SACS.c
                                                                          **
                                DefineArrays
   Description:
        DefineArrays assigns memory to the array pointers.
        *************
void DefineArrays()
   {
  CacheBlockAddress
                             = (AddressType*)
                               DefineArraylD (NumberOfBlocks,
                                             sizeof(AddressType));
  TastCacheBlockAccessTime
                             = (rimeType*)
                               DefineArray1D (NumberOfBlocks,
                                             sizeof(TimeType));
  CacheNextBlock
                             = (SizeType*)
                               DefineArraylD (NumberOfSets,
                                             sizeof(SizeType));
  CacheValidBit
                             = (YesNoType**)
                               DefineArray2D (NumberOfBlocks,
                                             NumberOfSubBlocks,
                                             sizeof(YesNoType));
                             = (YesNoType**)
  CacheDirtyBit
                               DefineArray2D (NumberOfBlocks,
                                             NumberOfSubBlocks,
                                             sizeof(YesNoType));
  RequestTimeHistogram
                             = (TimeType**)
                               DefineArray2D (NumberOfRequestsAvailable,
                                             FileHistogramMaxIndex,
                                             sizeof(TimeType));
   StallTimeHistogram
                             = (TimeType**)
                               DefineArray2D (NumberOfCacheWaitingForsAvailable,
                                             FileHistogramMaxIndex,
                                             sizeof(TimeType));
   TotalRequestTime
                             = (TimeType*)
                               DefineArraylD(NumberOfRequestsAvailable,
                                             sizeof(TimeType));
   TotalStallTime
                             = (TimeType*)
                               DefineArraylD (NumberOfCacheWaitingForsAvailable,
                                             sizeof(TimeType));
   NumberOfAccesses
                             = (ScoreType*)
                               DefineArraylD (NumberOfkequestsAvailable,
                                             sizeof(ScoreType));
  NumberOfCacheHits
                             = (ScoreType*)
                               DefineArray1D (NumberOfRequestsAvailable,
                                             sizeof(ScoreType));
   NumberOfBufferHits
                                = (ScoreType* )
                               DefineArraylD(NumberOfRequestsAvailable,
                                             sizeof(ScoreType));
   PredictedNumberOfAccesses = (ScoreType* )
                               DefineArraylD (NumberOfRequestsAvailable,
                                             sizeof(ScoreType));
  PredictedNumberOfHits
                             = (ScoreType*)
                               DefineArraylD (NumberOfRequestsAvailable,
                                             sizeof(ScoreType));
   }
```

```
Page 2-18 **
                                  SACS.c
                                FreeArrays
   Description:
**
**
        FreeArrays deallocates the memory assigned to the array points
**
   by DefineArrays.
      **********
void FreeArrays()
char c;
  FreeArraylD(CacheBlockAddress,
                                      NumberOfBlocks);
   FreeArraylD(LastCacheBlockAccessTime, NumberOfBlocks);
   FreeArray1D(CacheNextBlock,
                                        NumberOfSets);
   FreeArray2D (CacheValidBit,
                                        NumberOfBlocks, NumberOfSubBlocks);
   FreeArray2D (CacheDirtyBit,
                                        NumberOfBlocks, NumberOfSubBlocks);
   FreeArray2D (RequestTimeHistogram,
                                        NumberOfRequestsAvailable,
                                        FileHistogramMaxIndex);
   FreeArray2D (StallTimeHistogram,
                                        NumberOfCacheWaitingForsAvailable,
                                        FileHistogramMaxIndex);
   FreeArray1D (TotalRequestTime,
                                        NumberOfRequestsAvailable);
   FreeArray1D (TotalStallTime,
                                        NumberOfCacheWaitingForsAvailable);
   FreeArray1D (NumberOfAccesses,
                                        NumberOfRequestsAvailable);
                                        NumberOfRequestsAvailable);
   FreeArraylD (NumberOfCacheHits,
   FreeArraylD (NumberOfBufferHits,
                                        NumberOfRequestsAvailable);
   FreeArray1D (PredictedNumberOfAccesses, NumberOfRequestsAvailable);
   FreeArray1D (PredictedNumberOfHits,
                                        NumberOfRequestsAvailable);
```

-

```
Page 2-19 **
                                     SACS.c
                                  OpenDataFile
    Description:
         OpenDataFile opens the file specified by DataFileName for
    reading. This becomes the data file that GetNextFileRequest reads
                                                                               **
void OpenDataFile()
   {
   if (Test==No)
      if ((DataFile=fopen(DataFileName, "r")) == NULL)
         printf("Cannot open %s file", DataFileName);
         exit(0);
   else
      if ((DataFile=fopen(DataFileName, "w+")) ==NULL)
         printf("Cannot open %s file", DataFileName);
         exit(0);
         }
      }
   }
```

```
**
                                                              Page 2-21 **
**
                                   SACS.c
**
                               PauseForCommand
   Description:
        PauseForCommand controles the displays. It takes input for the
   keyboard to determan which display to provide. It also adjusts the
   global variable Desired Time based on "#", "-#", and "G #" commands.
      **********************
void PauseForCommand()
   static char LastDisplayMode=' ';
   char
            InputString[255],
            *TmpStringPt,
           CommandChar,
           DisplayMode=' ';
   int
           Index;
   TimeType TmpTime;
   if (Trace==Yes) LastDisplayMode='t'; else LastDisplayMode='r';
  while (DisplayMode!=LastDisplayMode)
      1
      if (DisplayMode!=' ') LastDisplayMode=DisplayMode;
      DisplayMode=LastDisplayMode;
      if (LastDisplayMode=='t') DisplayTrace();
      if (LastDisplayMode=='r') DisplayRequestsBreakDown();
      if (LastDisplayMode=='s') DisplayStallHistogram();
      if (LastDisplayMode=='c') DisplayCacheArguments();
      if (LastDisplayMode=='h') DisplayHelp();
      printf("\nNext Command Please [ T, R, S, C, G #, #, -#, Help] >>>");
      Index=-1;
      do
         Index++:
         scanf("%c",&InputString[Index]);
                       while (InputString[Index]!='\n');
      while (InputString[0]==' ')
         for (Index=0; InputString[Index]!='\n'; Index++)
            InputString[Index]=InputString[Index+1];
      CommandChar=InputString[0];
      if (CommandChar>='A' && CommandChar<='Z') CommandChar+=('a'-'A');</pre>
```

```
Page 2-22 **
                              SACS.c
                          PauseForCommand
                             continued
if (sscanf(InputString, "%U", &TmpTime) == 1 && CommandChar!='\n')
  DesiredTime=Time+TmpTime;
   Trace=No;
if (CommandChar=='-')
   TmpStringPt=InputString;
   TmpStringPt++;
   if (sscanf(TmpStringPt,"%U",&TmpTime)==1) DesiredTime=Time-TmpTime;
   Trace=No;
if (CommandChar=='q')
   TmpStringPt=InputString;
   TmpStringPt++;
   if (sscanf(TmpStringPt, "%U", &TmpTime) == 1) DesiredTime=TmpTime;
   Trace=No;
   }
if (CommandChar=='t') DisplayMode='t';
if (CommandChar=='r') DisplayMode='r';
if (CommandChar=='s') DisplayMode='s';
if (CommandChar=='c') DisplayMode='c';
if (CommandChar=="h') DisplayMode='h';
if (CommandChar=='q') exit(0);
}
```

/\* Page 3-0 \*\* \*\* Global.h Part Of SACS 1.0 \*\* (StillAnother Cache Simulator) \*\* Program Modified: 3/17/94 \*\* File Modified: 3/17/94 \*\* \*\* Author: William G. Smith \*\* Address: Electrical Engineering Department \*\* \*\* Naval Postgraduate School \*\* \*\* Monterey, CA 93940 \*\* \*\* \* \* Copyright 1994, William G. Smith \*\* \* \* Permission to use, copy, modify, and distribute this software and \*\* \*\* its documentation for any purpose and without fee is hereby granted \*\* \*\* \*\* provided that the above copyright notice appears in all copies. No \*\* modified version of this program should be redistributed without the \*\* \*\* authors consent. William G. Smith makes no warranty or \*\* \*\* representation, promise of guarantee, either expressed or implied, \*\* with respect to this software's ability to produce valid results. \*\* \*\* This program is provided "as is" any financial, personal or property \*\* \*\* damage caused by the use of this program is the responsibility of the \*\* \*\* \*\*

\*

Page 3-1 \*\* Global.1. Global Variables Used by SACS Packages Description: \*\* Global.h is the only include file needed by all of the SACS source \*\* files. It contains all the global variables, both user and programmer \*\* defined variables. The user defined variables represent all the input \*\* \*\* parameters. The programmer defined variables represent all global \*\* \*\* variables that are shared between all the SACS source code files, that \*\* \*\* the user does not have access to. \*\* \*\* \*\* SACS.c defines all of the initial values of the global variables \*\* \*\* therefore, does not include Global.h \*\* \*\* \*\* Table of Contents Cover Page ..... Page 3-1 User Defined Global Variables ..... Page 3-2 Programmer Defined Global Variables ..... Page 3-3 

#ifndef \_\_GLOBAL.H
#define \_\_GLOBAL.H

#include <stdlib.h>
#include <stdio.h>

#include "SACS.h"

```
/**********************
                                                           Page 3-2 **
* *
                                Global.h
**
                      User Defined Global Variables
** Description:
          These variables represent the programs input parameters.
**
**********************
                               CacheSize;
extern CacheSizeType
                              BlockSize;
extern SizeType extern SizeType
                              SubBlockSize;
                             Associativity;
extern AssociativityType
                              WordSize;
extern SizeType
                              ReadCacheAccessTime;
extern TimeType
                              ReadCacheHitTime;
extern TimeType
                              ReadCacheMissTime;
extern TimeType
                              WriteCacheAccessTime;
WriteCacheHitTime;
extern TireType
extern TimeType
                               WriteCacheMissTime:
extern TimeType
                              MemoryAccessTime;
extern TimeType
                              MemoryTransferTime;
extern TimeType
                              BufferCacheAccessTime;
extern TimeType
                              ReadBufferSize;
extern BufferSizeType
                               WriteBufferSize;
extern BufferSizeType
extern BlockReplacementPolicyType BlockReplacementPolicy;
extern WritePolicyType WritePolicy;
extern WriteMissPolicyType
                              WriteMissPolicy;
                              ReadForward;
extern YesNoType
                              CPUWaitsForCacheWrites;
extern YesNoType
                              SearchBlockBuffer;
UpdateReadBuffer;
extern YesNoType
extern YesNoType
                              RemoveReadDuplicates;
extern YesNoType
                              RemoveWriteDuplicates;
extern YesNoType
                             ReadPriority;
extern PriorityType
                               WritePriority;
extern PriorityType
                              ReadForWriteAllocatePriority;
extern PriorityType
                               WriteDirtyBlockPriority;
extern PriorityType
extern PriorityType
                              NoPriority;
                               Trace;
extern YesNoType
                                Check;
extern YesNoType
extern YesNoType
                                Test;
extern YesNoType
                                KeyBoardIO;
                                *DataFileName;
extern char
                                ScreenHistogramMaxIndex;
extern HistogramIndexType
```

FileHistogramMaxIndex;

extern HistogramIndexType

```
* *
                                                                    Page 3-3 **
                                     Global.h
                      Programmer Defined Global Variables
        ********
extern TimeType
                             Time;
extern TimeType
                             DesiredTime;
extern CacheWaitingForType CacheWaitingFor;
extern MemoryWaitingForType MemoryWaitingFor;
extern BlockWaitingForType BlockWaitingFor;
extern YesNoType
                             DiscrepancyFound;
extern YesNoType
                      CacheHit;
extern YesNoType
                      BufferHit;
extern YesNoType
                      CacheBusy;
extern RequestType Request;
extern RequestType LastRequest;
extern AddressType RequestAddress;
extern SizeType RequestSize;
extern SizeType RequestBlock
extern TimeType TimeOfNextRe
                      RequestBlockNumber;
extern TimeType
                      TimeOfNextRequest;
extern SizeType
                      NumberOfBlocks;
extern SizeType extern SizeType
                      NumberOfSubBlocks;
                      NumberOfSets;
                      *CacheBlockAddress; /* [NumberOfBlocks]
extern AddressType
                                                                                 */
extern TimeType
extern SizeType
extern YesNoType
                      *LastCacheBlockAccessTime;
                      *CacheNextBlock; /* [NumberOfSets]
                                                                                 */
                      **CacheValidBit;
                                              /* [NumberOfBlocks]
                                                                                 * /
                      **CacheDirtyBit;
                                              /* [NumberOfSubBlocks]
extern YesNoType
extern TimeType
                      **RequestTimeHistogram; /* [NumberOfRequestsAvailable] */
                                               /* [FileHistgramMaxIndex]
                      **StallTimeHistogram; /* [NumberOfCacheWaitingForsAv]*/
extern TimeType
                                               /* [FileHistgramMaxIndex] */
                                               /* [NumberOfRequestsAvailable] */
/* [NumberOfStallsAvailable] */
                      *TotalRequestTime;
extern TimeType
                      *TotalStallTime;
extern TimeType
                                              /* [NumberOfRequestsAvailable] */
extern ScoreType
                      *NumberOfAccesses;
extern ScoreType
                      *NumberOfCacheHits;
extern ScoreType
extern ScoreType
extern ScoreType
extern ScoreType
                      *NumberOfBufferHits;
                      *PredictedNumberOfAccesses;
                      *PredictedNumberOfHits;
                      TotalNumberOfAccesses;
extern ScoreType
extern ScoreType
extern ScoreType
                      TotalNumberOfWordsReadFromMemory;
                      TotalNumberOfWordsWrittenToMemory;
extern ScoreType
                      TotalNumberOfWordsWrittenToCache;
extern BufferType
extern BufferType
                      ReadBuffer;
                      WriteBuffer;
extern BufferType
                      BlockBuffer;
extern AddressType
                      MAR:
                      TOA;
extern TimeType
                      TOD;
extern TimeType
extern TimeType
                      BlockTOA;
extern FILE
                      *DataFile;
extern YeaNcTune
                      FndOfDataFile:
```

\*\*\*\*\*\*\*\*\*\*\*\*

#endif

\*\* Page 4-0 \*\* Cache.c \*\* Part Of SACS 1.0 (StillAnother Cache Simulator) Program Modified: 3/17/94 \*\* File Modified: 3/17/94 \*\* \*\* \*\* \*\* Author: William G. Smith \*\* Address: Electrical Engineering Department \*\* \*\* Naval Postgraduate School \*\* Monterey, CA 93940 \*\* \*\* \*\* \* \* Copyright 1994, William G. Smith \*\* Permission to use, copy, modify, and distribute this software and \*\* \*\* its documentation for any purpose and without fee is hereby granted \*\* provided that the above copyright notice appears in all copies. No \*\* modified version of this program should be redistributed without the \*\* \*\* authors consent. William G. Smith makes no warranty or representation, promise of guarantee, either expressed or implied, with respect to this software's ability to produce valid results. \*\* This program is provided "as is" any financial, personal or property \*\* damage caused by the use of this program is the responsibility of the \*\* \*\* \*\* user.

\*

/**********************							
**	Page 4-1	**					
**	Cache.c	**					
* *		**					
**	Description:	**					
**	•	**					
**	CacheModel makes all the necessary calls to simulate cache memory.	**					
**	CacheModel decides which calls to make, based on the value of CacheHit,	**					
**	and Request. This function is called every time Time is incremented.	**					
**	If there are no read or write requests waiting to be completed the	**					
**	function does nothing. The value of CacheHit will remain Unknown until	**					
**	the appropriate cache access time has expired. Then CacheModel will	**					
**	call IsRequestAHit to determine if the request is a hit or a miss.	**					
**		**					
**	Table of Contents	**					
**		**					
**	Cover Page Page 4- 1	**					
**	List of Cache.c Function Declarations Page 4-2	**					
**	CacheModel() Page 4-3	**					
**	IsRequestAHit() Page 4-4	**					
**	ReadHit() Page 4-5	**					
**	ReadMiss() Page 4- 6	**					
**	WriteHit() Page 4-7	**					
**	WriteMiss() Page 4-8	**					
**	AccessCache() Page 4-10	**					
**		**					
**	SelectBlockVictim()	**					
**	SetDirtyBits() Page 4-13	**					
**	WriteDirtySubBlocks() Page 4-14	**					
**	AddToReadBuffer() Page 4-16	**					
**	SearchCache() Page 4-20	**					
**	AddToWriteBuffer() Page 4-21	**					
**		**					

#include "Global.h"

```
/********************************
                                                           Page 4-2 **
                                 Cache.c
                                                                        **
                                                                        **
                  List of Cache.c Function Declarations
                                                                        **
** Description:
                                                                        **
                                                                        **
     This is a list of function declarations within the file scope
                                                                       **
** of "Cache.c".
                                                                        **
**
                                                                        **
void CacheModel();
void IsRequestA
                                                          /* Page 4-3 */
/* Page 4-4 */
/* Page 4-5 */
/* Page 4-6 */
                                                           /* Page 4-7 */
                                                          /* Page 4-8 */
                                                          /* Page 4-10 */
void SelectBlockVictim();
void SetDirtyBits();
void WriteDirtySubBlocks();
void AddToReadBuffer();
                                                          /* Page 4-11 */
                                                          /* Page 4-13 */
                                                          /* Page 4-14 */
                                                          /* Page 4-16 */
/* Page 4-20 */
/* Page 4-21 */
YesNoType SearchCache();
void AddToWriteBuffer();
```

```
Page 4-3 **
**
                                  Cache.c
                                                                         **
                                 CacheModel
   Description:
                                                                         **
**
**
        CacheModel makes all the necessary calls to simulate cache memory. **
** CacheModel decides which calls to make, based on the value of CacheHit, **
**
   and Request. This function is called every time Time is incremented.
**
   If there are no read or write requests waiting to be completed the
   function does nothing. The value of CacheHit will remain Unknown until **
** the appropriate cache access time has expired. Then CacheModel will **
   call IsRequestAHit to determine if the request is a hit or a miss.
                                                                         **
**
                                                                         **
***********************************
void CacheModel()
   if (CacheHit==Unknown && Request!=None)
      if (Request==Read )
        AccessCache (ReadCacheAccessTime, CacheWaitingForReadCacheRequest);
      if (Request==Write)
        AccessCache (WriteCacheAccessTime, CacheWaitingForWriteCacheRequest);
      if (CacheWaitingFor==Nothing) IsRequestAHit();
   if (CacheHit==Yes && Request==Read ) ReadHit();
   if (CacheHit==No && Request==Read ) ReadMiss();
   if (CacheHit==Yes && Request==Write) WriteHit();
   if (CacheHit==No && Request==Write) WriteMiss();
   }
```

```
**
                                                               Page 4-4 **
                                  Cache.c
                                                                           **
                               IsRequestAHit
                                                                           **
** Description:
                                                                           **
        IsRequestAHit determines if the request is a hit or a miss, and
** sets CacheHit to the appropriate value. IsRequestAHit will find the
                                                                           **
** SetNumber that the data is supposed to be in. Then all
                                                                           **
** CacheBlockAddresses in that set will be checked to see if they equal
** the BlockAddress for that request. If the correct block is found,
                                                                           **
** then all sub blocks that are required to satisfy the request will be
                                                                           **
** inspected for validity. If all required sub blocks are valid then
                                                                           **
** CacheHit will equal Yes on return from IsRequestAHit.
                                                                           **
*****************************
void IsRequestAHit ()
   1
             SetNumber = Set(RequestAddress);
  SizeType
  SizeType FirstBlock = SetNumber*Associativity;
SizeType LastBlock = FirstBlock+Associativity-1;
  SizeType BlockIndex;
  SizeType SubBlockIndex;
  CacheHit=No;
  BufferHit=Unknown;
  for (BlockIndex=FirstBlock; BlockIndex++)
      {
      if (CacheBlockAddress[BlockIndex]==BlockAddress(RequestAddress))
        CacheHit=Yes;
        if (Request == Read)
           for (SubBlockIndex=SubBlock(RequestAddress);
                 SubBlockIndex<=SubBlock(RequestAddress+RequestSize-1);</pre>
                 SubBlockIndex++)
               if (CacheValidBit[BlockIndex][SubBlockIndex]==No) CacheHit=No;
        LastCacheBlockAccessTime[BlockIndex]=Time;
      }
   if (CacheHit==Yes) BufferHit=No;
   ŀ
```

```
Page 4-5 **
                                Cache.c
                                                                      **
                                                                      **
                                ReadHit
                                                                      **
                                                                      **
   Description:
**
                                                                      **
**
        ReadHit is called to simulate a cache hit during a read request.
                                                                      **
** Read Hit simply finishes simulating the cache access for the hit.
                                                                      **
** ReadCachHitTime is the time required to send the data from the cache
                                                                      **
** to the CPU. Note that the Ttime to locate the block in the cache is **
** simulated in CacheModel. ReadHit is called repeatedly while Time is
                                                                     **
** incremented until Access Cache returns with CacheWaitingFor equal to
                                                                      **
** Nothing. AccessCache will return CacheWaitingFor equal to
                                                                      **
                                                                      **
** ReadCacheRequest until the ReadCacheHitTime has expired.
*************************
void ReadHit()
  {
  AccessCache (ReadCacheHitTime, CacheWaitingForReadCacheRequest);
  }
```

```
*********
                                 Cache.c
                                ReadMiss
   Description:
**
        ReadMiss is called to simulate a cache miss during a read request. **
   ReadMiss first simulates the time it would take to perform all block
   management for a read miss. This time is called Read Cache Miss Time.
   Once that time has passed Read Miss calls Select Block Victim to pick a **
   block in the set. When SelectBlockVictim returns with CacheWaitingFor
                                                                         * *
   equal to Nothing the Request Block Number will contain the new block
                                                                         **
   number where the data will be placed.
                                                                         **
                                                                         * *
**
        Once the new block has been chosen, ReadMiss will call
** AddToReadBuffer. If ReadForward is selected, then RequiredSize for the **
** memory request will be equal BlockSize. The RequiredSize in the read
                                                                         **
** memory request tells the MemoryModel how much of the requested data
                                                                         ++
   must be read into the BlockBuffer before resetting Cache WaitingFor
                                                                         ++
   back to Nothing. By setting RequiredSize equal to BlockSize, Read Miss **
**
   is forcing Memory Model to read in the entire block before setting
** Cache aiting For back to Nothing. Once the Memory Model has read in
   the data, it is assumed to be able to the CPU during that clock cycle.
*************************
void ReadMiss()
  {
  AccessCache (ReadCacheMissTime, CacheWaitingForReadCacheRequest);
  if (CacheWaitingFor==Nothing ||
      CacheWaitingFor==CacheWaitingForFullWriteBuffer)
     SelectBlockVictim();
  if (CacheWaitingFor==Nothing ||
      CacheWaitingFor==CacheWaitingForFullReadBuffer)
     if (ReadForward==Yes)
        AddToReadBuffer (RequestAddress,
                       BlockSize,
                        RequestSize,
                        RequestBlockNumber,
                        ReadPriority);
     else
        AddToReadBuffer (RequestAddress,
                       BlockSize,
                       BlockSize,
                        RequestBlockNumber,
                        ReadPriority);
     if (CacheWaitingFor==Nothing)
        CacheWaitingFor=CacheWaitingForReadMemoryRequest;
  RecordStall(CacheWaitingFor);
  if (CacheWaitingFor==CacheWaitingForReadMemoryRequest &&
      NoRequestsLeft(&ReadBuffer))
     CacheWaitingFor=Nothing;
   }
```

```
***********
                                                              Page 4-7 **
                                 Cache.c
                                  WriteHit
   Description:
**
**
        WriteHit is called to simulate a cache hit during a write request.
   Write Hit will first simulate the time to write the data to the
   RequestBlockNumber in the cache. Note that the time to locate the
                                                                         **
**
   block was simulated by CacheModel. Once WriteCacheHitTime has expired **
   then WriteHit will perform the block management for the request. The
**
                                                                         **
** block management is dictated by the WritePolicy. For a WriteBack
                                                                         **
** policy the sub blocks written to must have their dirty bits set. This **
**
   is done by SetDirtyBit. For a WriteThrough policy the request must be **
   set to the write buffer. This is done by AddToWriteBuffer.
void WriteHit()
   {
   AddressType TempAddress;
  AccessCache (WriteCacheHitTime, CacheWaitingForWriteCacheRequest);
   if (CacheWaitingFor==Nothing ||
      CacheWaitingFor==CacheWaitingForFullWriteBuffer)
     switch (WritePolicy)
        case WriteBack:
           SetDirtyBits();
           break;
        case WriteThrough:
           for (TempAddress = SubBlockAddress(RequestAddress+SubBlockSize-1);
                TempAddress <SubBlockAddress(RequestAddress+RequestSize);</pre>
                TempAddress+=SubBlockSize)
              CacheValidBit[RequestBlockNumber][SubBlock(TempAddress)]=Yes;
           AddToWriteBuffer(RequestAddress, RequestSize, WritePriority);
           break;
           }
        default:
           printf("WritePolicy not defined for [WriteHit] procedure.");
           exit(1);
        }
     }
```

}

```
Page 4-8 **
                                Cache.c
                                WriteMiss
   Description:
**
        WriteMiss is called to simulate a cache miss during a write
** request. WriteMiss will first simulate the time needed to perform
                                                                        **
   all block management requests. The time is called WriteCacheMissTime.
**
   This is only the time required to make the requests, not the time
** required to complete the block management requests. The time to
                                                                        **
** determine that a miss occurred was simulated by CacheModel. Once the
   WriteCacheMissTime has expired, then WriteMiss will perform all block
   management requests. The memory requests are dictated by the
                                                                        * *
   WriteMissPolicy. The simplest policy is WriteAround. For a
                                                                        **
   WriteAround policy the write data is placed in the WriteBuffer by
   AddToWriteBuffer. WriteAllocate however, is the toughest simulation
**
   in SACS. WriteMiss must first choose a block to put the new data in.
                                                                        * *
**
   This is done by SelectBlockVictim. Then the block data not provided
**
   by the write has to be read in. This read request is made by
** AddToReadBuffer. Because the read address is calculated by adding the
** request size to the address. The new address may be in the next block **
** so to make the addition modulo the BlockSize may have to be subtracted. **
** When the read request has been make then the sub blocks that were
** written to in there entirety will have there valid bits set. If only
   part of a sub block was written to then the CacheValidBit will not be
   set.
**
                                                                        **
**
        WriteMiss then uses the WritePolicy to dictate how the write data
                                                                        **
** is to update the memory. For a WriteBack policy dirty bits are set by **
**
   SetDirtyBits. For a WriteThough the data is added to the WriteBuffer
   by AddToWriteBuffer.
**
void WriteMiss()
   {
  AddressType TempAddress;
  AccessCache (WriteCacheMissTime, CacheWaitingForWriteCacheRequest);
  switch (WriteMissPolicy)
     case WriteAround:
        if (CacheWaitingFor==Nothing ||
            CacheWaitingFor==CacheWaitingForFullWriteBuffer)
           AddToWriteBuffer(RequestAddress, RequestSize, WritePriority);
        break;
     default:
        printf("WriteMissPolicy not defined in [WriteMiss] procedure");
        exit(1);
        }
```

```
Page 4-9
                             Cache.c
                            WriteMiss
                            continued
                ***********
case WriteAllocate:
  if (CacheWaitingFor==Nothing ||
      CacheWaitingFor==CacheWaitingForFullWriteBuffer)
     SelectBlockVictim();
  if (CacheWaitingFor==Nothing ||
      CacheWaitingFor==CacheWaitingForFullReadBuffer)
     if ((BlockSize-RequestSize)>0)
         if (BlockAddress(RequestAddress+RequestSize)
          ==BlockAddress (RequestAddress))
           AddToReadBuffer (RequestAddress+RequestSize,
                            BlockSize-RequestSize,
                            RequestBlockNumber,
                            ReadForWriteAllocatePriority);
        else
           AddToReadBuffer((RequestAddress+RequestSize)-BlockSize,
                            BlockSize-RequestSize,
                            0.
                            RequestBlockNumber,
                            ReadForWriteAllocatePriority);
     }
  if ((CacheWaitingFor==Nothing | |
       CacheWaitingFor==CacheWaitingForFullWriteBuffer) &&
     CacheBlockAddress [RequestBlockNumber] == BlockAddress (RequestAddress))
     for (TempAddress = SubBlockAddress(RequestAddress+SubBlockSize-1);
           TempAddress <SubBlockAddress(RequestAddress+RequestSize);</pre>
           TempAddress+=SubBlockSize)
        CacheValidBit [RequestBlockNumber] [SubBlock (TempAddress)] = Yes;
     switch (WritePolicy)
        case WriteBack:
           SetDirtyBits();
        case WriteThrough:
           AddToWriteBuffer(RequestAddress, RequestSize, WritePriority);
           break;
        default:
           printf("WritePolicy not defined for [WriteMiss] procedure");
           exit(1);
  break;
```

}

```
Page 4-10
                                  Cache.c
                                                                           * *
                                                                           * *
                                AccessCache
   Description:
                                                                           **
**
                                                                           **
* *
        AccessCache is called to simulate a the CPU accessing the cache.
                                                                           **
** AccessCache first waits for the cache not to be busy. The only reason
                                                                          **
   it could be busy is if the BlockBuffer is in the process of updating
                                                                           * *
** the cache. During this time AccessCache will return CacheWaitingFor
                                                                           **
** equal to CPUCacheAccess. Once the cache is not busy then CacheBusy is
                                                                           * *
** set to Yes locking out the BlockBuffer from accessing the cache. Then **
** CacheWaitingFor will set equal to WaitingForRequest this is a local
                                                                           ++
** variable passed by the caller. It will either be equal to
** ReadCacheAccess, or WriteCacheAccess. Then CacheBusy is set for the
** time specified by RequestTime. RequestTime is a local variable. It
** could equal any of the hit, miss, or access times. Once RequestTime
** has expired then AccessCache will set CacheBusy equal to No, and
                                                                           * *
** CacheWaiting For equal to Nothing.
                                                                           **
**
                                                                           * *
                       ***********
void AccessCache(RequestTime, WaitingForRequest)
  TimeType
                      RequestTime;
  CacheWaitingForType WaitingForRequest;
   {
  static TimeType CacheTOA=0;
  if (CacheBusy==Yes && CacheWaitingFor==Nothing )
     CacheWaitingFor=CacheWaitingForCPUCacheAccess;
   if (CacheBusy==No && CacheWaitingFor==CacheWaitingForCPUCacheAccess)
     CacheWaitingFor=Nothing;
   if (CacheWaitingFor==Nothing)
     CacheBusy=Yes;
     CacheWaitingFor=WaitingForRequest;
     CacheTOA=Time+RequestTime;
     }
  RecordStall(CacheWaitingFor);
   if (CacheTOA<=Time && CacheWaitingFor==WaitingForRequest)</pre>
     CacheBusy=No;
     CacheWaitingFor=Nothing;
   }
```

```
Page 4-11 **
                                 Cache.c
                                                                        **
* *
                                                                         **
**
                             SelectBlockVictim
**
** Description:
**
* *
        SelectBlockVictim chooses the next block to be used, and writes
** the dirty subblocks out to the WriteBuffer. Se "BlockVictim first
                                                                         * *
   surveys the cache set that the RequestAddress mans to. The servey
                                                                         **
**
   includes finding the block that was least recently accessed. This
                                                                         **
**
   BlockNumber is stored in LRUBlock. Once the set has been surveyed
   then the ReplacementPolicy dictates how the block is chosen. For the
* *
                                                                         **
* *
   LRU policy Request Block Number is set equal to LRUBlock. For the
                                                                        **
** FIFO policy CacheNextBlock keeps track of the next victim block for
                                                                        **
* *
   each set. CacheNextBlock is initialized to all zeros during the
                                                                        **
** beginning of a run. Therefore it must be checked to see if it is
                                                                         **
** between the first, and last blocks for the set. If it is not then
** CacheNextBlock for SetNumber is reset to FirstBlock. Once
** SelectBlockVictim knows it has a valid Cache Next Block then
                                                                         **
** RequestBlock is set equal to it. Then CacheNextBlock for the
                                                                         * *
** SetNumber is incremented. For RAND policy the block number is chosen
                                                                         **
** randomly from all the blocks in the set
                                                                         **
**
                                                                         **
        SelectBlockVictim writes all dirty sub blocks to the WriteBuffer
**
** using WriteDirtySubBlocks. WriteDirtySubBlocks takes care of clearing **
** the dirty and valid bits in the block. Once SelectBlockVictim is
** called and it gets to the bottom of the function with Cache..aitingFor
** equal to Nothing then the CacheBlockAddress for the RequestBlockNumber **
* *
   is set equal to the block address of RequestAddress.
*****************************
void SelectBlockVictim()
  SizeType SetNumber = Set(RequestAddress);
  SizeType FirstBlock = SetNumber*Associativity;
  SizeType LastBlock = FirstBlock+Associativity-1;
  SizeType BlockIndex;
  SizeType SubBlockIndex;
  TimeType LRUTime
                         = Time+1;
   SizeType LRUBlock;
```

```
*******
                                                          Page 4-12
                              Cache.c
                          SelectBlockVictim
                             Continued
       RequestBlockNumber=FirstBlock;
for (BlockIndex=FirstBlock; BlockIndex<=LastBlock; BlockIndex++)</pre>
   if (CacheBlockAddress[BlockIndex]==BlockAddress(RequestAddress))
     RequestBlockNumber=BlockIndex;
   if (LRUTime>LastCacheBlockAccessTime[BlockIndex])
     LRUTime=LastCacheBlockAccessTime[BlockIndex];
     LRUBlock=BlockIndex;
   }
if (CacheBlockAddress[RequestBlockNumber]!=BlockAddress(RequestAddress)
   {
   switch (BlockReplacementPolicy)
      1
     case LRU:
        RequestBlockNumber=LRUBlock;
        LastCacheBlockAccessTime[RequestBlockNumber]=Time;
        break;
      case FIFO:
        if (CacheNextBlock[SetNumber]<FirstBlock | |</pre>
            CacheNextBlock[SetNumber]>LastBlock
           CacheNextBlock[SetNumber]=FirstBlock;
        RequestBlockNumber=CacheNextBlock[SetNumber];
        if (RequestBlockNumber<LastBlock)</pre>
           CacheNextBlock[SetNumber]++;
        else
           CacheNextBlock(SetNumber)=FirstBlock;
        break;
      case RAND:
        RequestBlockNumber=(rand()%Associativity)+FirstBlock;
        break;
      }
   WriteDirtySubBlocks();
   }
if (CacheWaitingFor==Nothing)
   CacheBlockAddress [RequestBlockNumber] = BlockAddress (RequestAddress);
}
```

```
Page 4-13 **
                           Cache.c
                          SetDirtyBits
** Description:
       SetDirtyBits sets the dirty bits for all sub blocks that contains **
  data that was modified by a write request.
*******************************
void SetDirtyBits()
  {
  SizeType SubBlockIndex;
  for (SubBlockIndex=SubBlock(RequestAddress);
      SubBlockIndex<=SubBlock(RequestAddress+RequestSize-1);</pre>
      SubBlockIndex++)
    CacheDirtyBit [RequestBlockNumber] [SubBlockIndex]=Yes;
  }
```

```
Page 4-14 **
                               Cache.c
                                                                    **
                           WriteDirtySubBlocks
                                                                    **
** Description:
                                                                    **
                                                                    **
**
        WriteDirtySubBlocks is called to simulate writing all the dirty
** sub blocks in RequestBlock. WriteDirtySubBlocks not only clears all
** the dirty bits. It also clears all the valid bits.
** WriteDirtySubBlocks prepares a block to receive new data, and is called **
** after a block has been selected as a victim. WriteDirtySubBlocks will **
** search the block for consecutive dirty blocks and splice them together
** into one write request. The write request is then added to the
                                                                    **
** WriteBuffer. All of the sub blocks that make up the request will have
** their dirty and valid bits cleared. This process of searching and
                                                                    **
** writing is repeated until all the bits are not dirty. Then all the
                                                                    **
** valid bits are cleared.
                                                                    **
                                                                    **
void WriteDirtySubBlocks()
  ĺ
  SizeType
              i;
              SubBlockIndex = 0;
  SizeType
  AddressType MemoryRequestAddress = CacheBlockAddress[RequestBlockNumber];
  SizeType MemoryRequestSize = 0;
  PriorityType MemoryRequestPriority = WriteDirtyBlockPriority;
```

ŧ

```
************
                                                            Page 4-15
                               Cache.c
                          WriteDirtySubBlocks
                              continued
do
  MemoryRequestSize=0;
  while ((CacheDirtyBit[RequestBlockNumber][SubBlockIndex]==No ||
           CacheValidBit[RequestBlockNumber][SubBlockIndex]==No) &&
          SubBlockIndex<NumberOfSubBlocks)
      SubBlockIndex++;
  MemoryRequestAddress=CacheBlockAddress[RequestBlockNumber]
                       +SubBlockIndex*SubBlockSize;
   while (CacheDirtyBit [RequestBlockNumber] [SubBlockIndex] == Yes &&
          SubBlockIndex<NumberOfSubBlocks)
     MemoryRequestSize+=WordSize;
      SubBlockIndex++;
      }
   if (MemoryRequestSize)
      AddToWriteBuffer (MemoryRequestAddress,
                      MemoryRequestSize,
                       MemoryRequestPriority);
      if (CacheWaitingFor==Nothing)
         for (i=0; i<=SubBlockIndex && i<NumberOfSubBlocks; i++)</pre>
            CacheDirtyBit [RequestBlockNumber] [i] =No;
      }
while (SubBlockIndex<NumberOfSubBlocks && CacheWaitingFor==Nothing);
if (CacheWaitingFor==Nothing)
   for (i=0; i<NumberOfSubBlocks; i++)</pre>
      CacheValidBit [RequestBlockNumber] [i]=No;
}
```

Page 4-16 \*\*

\*\* \*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\* \*

\*\*

\* \*

\*\*

\*\*

\*\*

Cache.c

## AddToReadBuffer

Description:

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\* \*

\*\*

\*\*

\* \*

\*\*

\*\*

\*\*

\*\*

\*\* \*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

\*\*

AddToReadBuffer takes the elements of a request, and adds the request to the ReadBuffer. It will perform all of the searches, and updates necessary to support the appropriate scoreboarding protocals.

AddToReadBuffer will begin by searching the cache, and BlockBuffer for each byte in the request starting at the beginning of the request. Every time a byte is found in one or the other then the Address is incremented, while Size and RequiredSize are decremented. This simulates removing the available data from the front of the request. Then AddToReadBuffer will search the cache, and BlockBuffer for the data at the end of the request. Every time a byte is found then the Size of the request is decremented by one. If the byte was a \*\* required byt then the RequiredSize is decremented also. This simulates \*\* \*\* removing any data available from the end of the request. \*\* AddToReadBuffer is either left with a request that has a Size equal to \*\* zero or the end points are both needed from memory. If the RequiredSize \*\* is zero then the request is a buffer hit, otherwize the request is a \*\* buffer miss. If the request is already a cache hit then the buffer \*\* hit is for some block management request. These kinds of buffer hits are not recorded because it would confuse the ResultsDisplay, by making \*\* it possible to get a hit rate greater tha 100%. If the Size is not zero and Remove ReadDuplicates is eaual to No then the request is added to the end of the ReadBuffer using Append. Append is a buffer utility that adds the request to the end of the buffer. The request must be added to the end of the buffer in ouder not to interfere with MemoryModel which maybe in the middle of a memory read. If RemoveReadDuplicates is equal to Yes then the first byte in the request \*\* will be spliced into the Read Buffer.

Splice is another buffer utility. Splice will first search the ReadBuffer for the byte if it cant't find a request in the buffer that contains the byte then it will search for a read request that is getting data from the same block. If one is found then the request is modified to include the new read byte request. If no suitable request can be found then Splice will add a one byt request to the Read BUffer. \*\* The Address is then incremented while the Size, and Required Size are decremented. Then the cache, and BlockBuffer are searched for the next \*\* byte. If it is not found then the next byte is spliced into the ReadBuffer. This process is repeated until all of the bytes of the request have either been spliced into the ReadBuffer or found.

The BufferHit is normally defined as when the data is available but in the cache. However in order to support the testing of SACS. the definition of a buffer hit is redefined to mean that a request was found to have accrued recently, and that given time to complete all block management the requested data would have been in the cache. This allows TestSACS to predict the hits of a test run without taking into account the time in takes to preform the block management.

Every time a request is spliced into the read or write buffers then the TimeToExecute, and CompletionTimeExtamate must be recalculated. The new time estimates are performed by CalculateTimeEstimates.

\*

```
Page 4-17
                                        Cache.c
                                                                                        **
                                                                                        **
                                    AddToReadBuffer
                                       continued
void AddToReadBuffer(Address, Size, RequiredSize, Block, Priority)
   AddressType Address;
   SizeType Size;
SizeType RequiredSize;
SizeType Block;
   PriorityType Priority;
   MemoryRequestType ReadMemoryRequest;
   YesNoType FoundByte;
AddressType ByteAddress;
AddressType CurrentBlockAddress = BlockAddress(Address);
BufferSizeType OldReadBufferNext = ReadBuffer.Next;
   ReadMemoryRequest.Address
                                                 = Address;
                                                 = Size;
   ReadMemoryRequest.Size
   ReadMemoryRequest.RequiredSize
                                               = RequiredSize;
= Block;
   ReadMemoryRequest.Block
   ReadMemoryRequest.Block
                                                  = Priority;
                                             = No;
   ReadMemoryRequest.AccessInProgress
   ReadMemoryRequest.TimeToExecute
                                                  = 0;
   ReadMemoryRequest.CompletionTimeEstimate = 0;
```

```
********
/****
**
                                                               Page 4-18 **
                                  Cache.c
                                                                           **
                              AddToReadBuffer
                                                                           **
                                 continued
                                                                           **
  if (CacheWaitingFor==CacheWaitingForFullReadBuffer) CacheWaitingFor=Nothing;
  FoundByte=Yes;
  while (FoundByte==Yes && Size>0)
     FoundByte=No;
     if (SearchCache(Address) == Yes)
        FoundByte=Yes;
     else if (SearchBlockBuffer==Yes && Search(&BlockBuffer, Address))
        FoundByte=Yes;
     if (FoundByte==Yes)
        Address++;
        if (BlockAddress(Address)!=CurrentBlockAddress) Address-=BlockSize;
        if (Size>0)
                      Size--;
        if (RequiredSize>0) RequiredSize--;
        }
     }
  ByteAddress=Address+Size-1;
  if (BlockAddress(ByteAddress)!=CurrentBlockAddress) ByteAddress-=BlockSize;
  FoundByte=Yes;
  while (FoundByte==Yes && Size>0)
     FoundByte=No;
     if (SearchCache(ByteAddress) == Yes)
        FoundByte=Yes;
     else if (SearchBlockBuffer==Yes && Search(&BlockBuffer, ByteAddress))
        FoundByte=Yes;
     if (FoundByte==Yes)
        ByteAddress--;
        if (BlockAddress(ByteAddress)!=CurrentBlockAddress)
           ByteAddress+=BlockSize;
        if (Size>0) Size--;
        if (RequiredSize>Size) RequiredSize=Size;
        }
     }
  if (Request==Read && Test==No)
     if (RequiredSize==0 && CacheHit==No)
        BufferHit=Yes;
     else
        BufferHit=No;
  if (RequiredSize==0 && Request==Read) CacheWaitingFor=Nothing;
  ReadMemoryRequest.Address
                                 = Address;
  ReadMemoryRequest.Size
                                 = Size;
  ReadMemoryRequest.RequiredSize = RequiredSize;
  if (RemoveReadDuplicates==No && Size>0)
     Append(&ReadBuffer, &ReadMemoryRequest);
```

```
/********************
                                                       Page 4-19 **
                                                                  **
                              Cache.c
                           AddToReadBuffer
                                                                  **
                             continued
********************************
  while (Size>0 && RemoveReadDuplicates==Yes)
     {
    FoundByte=No;
    if (SearchCache(Address)==Yes)
       FoundByte=Yes;
    else if (SearchBlockBuffer==Yes && Search(&BlockBuffer, Address))
       FoundByte=Yes;
    if (FoundByte==No)
       Splice(&ReadBuffer, Address, RequiredSize, Block, Priority);
    Address++;
    if (BlockAddress(Address)!=CurrentBlockAddress) Address=BlockSize;
    if (Size>0) Size--;
    if (RequiredSize>0) RequiredSize--;
     }
  if (Request==Read && Test==Yes)
    if (ReadBuffer.Next==OldReadBufferNext && CacheHit==No)
       BufferHit=Yes;
    else
       BufferHit=No;
  CalculateTimeEstimates();
  }
```

```
Page 4-20 **
                                   Cache.c
                                                                              **
                                                                              **
**
                                  SearchCache
                                                                              **
                                                                              **
** Description:
**
         SearchCache is called by AddToReadBuffer to find any parts of
** the request that may be already located in the cache. This must be
                                                                              **
** done because if a read request follows a write request using a write
                                                                              **
   allocate policy then part of the read may be in the cache while the
                                                                              **
** rest may still need to be read from memory. Search Cache checks all
   CacheBlockAddresses in the cache set. If any of the cache block addresses equals the block address of the byte, then Search Cache
**
                                                                              **
   checks the CacheValidBit for the sub block that the byte is located in. **
** If the sub block is valid then SearchCache returns Yes.
**
                                                                              **
**************************
YesNoType SearchCache (Address)
  AddressType Address;
   {
   SizeType FirstBlock = Set (Address) *Associativity;
   SizeType LastBlock = FirstBlock+Associativity-1;
   SizeType BlockIndex;
   YesNoType FoundByte;
   for (BlockIndex=FirstBlock; BlockIndex<=LastBlock; BlockIndex++)</pre>
      if (CacheBlockAddress[BlockIndex] == BlockAddress(Address))
         if (CacheValidBit[BlockIndex][SubBlock(Address)]) FoundByte=Yes;
   return (FoundByte);
   }
```

```
Page 4-21 **
                                    Cache.c
* *
**
                                AddToWriteBuffer
                                                                               **
   Description:
                                                                                **
**
**
         AddToWriteBuffer adds one record to write buffer. It also updates **
** the ReadBuffer it the UpdateReadBuffer arguments is asserted. The
** process of updating the ReadBuffer is simply changein the requests so
                                                                               **
** that data make available by the write request is not requested form
                                                                               **
** memory. UpdateReadBuffer should not be used unless the word and sub
                                                                               **
** block sizes are equal. This is because a write request may reduce a
                                                                               **
** read request to where the read request will not be large enough to
                                                                               **
** validate a sub block. The write request may alsobe unable to set any
** valid bits because of sub block alignment. The result is that a sub
** block was supposed to be read in is not.
                                                                               **
************************
void AddToWriteBuffer(Address, Size, Priority)
   AddressType Address;
   SizeType Size;
   PriorityType Priority;
   MemoryRequestType WriteMemoryRequest;
  YesNoType FoundByte;
AddressType ByteAddress;
AddressType CurrentBlockAddress = BlockAddress(Address);
SizeType NoBytes;
   BufferSizeType OldWriteBufferNext = WriteBuffer.Next;
   WriteMemoryRequest.Address
WriteMemoryRequest.Size
WriteMemoryRequest.RequiredSize
                                             = Address;
                                             = Size;
                                           = 0;
                                             = 0;
   WriteMemoryRequest.Block
WriteMemoryRequest.Priority
   WriteMemoryRequest.CompletionTimeEstimate = 0;
```

```
/***
                                                                 Page 4-22 **
                                   Cache.c
                               AddToWriteBuffer
                                  continued
  if (CacheWaitingFor==CacheWaitingForFullWriteBuffer)
     CacheWaitingFor=Nothing;
  FoundByte=Yes;
  while(FoundByte==Yes && UpdateReadBuffer==Yes)
     FoundByte=No;
     ByteAddress=Address;
      for (NoBytes=0; NoBytes<Size; NoBytes++)</pre>
         if (UpdatingReadBuffer(ByteAddress) == Yes) FoundByte=Yes;
        ByteAddress++;
         if (BlockAddress(ByteAddress)!=CurrentBlockAddress)
            ByteAddress-=BlockSize;
      }
  if (RemoveWriteDuplicates==No && Size>0)
     Append(&WriteBuffer, &WriteMemoryRequest);
  while (RemoveWriteDuplicates==Yes && Size>0)
      Splice(&WriteBuffer, Address, 0, 0, Priority);
     Address++;
     if (BlockAddress(Address)!=CurrentBlockAddress) Address=BlockSize;
      if (Size>0) Size--;
  if (Request==Write)
     BufferHit=No;
     if (WriteBuffer.Next==OldWriteBufferNext && CacheHit==No) BufferHit=Yes;
      if (WriteBuffer.Next==OldWriteBufferNext &&
          CacheWaitingFor !=CacheWaitingForFullWriteBuffer)
         CacheWaitingFor=Nothing;
      }
  CalculateTimeEstimates();
```

}

\*\*\*\*\*\*\*\*\*\*\*\*\* Page 5-0 \*\* Memory.c Part Of SACS 1.0 (StillAnother Cache Simulator) \*\* Program Modified: 3/17/94 \*\* File Modified: 3/17/94 \*\* Author: William G. Smith \*\* \*\* Address: Electrical Engineering Department \*\* Naval Postgraduate School \*\* \*\* Monterey, CA 93940 \*\* \*\* \*\* Copyright 1994, William G. Smith \*\* \*\* Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted \*\* provided that the above copyright notice appears in all copies. No \*\* modified version of this program should be redistributed without the \*\* \*\* authors consent. William G. Smith makes no warranty or \*\* \*\* representation, promise of guarantee, either expressed or implied, with respect to this software's ability to produce valid results. \*\* \*\* This program is provided "as is" any financial, personal or property \*\* damage caused by the use of this program is the responsibility of the \*\* \*\*

Memory.c  Description:  Memory.c contains all functions that relate to the simulation of main memory. Memory Model makes all the necessary calls to simulate main memory. MemoryModel decides which calls to make, based on MemoryWaitingFor. This function is called every time Time is incremented. If there are no read or write requests waiting to be completed, the function does nothing. Memory Model contains a loop that forces the procedure to continue modeling until TOA and TOD are not equal to Time. This insures that if there are any events that occur in zero clock cycles then the next event is allowed to start.  Memory Model calls SelectMemoryRequest to choose a request from either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory access times. Cache Update after memory read.  Table of Contents  Cover Page			Page 5- 1	1
Memory.c contains all functions that relate to the simulation of main memory. Memory Model makes all the necessary calls to simulate main memory. MemoryModel decides which calls to make, based on MemoryWaitingFor. This function is called every time Time is incremented. If there are no read or write requests waiting to be completed, the function does nothing. Memory Model contains a loop that forces the procedure to continue modeling until TOA and TOD are not equal to Time. This insures that if there are any events that occur in zero clock cycles then the next event is allowed to start.  Memory Model calls SelectMemoryRequest to choose a request from either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page		Memory.c		
Memory.c contains all functions that relate to the simulation of main memory. Memory Model makes all the necessary calls to simulate main memory. MemoryModel decides which calls to make, based on MemoryWaitingFor. This function is called every time Time is incremented. If there are no read or write requests waiting to be completed, the function does nothing. Memory Model contains a loop that forces the procedure to continue modeling until TOA and TOD are not equal to Time. This insures that if there are any events that occur in zero clock cycles then the next event is allowed to start.  Memory Model calls SelectMemoryRequest to choose a request from either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page	Dago	rintion.		
main memory. Memory Model makes all the necessary calls to simulate main memory. MemoryModel decides which calls to make, based on MemoryWaitingFor. This function is called every time Time is incremented. If there are no read or write requests waiting to be completed, the function does nothing. Memory Model contains a loop that forces the procedure to continue modeling until TOA and TOD are not equal to Time. This insures that if there are any events that occur in zero clock cycles then the next event is allowed to start.  Memory Model calls SelectMemoryRequest to choose a request from either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page	Desc	ription:		
main memory. Memory Model makes all the necessary calls to simulate main memory. MemoryModel decides which calls to make, based on MemoryWaitingFor. This function is called every time Time is incremented. If there are no read or write requests waiting to be completed, the function does nothing. Memory Model contains a loop that forces the procedure to continue modeling until TOA and TOD are not equal to Time. This insures that if there are any events that occur in zero clock cycles then the next event is allowed to start.  Memory Model calls SelectMemoryRequest to choose a request from either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page		Memory.c contains all functions that relate to the s	imulation of	
main memory. MemoryModel decides which calls to make, based on MemoryWaitingFor. This function is called every time Time is incremented. If there are no read or write requests waiting to be completed, the function does nothing. Memory Model contains a loop that forces the procedure to continue modeling until TOA and TOD are not equal to Time. This insures that if there are any events that occur in zero clock cycles then the next event is allowed to start.  Memory Model calls SelectMemoryRequest to choose a request from either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory reads.  Table of Contents  Cover Page	main			
MemoryWaitingFor. This function is called every time Time is incremented. If there are no read or write requests waiting to be completed, the function does nothing. Memory Model contains a loop that forces the procedure to continue modeling until TOA and TOD are not equal to Time. This insures that if there are any events that occur in zero clock cycles then the next event is allowed to start.  Memory Model calls SelectMemoryRequest to choose a request from either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times.  Simulated memory reads.  Table of Contents  Cover Page Page 5- 1  List of Memory.c Function Declarations Page 5- 2  MemoryModel() Page 5- 3  SelectMemoryRequest Page 5- 4  StartMemoryReads() Page 5- 6  StartMemoryReads() Page 5- 6  StartMemoryWrites() Page 5- 8  ContinueMemoryWrites() Page 5- 9  UpdateCache() Page 5- 11  AddAWordToMemoryRequest() Page 5- 13				
completed, the function does nothing. Memory Model contains a loop that forces the procedure to continue modeling until TOA and TOD are not equal to Time. This insures that if there are any events that occur in zero clock cycles then the next event is allowed to start.  Memory Model calls SelectMemoryRequest to choose a request from either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times.  Simulated memory transfer times.  Cache Update after memory read.  Table of Contents  Cover Page				
that forces the procedure to continue modeling until TOA and TOD are not equal to Time. This insures that if there are any events that occur in zero clock cycles then the next event is allowed to start.  Memory Model calls SelectMemoryRequest to choose a request from either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory access times. Cache Update after memory read.  Table of Contents  Cover Page	incr	emented. If there are no read or write requests wait.	ing to be	
not equal to Time. This insures that if there are any events that occur in zero clock cycles then the next event is allowed to start.  Memory Model calls SelectMemoryRequest to choose a request from either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page				
Memory Model calls SelectMemoryRequest to choose a request from either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page				
Memory Model calls SelectMemoryRequest to choose a request from either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page Page 5- 1  List of Memory.c Function Declarations Page 5- 2  MemoryModel() Page 5- 3  SelectMemoryRequest Page 5- 4  StartMemoryReads() Page 5- 5  ContinueMemoryReads() Page 5- 6  StartMemoryWrites() Page 5- 8  ContinueMemoryWrites() Page 5- 9  UpdateCache() Page 5- 1  AddAWordToMemoryRequest() Page 5-13				
either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page	occu	r in zero clock cycles then the next event is allowed	to start.	
either the read or the write buffers. Memory Model calls Start Reads, and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page		Moments Model calle ColortMomentsDominat to share	00000 F	
and Start Writes, to simulate accessing memory and receiving the first word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page	ai+1			
word of a memory request. ContinueMemoryReads, and ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page				
ContinueMemoryWrites are then called to simulate the memory transfer of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page			ing the ilist	-
of the following words of data.  The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page			rv transfer	
The simulation of main memory includes:  Choosing memory request from read, write buffers. Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page			-, crampici	
Choosing memory request from read, write buffers.  Simulated memory access times.  Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page Page 5-1  List of Memory.c Function Declarations Page 5-2  MemoryModel() Page 5-3  SelectMemoryRequest Page 5-4  StartMemoryReads() Page 5-5  ContinueMemoryReads() Page 5-6  StartMemoryWrites() Page 5-8  ContinueMemoryWrites() Page 5-9  UpdateCache() Page 5-11  AddAWordToMemoryRequest() Page 5-13				
Choosing memory request from read, write buffers.  Simulated memory access times.  Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page Page 5-1  List of Memory.c Function Declarations Page 5-2  MemoryModel() Page 5-3  SelectMemoryRequest Page 5-4  StartMemoryReads() Page 5-5  ContinueMemoryReads() Page 5-6  StartMemoryWrites() Page 5-8  ContinueMemoryWrites() Page 5-9  UpdateCache() Page 5-11  AddAWordToMemoryRequest() Page 5-13		The simulation of main memory includes:		
Simulated memory access times. Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page		•		
Simulated memory transfer times. Cache Update after memory read.  Table of Contents  Cover Page			s.	
Cache Update after memory read.  Table of Contents  Cover Page				
Table of Contents  Cover Page				
Cover Page		Cache Update after memory read.		
Cover Page		Mobile of Contacts		
List of Memory.c Function Declarations Page 5-2  MemoryModel() Page 5-3  SelectMemoryRequest Page 5-4  StartMemoryReads() Page 5-5  ContinueMemoryReads() Page 5-6  StartMemoryWrites() Page 5-8  ContinueMemoryWrites() Page 5-9  UpdateCache() Page 5-11  AddAWordToMemoryRequest() Page 5-13		Table of Contents		
List of Memory.c Function Declarations Page 5-2  MemoryModel() Page 5-3  SelectMemoryRequest Page 5-4  StartMemoryReads() Page 5-5  ContinueMemoryReads() Page 5-6  StartMemoryWrites() Page 5-8  ContinueMemoryWrites() Page 5-9  UpdateCache() Page 5-11  AddAWordToMemoryRequest() Page 5-13		Cover Page	5_ 1	
MemoryModel()       Page 5-3         SelectMemoryRequest       Page 5-4         StartMemoryReads()       Page 5-5         ContinueMemoryReads()       Page 5-6         StartMemoryWrites()       Page 5-8         ContinueMemoryWrites()       Page 5-9         UpdateCache()       Page 5-11         AddAWordToMemoryRequest()       Page 5-13				
SelectMemoryRequest Page 5- 4 StartMemoryReads() Page 5- 5 ContinueMemoryReads() Page 5- 6 StartMemoryWrites() Page 5- 8 ContinueMemoryWrites() Page 5- 9 UpdateCache() Page 5-11 AddAWordToMemoryRequest() Page 5-13				
StartMemoryReads() Page 5-5 ContinueMemoryReads() Page 5-6 StartMemoryWrites() Page 5-8 ContinueMemoryWrites() Page 5-9 UpdateCache() Page 5-11 AddAWordToMemoryRequest() Page 5-13				
ContinueMemoryReads()				
StartMemoryWrites()				
ContinueMemoryWrites()		StartMemoryWrites() Page	5- 8	
<pre>UpdateCache() Page 5-11 AddAWordToMemoryRequest() Page 5-13</pre>		ContinueMemoryWrites() Page	5- 9	
AddAWordToMemoryRequest()		UpdateCache() Page	5-11	
RemoveAWordFromMemoryRequest() Page 5-14		AddAWordToMemoryRequest() Page		
		RemoveAWordFromMemoryRequest() Page	5-14	

#include "Global.h"

```
/********************************
**
                                                                 Page 5-2 **
* *
                                    Memory.c
                                                                               **
**
                                                                               **
**
                   List of Memory.c Function Declarations
                                                                               **
** Description:
                                                                               **
**
                                                                               **
**
         This is a list of function declarations within the file scope
                                                                               **
** of Memory.c
                                                                               **
**********************
                                                                /* Page 5- 3 */
/* Page 5- 4 */
/* Page 5- 5 */
void MemoryModel();
void SelectMemoryRequest();
void StartMemoryReads();
void ContinueMemoryReads();
void StartMemoryWrites();
void ContinueMemoryWrites();
                                                                 /* Page 5- 6 */
                                                                /* Page 5-8 */
                                                                /* Page 5-9 */
                                                                /* Page 5-11 */
void UpdateCache();
                                                                /* Page 5-13 */
void AddAWordToMemoryRequest();
void RemoveAWordFromMemoryRequest();
                                                                /* Page 5-14 */
```

```
Page 5-3 **
* *
                                  Memory.c
                                 MemoryModel
** Description:
**
**
        Memory.c contains all functions that relate to the simulation of
** main memory. Memory Model makes all the necessary calls to simulate
                                                                          **
** main memory. MemoryModel decides which calls to make, based on
                                                                          ++
** MemoryWaitingFor. This function is called every time Time is
                                                                          **
** incremented. If there are no read or write requests waiting to be
                                                                          * *
**
  completed, the function does nothing. Memory Model contains a loop
                                                                          **
** that forces the procedure to continue modeling until TOA and TOD are
                                                                          **
** not equal to Time. This insures that if there are any events that
                                                                          **
** occur in zero clock cycles then the next event is allowed to start.
                                                                          **
* *
        Memory Model calls SelectMemoryRequest to choose a request from
                                                                          **
** either the read or the write buffers. Memory Model calls Start Reads,
                                                                          * *
** and Start Writes, to simulate accessing memory and receiving the first
                                                                          **
                                                                          **
   word of a memory request. ContinueMemoryReads, and
  ContinueMemoryWrites are then called to simulate the memory transfer
                                                                          **
   of the following words of data.
                                                                          * *
                                                                          * *
        The simulation of main memory includes:
                                                                          **
**
                                                                          **
* *
             Choosing memory request from read, write buffers.
             Simulated memory access times.
                                                                          **
             Simulated memory transfer times.
                                                                          **
             Cache Update after memory read.
                                                                          * *
void MemoryModel()
   {
  MemoryWaitingForType LastMemoryWaitingFor;
  do
     LastMemoryWaitingFor=MemoryWaitingFor;
     if (MemoryWaitingFor==Nothing) SelectMemoryRequest(&MemoryWaitingFor);
     else if (MemoryWaitingFor==MemoryWaitingForMemoryReadRequest ||
              MemoryWaitingFor==MemoryWaitingForCacheUpdate)
             StartMemoryReads();
     else if (MemoryWaitingFor==MemoryWaitingForMemoryReadAccess ||
              MemoryWaitingFor==MemoryWaitingForMemoryReadTransfer)
             ContinueMemoryReads();
     else if (MemoryWaitingFor==MemoryWaitingForMemoryWriteRequest)
             StartMemoryWrites();
     else if (MemoryWaitingFor==MemoryWaitingForMemoryWriteAccess ||
              MemoryWaitingFor==MemoryWaitingForMemoryWriteTransfer)
             ContinueMemoryWrites();
   while (MemoryWaitingFor!=LastMemoryWaitingFor || TOA==Time || TOD==Time);
   }
```

\*

```
* *
                                                             Page 5- 4
* *
                                 Memory.c
                             SelectMemoryRequest
   Description:
**
        SelectMemoryRequest is called when memory is waiting for nothing.
**
   SelectMemoryRequest chooses a request from either the read or write
                                                                         **
   buffers, based on priority. The request is not returned however, the
   request is left at the top of the buffer with its Priority and
   AccessInprogress set equal to Yes. If a request is found then
**
   MemoryWaitingFor is set to MemoryReadRequest, or MemoryWriteRequest
   depending on whether the request was found in the read or write
   buffers.
     void SelectMemoryRequest(MemoryWaitingFor)
  MemoryWaitingForType *MemoryWaitingFor;
  MemoryRequestType ReadMemoryRequest;
  MemoryRequestType WriteMemoryRequest;
  if (!(ReadBuffer.Empty))
     ReadMemoryRequest=View(&ReadBuffer);
  else
     ReadMemoryRequest.Priority=NoPriority;
  if (!(WriteBuffer.Empty))
     WriteMemoryRequest=View(&WriteBuffer);
  else
     WriteMemoryRequest.Priority=NoPriority;
  if (ReadMemoryRequest.Priority<=WriteMemoryRequest.Priority &&
      ReadMemoryRequest.Priority!=NoPriority)
     *MemoryWaitingFor=MemoryWaitingForMemoryReadRequest;
     ReadMemoryRequest.AccessInProgress=Yes;
     ReadMemoryRequest.Priority=0;
     ChangeTopMemoryRequest (&ReadBuffer, &ReadMemoryRequest);
  else if (WriteMemoryRequest.Priority!=NoPriority)
     *MemoryWaitingFor=MemoryWaitingForMemoryWriteRequest;
     WriteMemoryRequest.AccessInProgress=Yes;
     WriteMemoryRequest.Priority=0;
     ChangeTopMemoryRequest(&WriteBuffer, &WriteMemoryRequest);
  }
```

```
Page 5- 5
                                  Memory.c
                               StartMemoryReads
   Description:
**
        StartMemoryReads begins a read request, simulating the first word
** read from memory. The time to complete this read is called
                                                                          **
** MemoryAccessTime. The BlockBuffer is initialized in preparation to
**
   receive the new data words. If BlockWaitingFor is not equal to
**
   Nothing the StartMemoryReads will have to wait until it is before
**
   allowing the new memory read request to start. If StartMemoryReads
   does have to wait for the cache then MemoryWaitingFor it set equal to
                                                                          **
**
   CacheUpdate, otherwise MemoryWaitingFor is set to MemoryReadAccess.
                                                                          **
**
   The new block record is equal to the ReadBuffer with its sizes set to
                                                                          **
**
   zero. This gives the Block Memory Request the same block number and
                                                                          **
   the ReadMemoryRequest. The Address is aligned to WordSize. The
                                                                          **
   Address must be aligned because the words read in will be aligned
                                                                          * *
** to WordSize. The new BlockMemoryRequest is simply pushed onto the
                                                                          ++
** Block Buffer. The BlockWaitingFor is set equal to MemoryBlockTransfer.
** To indicate that data is being transferred from memory to the
                                                                          **
** BlockBuffer.
                                                                          ++
**
************
void StartMemoryReads()
   1
  MemoryRequestType ReadMemoryRequest;
  MemoryRequestType BlockMemoryRequest;
   if (BlockWaitingFor==Nothing)
     ReadMemoryRequest=View(&ReadBuffer);
     TOA=Time+MemoryAccessTime;
     MemoryWaitingFor=MemoryWaitingForMemoryReadAccess;
     BlockMemoryRequest=ReadMemoryRequest;
     BlockMemoryRequest.Address=WordAddress (ReadMemoryRequest.Address);
     BlockMemoryRequest.Size=0;
     BlockMemoryRequest.RequiredSize=0;
     BlockMemoryRequest.Priority=0;
     BlockMemoryRequest.AccessInProgress=No;
     Push(&BlockBuffer, &BlockMemoryRequest);
     BlockWaitingFor=MemoryBlockTransfer;
   else
     MemoryWaitingFor=MemoryWaitingForCacheUpdate;
      }
   ŀ
```

```
* *
                                                               Page 5- 6
                                  Memory.c
                              ContinueMemoryReads
   Description:
        ContinueMemoryReads continues the memory read request started by
** StartMemoryReads. It simulates every read from memory other than the
** first word which was simulated by StartMemcryReads. The time to
                                                                           **
   complete each word transfer is equal to MemroyTransferTime. The block,
   and read buffers are altered every time a word is read from memory.
                                                                           **
** Once a request is complete, it is removed from the Read Buffer, and
   Memory WaitingFor is reset to Nothing. Block Waiting For is set to
                                                                           **
** BlockCacheAccess in preparation to transfer the new data to the cache.
                                                                           **
** If the CompletionTimeEstimate for the memory read request is not equal
  to Time then a time predition error is rased.
          ************************************
void ContinueMemoryReads()
   {
   MemoryRequestType BlockMemoryRequest;
  MemoryRequestType ReadMemoryRequest;
   if (TOA<=Time)</pre>
      BlockMemoryRequest=View(&BlockBuffer);
      AddAWordToMemoryRequest (&BlockMemoryRequest);
      ChangeTopMemoryRequest(&BlockBuffer, &BlockMemoryRequest);
      ReadMemoryRequest=View(&ReadBuffer);
      RemoveAWordFromMemoryRequest(&ReadMemoryRequest);
      if (ReadMemoryRequest.Size>0)
         ChangeTopMemoryRequest(&ReadBuffer, &ReadMemoryRequest);
         TOA=Time+MemoryTransferTime;
        MemoryWaitingFor=MemoryWaitingForMemoryReadTransfer;
      else
        Pop(&ReadBuffer);
         TOA=0;
         if (Time!=ReadMemoryRequest.CompletionTimeEstimate)
           PrintTimePredictionError (ReadMemoryRequest.CompletionTimeEstimate,
                                     Time,
                                     "Read",
                                     "ContinueMemoryReads");
         MemoryWaitingFor=Nothing;
        BlockWaitingFor=BlockCacheAccess;
        BlockTOA=Time+BufferCacheAccessTime;
      TotalNumberOfWordsReadFromMemory++;
      }
```

```
************
                                                       Page 5- 7
                             Memory.c
                        {\tt Continue Memory Reads}
                             continued
else
  {
  ReadMemoryRequest=View(&ReadBuffer);
  if (ReadMemoryRequest.Size==0)
     Pop(&ReadBuffer);
     TOA=0;
     if (Time!=ReadMemoryRequest.CompletionTimeEstimate)
        PrintTimePredictionError (ReadMemoryRequest.CompletionTimeEstimate,
                               Time,
                               "Read",
                               "ContinueMemoryReads");
     MemoryWaitingFor=Nothing;
     BlockWaitingFor=BlockCacheAccess;
     BlockTOA=Time+BufferCacheAccessTime;
  }
```

```
/************************
                                                 Page 5-8 **
                           Memory.c
                        StartMemoryWrites
** Description:
                                                           **
**
      StartMemoryWrites begins a memory write request, simulating the
** first word written to memory. The time to complete this one word write **
** is called MemoryAccessTime. MemoryWaitingFor is set to
                                                           **
** MemoryWriteAccess.
                                                           **
void StartMemoryWrites()
  if (MemoryWaitingFor==MemoryWaitingForMemoryWriteRequest)
    TOD=Time+MemoryAccessTime;
    MemoryWaitingFor=MemoryWaitingForMemoryWriteAccess;
  }
```

```
************
                                                           Page 5-9 **
                                Memory.c
                          ContinueMemoryWrites
  Description:
**
        ContinueMemoryWrites continues the memory write request started
                                                                      **
** by StartMemoryWrites. Like ContinueMemoryReads, it simulates every
                                                                      **
** write to mwmory other than the first word which was simulated by
                                                                      **
** StartMemroyWrites. The time to complete each word transfer is equal
                                                                      **
** to MemoryTransferTime. The Write Buffer is altered every time a word
** is written to memory. Once the memory write request is complete, it
                                                                      **
** is removed form the WriteBuffer, and MemoryWaitingFor is reset to
                                                                      **
** Nothing. If the CompletionTimeEstimate for the memory read request is **
** not equal to Time when the request is completed then a time predition
                                                                      **
                                                                      **
  error is rased.
    ************
void ContinueMemoryWrites()
  MemoryRequestType WriteMemoryRequest;
   if (TOD<=Time)</pre>
     WriteMemoryRequest=View(&WriteBuffer);
     RemoveAWordFromMemoryRequest(&WriteMemoryRequest);
     if (WriteMemoryRequest.Size>0)
        ChangeTopMemoryRequest(&WriteBuffer, &WriteMemoryRequest);
        TOD=Time+MemoryTransferTime;
        MemoryWaitingFor=MemoryWaitingForMemoryWriteTransfer;
     else
        Pop(&WriteBuffer);
        TOD=0;
        if (Time!=WriteMemoryRequest.CompletionTimeEstimate)
           PrintTimePredictionError (WriteMemoryRequest.CompletionTimeEstimate,
                                  Time,
                                  "Write",
                                  "ContinueMemoryWrites");
        MemoryWaitingFor=Nothing;
     TotalNumberOfWordsWrittenToMemory++;
```

```
Page 5-10
                                Memory.c
                          ContinueMemoryWrites
                               continued
else
  WriteMemoryRequest=View(&WriteBuffer);
   if (WriteMemoryRequest.Size==0)
     Pop(&WriteBuffer);
      TOD=0;
      if (Time!=WriteMemoryRequest.CompletionTimeEstimate)
         PrintTimePredictionError(WriteMemoryRequest.CompletionTimeEstimate,
                                  Time,
                                  "Write",
                                  "ContinueMemoryWrites");
      MemoryWaitingFor=Nothing;
   }
}
```

1

```
Page 5-11 **
                                   Memory.c
**
                                                                            **
                                  UpdateCache
                                                                            **
                                                                            **
** Description:
                                                                            **
**
                                                                            **
**
        UpdateCache simulates entering data from the BlockBuffer into the
** cache. UpdateCache first checks wheter of not the cache is busy. If
                                                                            **
** it is not then CacheBusy is asserted, and BlockWaitingFor is set equal **
** to BlockCacheTransfer. The BlockTOA is calculated, to enable
                                                                            **
** CalculateTimeEstimates to predict the completion times for additional
                                                                            **
** memory read request in the buffer. If the cache is busy then the
                                                                            **
** previous memory request time completions may be wrong. That is because **
** the last estimates conunted on the old BlockTOA. This means that all **
** the time estimates must be recalculated.
                                                                            **
                                                                            **
**
        Once the BufferCacheAccessTime has expired then BlockWaitingFor
                                                                            **
** is set equal to Nothing, and the CacheBusy is deserted. The read data **
** must then be removed from the BlockBuffer. The appropriate sub blocks **
** in the cache will then have there dirty bits cleared, and valid bits
                                                                            **
                                                                            **
          ***************
void UpdateCache()
  MemoryRequestType BlockMemoryRequest;
  AddressType TempAddress;
```

```
Page 5-12
                                Memory.c
                               UpdateCache
                                 continued
if (BlockWaitingFor==BlockCacheAccess && CacheBusy==Yes)
  BlockTOA=Time+BufferCacheAccessTime+1;
  CalculateTimeEstimates();
if (BlockWaitingFor==BlockCacheAccess && CacheBusy==No)
   CacheBusy=Yes;
  BlockTOA=Time+BufferCacheAccessTime;
  BlockWaitingFor=BlockCacheTransfer;
if (BlockWaitingFor==BlockCacheTransfer && BlockTOA<=Time)</pre>
   CacheBusy=No;
  BlockWaitingFor=Nothing;
  BlockTOA=0;
  BlockMemoryRequest=Pop(&BlockBuffer);
   if (CacheBlockAddress[BlockMemoryRequest.Block] ==
       BlockAddress(BlockMemoryRequest.Address))
      for (TempAddress=BlockMemoryRequest.Address;
           TempAddress<=BlockMemoryRequest.Address</pre>
                       +BlockMemoryRequest.Size-1;
           TempAddress+=SubBlockSize)
         CacheDirtyBit[BlockMemoryRequest.Block][SubBlock(TempAddress)]=No;
         CacheValidBit[BlockMemoryRequest.Block][SubBlock(TempAddress)] = Yes;
      }
   }
else
   BlockMemoryRequest=View(&BlockBuffer);
   BlockMemoryRequest.TimeToExecute=BufferCacheAccessTime;
   BlockMemoryRequest.CompletionTimeEstimate=BlockTOA;
   ChangeTopMemoryRequest(&BlockBuffer, &BlockMemoryRequest);
```

}

```
/************************
                                                 Page 5-13 **
                           Memory.c
                     AddAWordToMemoryRequest
** Description:
      AddAWordToMemoryRequest adds a word to a MemoryRequest as if it
** had been read in from memory. The address is first aligned to
** WordSize. This simulates the data being added to the request.
                                                           **
                                                           **
void AddAWordToMemoryRequest (MemoryRequest)
  MemoryRequestType *MemoryRequest;
  {
  MemoryRequest->Address=WordAddress(MemoryRequest->Address);
  MemoryRequest->Size+=WordSize;
  }
```

```
*******
                                                             Page 5-14 **
                                 Memory.c
                                                                        **
                        RemoveAWordFromMemoryRequest
  Description:
                                                                        **
**
                                                                        **
**
        RemoveAWordFromMemoryRequest removes a word from a Memory Request, **
** as if it had been written to memory. A copy of the Address is first
                                                                        **
** stored in OldAddress. Then the Address is word aligned and incremented **
** by WordSize. The Required Size, and Size are then decremented by the
** difference of the new Address, and the OldAddress. Finally if the
** Address is outside the range of the original block then the Address is **
** decremented by BlockSize to simulate modulo addition. This simulates
** removing a word from the memory request taking into account word and
** block alignment constraints.
                                                                        **
                                                                        ++
*****************************
void RemoveAWordFromMemoryRequest (MemoryRequest)
  MemoryRequestType *MemoryRequest;
   {
  AddressType OldAddress=MemoryRequest->Address;
  MemoryRequest->Address=WordAddress(MemoryRequest->Address)+WordSize;
  if (MemoryRequest->Size>BlockSize-WordSize)
     MemoryRequest->Size=BlockSize-WordSize;
  else if (MemoryRequest->Size>MemoryRequest->Address-OldAddress)
     MemoryRequest->Size-=MemoryRequest->Address-OldAddress;
  else
     MemoryRequest->Size=0;
  if (MemoryRequest->RequiredSize>BlockSize-WordSize)
     MemoryRequest->RequiredSize=BlockSize-WordSize;
  else if (MemoryRequest->RequiredSize>MemoryRequest->Address-OldAddress)
     MemoryRequest->RequiredSize-=MemoryRequest->Address-OldAddress;
  else
     MemoryRequest->RequiredSize=0;
  if (BlockAddress(OldAddress) < BlockAddress(MemoryRequest -> Address))
     MemoryRequest->Address-=BlockSize;
   }
```

/\* Page 6-0 \*\* \*\* TimeEst.c Part Of SACS 1.0 (StillAnother Cache Simulator) \*\* \*\* \*\* Program Modified: 3/17/94 \*\* File Modified: 3/17/94 \*\* \*\* Author: William G. Smith \*\* Address: Electrical Engineering Department Naval Postgraduate School \*\* \*\* Monterey, CA 93940 \*\* \*\* \*\* \*\* Copyright 1994, William G. Smith \*\* \*\* Permission to use, copy, modify, and distribute this software and \*\* \*\* \*\* its documentation for any purpose and without fee is hereby granted \*\* \*\* provided that the above copyright notice appears in all copies. No \*\* \* \* \*\* modified version of this program should be redistributed without the \*\* \*\* authors consent. William G. Smith makes no warranty or \*\* representation, promise of guarantee, either expressed or implied, \* \* \*\* \*\* with respect to this software's ability to produce valid results. This program is provided "as is" any financial, personal or property \*\* damage caused by the use of this program is the responsibility of the \*\* \*\* \*\* ++

\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*

/*************************************							
**	Page 6-1	**					
**	TimeEst.c	**					
**		**					
**	Description:	**					
**		**					
**	TimeEst.c contains all functions that relate to estimating the	**					
**	execution, and completion times of memory requests.	**					
**		**					
**	Table of Contents	**					
**		**					
**	Cover Page Page 6- 1	**					
**	List of TimeEst.c Function Declarations Page 6-2	**					
**	UpdateTimeToExecute() Page 6- 3	**					
**	CalculateTimeEstimates() Page 6-5	**					
**		**					
******************							

#include "Global.h"

```
Page 6- 3
                                 TimeEst.c
**
                            UpdateTimeToExecute
   Description:
**
        UpdateTimeToExecute calculates the time to complete a memory
** transfer given the MemoryRequest. The Memory Request could be a read
   or write request in a buffer. UpdateTimeToExecute changes the
                                                                         **
** TimeToExecute field to the new value. TimeToexecute is calculated by
** first finding the number of WordsToBeTransfered. If the MemoryRequest
** is not being accessed then the TimeToExecute is simply the AccessTime
** plus the TransferTime times one less then WordsToBeWritten. If the
** MemoryRequest is in progress then the new TimeToExecute is dependent
   on TOA, or TOD of the next word. MemoryWaitingFor dictates whether to
   use the TOA, or TOD. If MemoryWaitingFor is equal to CacheUpdate then
   the request has not actually begun transferring data. So the
**
   TimeToExecute can be calculated as if the read request is not in
   progress.
**
************
void UpdateTimeToExecute(MemoryRequest)
  MemoryRequestType *MemoryRequest;
  SizeType WordsToBeTransfered;
  if (MemoryRequest->Size>0)
     WordsToBeTransfered=WordAddress (MemoryRequest->Address
                                    +MemoryRequest->Size-1)
                        -WordAddress (MemoryRequest->Address) +WordSize;
     }
  else
     WordsToBeTransfered=0;
  WordsToBeTransfered/=WordSize;
   if (WordsToBeTransfered>(BlockSize/WordSize))
     WordsToBeTransfered=BlockSize/WordSize;
```

\*\*\*\*\*\*\*

: . , ,

```
Page 6- 4
                              TimeEst.c
                         UpdateTimeToExecute
                              continued
       if (WordsToBeTransfered>0)
  if (MemoryRequest->AccessInProgress==No)
     MemoryRequest->TimeToExecute=MemoryAccessTime
                       +MemoryTransferTime* (WordsToBeTransfered-1);
  else
     if (MemoryWaitingFor==MemoryWaitingForMemoryReadAccess | |
         MemoryWaitingFor==MemoryWaitingForMemoryReadTransfer)
        MemoryRequest->TimeToExecute=TOA-Time+MemoryTransferTime
                                   *(WordsToBeTransfered-1);
     else if (MemoryWaitingFor==MemoryWaitingForMemoryWriteAccess ||
              MemoryWaitingFor==MemoryWaitingForMemoryWriteTransfer)
        MemoryRequest->TimeToExecute=TOD-Time+MemoryTransferTime
                                   *(WordsToBeTransfered-1);
     else if (MemoryWaitingFor==MemoryWaitingForCacheUpdate)
        MemoryRequest->TimeToExecute=MemoryAccessTime+MemoryTransferTime
                                   *(WordsToBeTransfered-1);
     else
        printf("Error found in [UpdateTimeToExecute] MemoryRequest\n");
        printf("with access in progress while MemoryWaitingFor not\n");
        printf("reading or writing.");
        DiscrepancyFound=Yes;
   }
else
  MemoryRequest->TimeToExecute=0;
```

```
Page 6-5
                                 TimeEst.c
                                                                        **
                          CalculateTimeEstimates
   Description:
        CalculateTimeEstimates updates the CompletionTimeEstimates for
   each request in both the read and write buffers. This funtion is
   called when ever the CacheModel adds to the read or write buffers.
   CalculateTimeEstimates must be called every time new data is entered
   into the buffers. This is because all previous estimates did not take **
   into account the new data requested. This is because all previous
   estimates did not take into account the new data requested.
                                                                        **
   CalculateTimeEstimates first orders all entries in both the ReadBuffer, **
   and the WriteBuffer by priority. Then CalculateTimeEstimates steps
** though both buffers simultaneously. Each time picking the request that **
** has the highest priority, and adding the time to execute to the
** TimeEstimate. The TimeEstimate becomes that requests
** CompletionTimeEstimate. This process is repeated until all requests
                                                                        **
   have a new CompletionTimeEstimate. TimeToExecute for cache request is
                                                                        **
   updated before it is used to calculate the TimeEstimate.
                                                                        **
      ------
void CalculateTimeEstimates()
  1
  BufferSizeType ReadIndex=0;
  BufferSizeType WriteIndex=0;
             TimeEstimate=Time;
  TimeType
  TimeType
                BlockTOAEstimate=BlockTOA;
  Order (&ReadBuffer);
  Order (&WriteBuffer);
```

\*\*\*\*\*\*\*\*\*

```
Page 6- 6
..
                                 TimeEst.C
                           CalculateTimeEstimates
                                 continued
  while (ReadIndex<ReadBuffer.Next || WriteIndex<WriteBuffer.Next)</pre>
     if (ReadIndex<ReadBuffer.Next && WriteIndex<WriteBuffer.Next)</pre>
        if (ReadBuffer.MemoryRequest[ ReadIndex ].Priority <=</pre>
            WriteBuffer.MemoryRequest[WriteIndex].Priority)
           UpdateTimeToExecute(&(ReadBuffer.MemoryRequest[ReadIndex]));
           if (TimeEstimate<BlockTOAEstimate) TimeEstimate=BlockTOAEstimate;</pre>
           TimeEstimate+=ReadBuffer.MemoryRequest[ReadIndex].TimeToExecute;
           ReadBuffer.MemoryRequest[ReadIndex].CompletionTimeEstimate=
              TimeEstimate;
           BlockTOAEstimate=TimeEstimate+BufferCacheAccessTime;
           ReadIndex++;
        else
           UpdateTimeToExecute(&(WriteBuffer.MemoryRequest[WriteIndex]));
           TimeEstimate+=WriteBuffer.MemoryRequest[WriteIndex].TimeToExecute;
           WriteBuffer.MemoryRequest[WriteIndex].CompletionTimeEstimate=
              TimeEstimate;
           WriteIndex++;
     else if (ReadIndex<ReadBuffer.Next)</pre>
        UpdateTimeToExecute(&(ReadBuffer.MemoryRequest[ReadIndex]));
        TimeEstimate+=ReadBuffer.MemoryRequest.ReadIndex].TimeToExecute;
        ReadBuffer.MemoryRequest [ReadIndex].CompletionTimeEstimate=
           TimeEstimate;
        BlockTOAEstimate=TimeEstimate+BufferCacheAccessTime;
        ReadIndex++;
     else if (WriteIndex<WriteBuffer.Next)</pre>
        UpdateTimeToExecute(&(WriteBuffer.MemoryRequest[WriteIndex]));
        TimeEstimate+=WriteBuffer.MemoryRequest[WriteIndex].TimeToExecute;
        WriteBuffer.MemoryRequest[WriteIndex].CompletionTimeEstimate=
           TimeEstimate;
        WriteIndex++;
     }
  }
```

Page 7-0 \*\* Get.c Part Of SACS 1.0 (StillAnother Cache Simulator) \*\* \*\* Program Modified: 3/17/94 File Modified: 3/17/94 \*\* \*\* Author: William G. Smith Address: Electrical Engineering Department Naval Postgraduate School Monterey, CA 93940 \*\* \*\* Copyright 1994, William G. Smith Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted provided that the above copyright notice appears in all copies. No \*\* modified version of this program should be redistributed without the \*\* \*\* authors consent. William G. Smith makes no warranty or \*\* representation, promise of guarantee, either expressed or implied, \*\* with respect to this software's ability to produce valid results. \*\* \*\* This program is provided "as is" any financial, personal or property \*\* \*\* damage caused by the use of this program is the responsibility of the \*\* \*\* user. \*\*

\*

/**	*************	***
**	Page 7- 1	**
**	Get.c	**
**		**
**	Description:	**
**		**
**	Get.c contains all functions that relate getting the next CPU	**
**	request. GetNextRequest is the only procedure called outside of this	**
**	file scope. It determines whether to take input from the keyboard or	**
**	an input file. It also checks the input data to see if it makes sense.	**
**	•	**
**	Table of Contents	**
**		**
**	Cover Page Page 7- 1	**
**	List of Get.c Function Declarations Page 7-2	**
**	GetNextRequest() Page 7-3	**
**	GetNextFileRequest() Page 7-5	**
**	GetNextKeyBoardRequest() Page 7- 6	**
**		**

<sup>#</sup>include "Global.h"

```
/*************************
**
                                               Page 7-2 **
                          Get.c
                                                         **
               List of Get.c Function Declarations
                                                         **
** Description:
                                                         **
     This is a list of function declarations within the file scope
** of "Get.c".
                                                         **
**
                                                         **
void GetNextRequest();
                                               /* Page 7-3 */
                                               /* Page 7-5 */
/* Page 7-6 */
void GetNextFileRequest();
void GetNextKeyBoardRequest();
```

```
***********
                                                     Page 7-3 **
                              Get.c
**
                          GetNextRequest
**
                                                                **
** Description:
**
                                                                **
**
                                                                **
       GetNextRequest gets the next simulated request from the CPU to
** cache (ie a Read or Write request). The request is checked to make
                                                                **
                                                                **
** sure it makes sense. If a request is not block alined, then
                                                                **
** GetNextRequest will split the request up and return portions of the
** request until all portions have been used, as if the user had made
** several different requests.
*******************************
void GetNextRequest()
  {
  static AddressType NextRequestAddress;
  static SizeType NextRequestSize=0;
  static RequestType NextRequest;
```

```
Page 7- 4
                                  Get.c
                             GetNextRequest
                               continued
if (NextRequestSize>0)
   if (NextRequestSize<=BlockSize)</pre>
     RequestSize=NextRequestSize;
     NextRequestSize=0;
  else
      RequestSize=BlockSize;
     NextRequestSize-=BlockSize;
   RequestAddress=BlockAddress(RequestAddress)+BlockSize;
   Request=NextRequest;
else
   if (KeyBoardIO)
      PauseForCommand();
      GetNextKeyBoardRequest();
   else
      GetNextFileRequest();
   if (BlockAddress(RequestAddress)!=
       BlockAddress(RequestAddress+RequestSize-1))
      NextRequestSize=RequestSize;
      RequestSize=(BlockAddress(RequestAddress)+BlockSize)-RequestAddress;
      NextRequestSize-=RequestSize;
      NextRequestAddress=BlockAddress(RequestAddress)+BlockSize;
      NextRequest=Request;
   }
if (Request!=None)
   LastRequest=Request;
   NumberOfAccesses [Request] ++;
}
```

```
Page 7- 5
                                  Get.c
                           GetNextFileRequest
   Description:
                                                                         **
        GetNextFileRequest reads in one request, without doing any error
**
                                                                         **
   checking.
***************
void GetNextFileRequest()
   char RequestChar=' ',
       Chr;
  Request=None;
   if (feof(DataFile)) EndOfDataFile=Yes;
  while (RequestChar!='r' && RequestChar!='w' && RequestChar!='E' &&
         EndOfDataFile==No && !feof(DataFile))
      fscanf(DataFile, "%c", &RequestChar);
   if (feof(DataFile) || RequestChar=='E') EndOfDataFile=Yes;
   if (EndOfDataFile==No)
      {
      fscanf(DataFile,"%lX", &RequestAddress);
      fscanf(DataFile, "%u", &RequestSize);
      fscanf(DataFile, "%U", &TimeOfNextRequest);
      if (RequestChar=='r') Request=Read;
      if (RequestChar=='w') Request=Write;
     TimeOfNextRequest+=Time;
     while (RequestChar!='\n' && !feof(DataFile))
        fscanf(DataFile, "%c", &RequestChar);
   if (feof(DataFile)) EndOfDataFile=Yes;
   }
```

```
Page 7-6 **
                                Get.c
                                                                    **
                           GetNextBoardKey
                                                                    **
                                                                    **
  Description:
                                                                    **
        GetNextFileRequest reads in one request, without doing any error
                                                                    **
                                                                    **
   checking.
                                                                    **
void GetNextKeyBoardRequest()
  {
  char chr;
  printf("Please enter request type (r,w). ");
  while (chr!='r' && chr!='w' && chr!='q')
    scanf("%c", &chr);
    }
  if (chr=='q') exit(0);
  if (chr=='r') Request=Read; else Request=Write;
  printf("Please enter Address ");
  scanf("%U", &RequestAddress);
  printf("Please enter size ");
  scanf("%u", &RequestSize);
  printf("Time until next request. ");
  fflush(stdin);
  scanf("%U", &TimeOfNextRequest);
  TimeOfNextRequest+=Time;
   }
```

\*\* Page 8-0 \*\* Display.c Part Of SACS 1.0 (StillAnother Cache Simulator) \*\* \*\* \*\* Program Modified: 3/17/94 \*\* File Modified: 3/17/94 \*\* \*\* Author: William G. Smith \*\* \*\* Address: Electrical Engineering Department \*\* \*\* Naval Postgraduate School \*\* \*\* Monterey, CA 93940 \*\* \*\* \*\* Copyright 1994, William G. Smith \*\* \*\* \*\* \*\* Permission to use, copy, modify, and distribute this software and \*\* \*\* its documentation for any purpose and without fee is hereby granted \*\* \*\* provided that the above copyright notice appears in all copies. No \*\* \*\* modified version of this program should be redistributed without the \*\* \*\* \*\* authors consent. William G. Smith makes no warranty or representation, promise of guarantee, either expressed or implied, \*\* \*\* with respect to this software's ability to produce valid results. \*\* \*\* This program is provided "as is" any financial, personal or property \*\* \*\* damage caused by the use of this program is the responsibility of the \*\* \*\*

\*

/**	**********	****	*****	*****	***
**			Page	8- 1	**
**	Display.c		90	-	**
**	• 1				**
**	Description:				**
**					**
**	Display.c contains all display functions used w	ithin	SACS.		**
**					**
**	Table of Contents				**
**					**
**	Cover Page	Page	8- 1		**
**	List of Cache.c Function Declarations		8- 2		**
**	DisplayTrace()		8- 3		**
**	DisplayCurrentRequest()		8- 4		**
**	DisplayWaitingFors()		8- 5		**
**	DisplayBlock()		8- 6		**
**	DisplayBuffers()		8- 7		**
**	DisplayBuffer()		8 -8		**
**	• •	-			**
**	DisplayRequestsBreakDown()	Page	8- 9		**
**	DisplayRequestHistogram()		8-11		**
**	• • •	-			**
**	<pre>DisplayStallHistogram()</pre>	Page	8-13		**
**	LastScreenHistogramScore()		8-14		**
**	DisplayCacheArguments()		8-15		**
**	DisplayHelp()		8-17		**
**		•			**
**	<pre>DisplayTestingHeader()</pre>	Page	8-18		**
**	• •	-			**
**	PrintTime()	Page	8-20		°c <b>★</b>
**	<pre>PrintTimeCentered()</pre>	Page	8-20		**
**	<pre>PrintScoreCentered()</pre>	Page	8-20		**
**	<pre>PrintAddress()</pre>	Page	8-20		**
**	<pre>PrintCacheSize()</pre>	Page	8-20		**
**	PrintSize()	Page	8-20		**
**	PrintSize2()	Page	8-20		**
**	PrintBufferSize()	Page	8-21		**
* *	PrintPriority()	Page	8-21		**
**	PrintAssociativity()		8-21		**
**	<pre>PrintHistogramIndex()</pre>	Page	8-21		**
**					**
**	PrintBit()		8-22		**
**	<pre>PrintPercent()</pre>		8-22		**
**	PrintAveAccess()	Page	8-22		**
**		-			**
				*****	++/

#include "Global.h"

```
Page 8-2 **
                                           Display.c
                                                                                                 **
                                                                                                 **
                        List of Display.c Function Declarations
**
** Description:
**
                                                                                                 **
**
           This is a list of function declarations within the file scope
                                                                                                 **
                                                                                                 **
** of "Display.c".
******************************
           DisplayTrace();
                                                                               /* Page 8-3 */
void
                                                                               /* Page 8-4 */
              DisplayCurrentRequest();
void
                                                                               /* Page 8-5 */
void
              DisplayWaitingFors();
void
              DisplayBlock();
                                                                               /* Page 8-6 */
void
              DisplayBuffers();
                                                                               /* Page 8-7 */
void
                   DisplayBuffer();
                                                                               /* Page 8-8 */
                                                                               /* Page 8-9 */
void DisplayRequestsBreakDown();
               DisplayRequestHistogram();
                                                                              /* Page 8-11 */
void
          DisplayStallHistogram();
                                                                              /* Page 8-13 */
void
ScoreType LastScreenHistogramScore();
                                                                               /* Page 8-14 */
        DisplayCacheArguments();
DisplayHelm().
                                                                               /* Page 8-15 */
void
                                                                               /* Page 8-17 */
void
void DisplayTestingHeader();
                                                                               /* Page 8-18 */
void PrintYesNo();
void PrintRequest();
void PrintReplacementPolicy();
void PrintWritePolicy();
void PrintWriteMissPolicy();
void PrintWaitingFor();
void PrintMemoryWaitingFor();
void PrintBlockWaitingFor();
                                                                               /* Page 8-19 */
                                                                               /* Page 8-19 */
void     PrintTime();
void     PrintTimeCentered();
void     PrintScoreCentered();
void     PrintAddress();
void     PrintCacheSize();
void     PrintSize();
void     PrintSize2();
void     PrintBufferSize();
void     PrintPriority();
void     PrintAssociativity();
void     PrintHistogramIndex();
                                                                               /* Page 8-20 */
                                                                               /* Page 8-21 */
                                                                               /* Page 8-21 */
                                                                               /* Page 8-21 */
                                                                               /* Page 8-21 */
void PrintBit();
void PrintPercent();
                                                                               /* Page 8-22 */
                                                                               /* Page 8-22 */
void
           PrintAveAccess();
                                                                               /* Page 8-22 */
```

```
/****************************
                                                       Page 8-3 **
                              Display.c
                             DisplayTrace
        **************************
void DisplayTrace()
  SizeType Block0=Set (RequestAddress) *Associativity;
  SizeType BlockIndex;
  SizeType SubBlockIndex;
  system(ClearScreen);
  DisplayCurrentRequest();
  DisplayWaitingFors();
  printf("\n");
  printf(" Set Block Address ");
  for (SubBlockIndex=0; SubBlockIndex<NumberOfSubBlocks; SubBlockIndex++)</pre>
     printf(" V/D ");
  printf("\n");
  for (BlockIndex=Block0; BlockIndex<Block0+Associativity; BlockIndex++)</pre>
     DisplayBlock(BlockIndex);
  printf("\n");
  DisplayBuffers();
   }
```

```
************
                                                           Page 8- 4
                               Display.c
                         DisplayCurrentRequest
          ************
void DisplayCurrentRequest()
  {
  if (Request!=None) LastRequest=Request;
  if (LastRequest==None)
     RequestAddress=0;
     RequestSize=0;
     CacheHit=No;
  if (Request!=None) LastRequest=Request;
  if (CacheWaitingFor!=Nothing)
     printf("\nCurrent Request:
                                 ");
  else
     printf("\nLast Request:
                                 ");
  PrintRequest (LastRequest);
                                                 ");
  printf("
                              Time:
  PrintTime(Time);
  printf("\nAddress:
                               ");
  PrintAddress (RequestAddress);
  printf("
                           Next Request Time: ");
  PrintTime(TimeOfNextRequest);
  printf("\nSize:
                              ");
  PrintSize2 (RequestSize);
  if (MemoryWaitingFor==MemoryWaitingForMemoryReadAccess ||
      MemoryWaitingFor==MemoryWaitingForMemoryReadTransfer)
                                                      ");
     printf("
                                    TOA:
     PrintTime (TOA);
   if (MemoryWaitingFor==MemoryWaitingForMemoryWriteAccess ||
      MemoryWaitingFor==MemoryWaitingForMemoryWriteTransfer)
     printf("
                                    TOD:
                                                      ");
     PrintTime (TOD);
  printf("\n");
  }
```

. .

```
/****************************
                                                            Page 8-6 **
                               Display.c
                               DisplayBlock
void DisplayBlock(BlockIndex)
  SizeType BlockIndex;
   {
  SizeType SubBlockIndex;
  if (BlockIndex%Associativity==0)
     PrintSize(BlockIndex/Associativity);
  else
     printf(" ");
  printf(" ");
  PrintSize(BlockIndex);
  printf(" ");
  PrintAddress(CacheBlockAddress[BlockIndex]);
   for (SubBlockIndex=0; SubBlockIndex<NumberOfSubBlocks; SubBlockIndex++)</pre>
     1
     printf(" ");
     PrintBit (CacheValidBit [BlockIndex] [SubBlockIndex]);
     printf(" ");
     PrintBit (CacheDirtyBit [BlockIndex] (SubBlockIndex]);
     printf(" ");
  printf("\n");
```

```
/***********************
                                               Page 8-7 **
                         Display.c
                        DisplayBuffers
           **********************
void DisplayBuffers()
  {
  printf("Read Buffer ");
  DisplayBuffer(&ReadBuffer);
  printf("\n");
  printf("Write Buffer ");
  DisplayBuffer(&WriteBuffer);
  printf("\n");
  printf("Block Buffer ");
  DisplayBuffer(&BlockBuffer);
  }
```

```
/***********************************
                                                        Page 8-8
                              Display.c
                            DisplayBuffer
                   *******************
void DisplayBuffer(PrintBuffer)
  BufferType *PrintBuffer;
  {
  int R;
  printf("Address
                   Size
                         Req. Block Priority");
  printf(" Time Req. Comp. Time\n");
  for (R=0; R<PrintBuffer->Next; R++)
     printf("
     PrintAddress(PrintBuffer->MemoryRequest[R].Address);
     printf(" ");
     PrintSize2(PrintBuffer->MemoryRequest(R).Size);
                ");
     PrintSize2(PrintBuffer->MemoryRequest[R].RequiredSize);
     printf("
     PrintSize(PrintBuffer->MemoryRequest[R].Block);
               ");
     printf("
     PrintPriority(PrintBuffer->MemoryRequest[R].Priority);
     printf("
                ");
     PrintTimeCentered(PrintBuffer->MemoryRequest[R].TimeToExecute);
     printf("
              ");
     PrintTimeCentered(PrintBuffer->MemoryRequest[R].CompletionTimeEstimate);
     printf("\n");
  }
```

```
Page 8- 9
                                 Display.c
                                                                           **
                           DisplayRequestBreakDown
                                                                           **
       **********************
void DisplayRequestsBreakDown()
   {
   ScoreType
      TotalNumberOfAccesses = NumberOfAccesses [Read] + NumberOfAccesses [Write].
      TotalNumberOfCacheHits=NumberOfCacheHits[Read]+NumberOfCacheHits[Write],
      TotalNumberOfBufferHits=NumberOfBufferHits[Read]+NumberOfBufferHits[Write];
   system(ClearScreen);
  printf("\n
                                           Requests Break Down\n");
                   ");
  printf("\n
  printf("
                        Number
                                     Number
                                                 Number
                                                                            ");
                  ");
  printf("\n
  printf("Request
                          of
                                       of
                                                   of
                                                                Hit
                                                                         Miss ");
   printf("\n
                   ");
  printf(" Types
                                 Cache Hits Buffer Hits
                       Requests
                                                               Rates
                                                                         Rates");
   printf("\n");
   printf("\n
                   Read
   PrintScoreCentered(NumberOfAccesses(Read]);
   printf("
               ");
   PrintScoreCentered(NumberOfCacheHits[Read]);
   printf("
              ");
   PrintScoreCentered(NumberOfBufferHits(Read));
   if (NumberOfAccesses[Read]>0)
     printf("
     PrintPercent (NumberOfCacheHits [Read] + NumberOfBufferHits [Read],
                  NumberOfAccesses(Read));
      printf("
     PrintPercent ((NumberOfAccesses[Read]-NumberOfCacheHits[Read]),
                   NumberOfAccesses [Read]);
      }
                                ");
   printf("\n
                   Write
   PrintScoreCentered(NumberOfAccesses[Write]);
   printf("
   PrintScoreCentered(NumberOfCacheHits[Write]);
   printf("
               ");
   PrintScoreCentered(NumberOfBufferHits[Write]);
   if (NumberOfAccesses[Write]>0)
      printf("
      PrintPercent (NumberOfCacheHits[Write] + NumberOfBufferHits[Write],
                  NumberOfAccesses[Write]);
                 ");
      printf("
      PrintPercent((NumberOfAccesses[Write]-NumberOfCacheHits[Write]),
                   NumberOfAccesses(Write));
      }
```

```
Page 8-10
                            Display.c
                      DisplayRequestBreakDown
                            continued
    ************
printf("\n
               Total
                          ");
PrintScoreCentered(TotalNumberOfAccesses);
printf(" ");
PrintScoreCentered(TotalNumberOfCacheHits);
printf(" ");
PrintScoreCentered(TotalNumberOfBufferHits);
if (TotalNumberOfAccesses>0)
  printf("
               ");
  PrintPercent (TotalNumberOfCacheHits+TotalNumberOfBufferHits,
              TotalNumberOfAccesses);
            ۳);
  printf("
  PrintPercent (TotalNumberOfAccesses-TotalNumberOfCacheHits
                                  -TotalNumberOfBufferHits,
              TotalNumberOfAccesses);
  }
printf("\n");
DisplayRequestHistogram();
}
```

```
/******************************
                                                       Page 8-11 **
                              Display.c
                                                                   **
                        DisplayRequestHistogram
                                                                   **
       *************************
void DisplayRequestHistogram()
  {
  SizeType TimeIndex;
  printf("\n
                                      Request Time Histogram");
                     ");
  printf("\n
  for (TimeIndex=0; TimeIndex<ScreenHistogramMaxIndex; TimeIndex++)</pre>
     printf("
                   ");
  printf(" Ave ");
printf("\n ").
  for (TimeIndex=0; TimeIndex<ScreenHistogramMaxIndex; TimeIndex++)</pre>
     printf("
  printf("
                  Access");
  printf("\n
                     ");
  for (TimeIndex=0; TimeIndex<ScreenHistogramMaxIndex-1; TimeIndex++)</pre>
     printf(" Time=");
     PrintSize2(TimeIndex);
  printf(" Time>=");
  PrintSize2(TimeIndex);
  printf(" Total Time ");
```

```
*******
/***
                                                           Page 8-12
                               Display.c
                          DisplayRequestHistogram
**
                               continued
       ***************
  printf("\n
                 Read ");
  for (TimeIndex=0; TimeIndex<(ScreenHistogramMaxIndex-1); TimeIndex++)</pre>
     printf(" ");
     PrintScoreCentered(RequestTimeHistogram[Read][TimeIndex]);
  printf(" ");
  PrintScoreCentered(LastScreenHistogramScore(RequestTimeHistogram[Read]));
  printf(" ");
  PrintScoreCentered(TotalRequestTime[Read]);
  printf(" ");
  PrintAveAccess(TotalRequestTime[Read], NumberOfAccesses[Read]);
  printf("\n
                  Write ");
  for (TimeIndex=0; TimeIndex<(ScreenHistogramMaxIndex-1); TimeIndex++)
     printf(" ");
     PrintScoreCentered(RequestTimeHistogram[Write][TimeIndex]);
  printf(" ");
  PrintScoreCentered(LastScreenHistogramScore(RequestTimeHistogram[Write]));
  printf(" ");
  PrintScoreCentered(TotalRequestTime[Write]);
  printf(" ");
  PrintAveAccess(TotalRequestTime[Write], NumberOfAccesses[Write]);
                  Ideal ");
  printf("\n
  for (TimeIndex=0; TimeIndex<(ScreenHistogramMaxIndex-1); TimeIndex++)
     printf(" ");
     PrintScoreCentered(RequestTimeHistogram[None][TimeIndex]);
  printf(" ");
  PrintScoreCentered(LastScreenHistogramScore(RequestTimeHistogram[None]));
  printf(" ");
  PrintScoreCentered(TotalRequestTime[None]);
  printf("\n");
  }
```

```
Page 8-13
                                  Display.c
                            DisplayStallHistogram
void DisplayStallHistogram()
   ł
   SizeType
                       TimeIndex:
   CacheWaitingForType StallIndex;
   system(ClearScreen);
  printf("\n\n
                                           Stall Time Histogram\n\n");
                               ");
  printf("
   for (TimeIndex=0; TimeIndex<ScreenHistogramMaxIndex-1; TimeIndex++)
      printf(" Time=");
      PrintSize2(TimeIndex);
   printf(" Time>=");
   PrintSize2(TimeIndex);
   printf(" Total\n");
   printf("\n");
   for (StallIndex=0;
        StallIndex<NumberOfCacheWaitingForsAvailable;
        StallIndex++)
      PrintWaitingFor(StallIndex);
      for (TimeIndex=0;TimeIndex<ScreenHistogramMaxIndex-1;TimeIndex++)</pre>
         printf(" ");
         PrintScoreCentered(StallTimeHistogram[StallIndex][TimeIndex]);
      printf(" ");
      PrintScoreCentered(LastScreenHistogramScore(StallTimeHistogram[StallIndex]));
      printf(" ");
      PrintScoreCentered(TotalStallTime[StallIndex]);
      printf("\n");
   }
```

```
*********
* *
                                                              Page 8-15
                                 Display.c
                                                                          **
                           DisplayCacheArguments
                   **********
void DisplayCacheArguments()
  ł
  system(ClearScreen);
  printf("\n");
  printf("
                                       Cache Arguments List");
  printf("\n");
  printf("\nCache Size:
                                      "); PrintCacheSize(CacheSize);
                 ۳);
  printf("
  printf("Read Forward:
                                      "); PrintYesNo(ReadForward);
  printf("\nBlock Size:
                                      "); PrintSize(BlockSize);
                    ");
  printf("
  printf("CPU Waits For Cache Writes: "); PrintYesNo(CPUWaitsForCacheWrites);
  printf("\nSubBlock Size:
                                      "); PrintSize(SubBlockSize);
  printf("
                    ");
  printf("Search Block Buffer:
                                      "); PrintYesNo(SearchBlockBuffer);
  printf("\nAssociativity:
                                      "); PrintAssociativity(Associativity);
  printf("
  printf("Update Read Buffer:
                                      "); PrintYesNo(UpdateReadBuffer);
  printf("\nWord Size:
                                      "); PrintSize(WordSize);
                    ");
  printf("
  printf("Remove Read Duplicates:
                                      "); PrintYesNo(RemoveReadDuplicates);
  printf("\nRead Cache Access Time:
                                      "); PrintTime (ReadCacheAccessTime);
  printf("
                 ");
  printf("Remove Write Duplicates:
                                      "); PrintYesNo(RemoveWriteDuplicates);
  printf("\nRead Cache Hit Time:
                                      "); PrintTime (ReadCacheHitTime);
  printf("
                 ");
  printf("Read Priority:
                                      "); PrintPriority(ReadPriority);
                                      "); PrintTime (ReadCacheMissTime);
  printf("\nRead Cache Miss Time:
   printf("
                 ");
  printf("Write Priority:
                                      "); PrintPriority(WritePriority);
  printf("\nWrite Cache Access Time:
                                      "); PrintTime(WriteCacheAccessTime);
  printf("
                 ");
  printf("Read For Write Allocate:
                                      ");
      PrintPriority (ReadForWriteAllocate riority);
  printf("\nWrite Cache Hit Time:
                                      "); PrintTime(WriteCacheHitTime);
   printf("
                  ");
   printf("Write Dirty Block Priority: ");
      PrintPriority(WriteDirtyBlockPriority);
   printf("\nWrite Cache Miss Time: "); PrintTime(WriteCacheMissTime);
   printf("
                  ");
   printf("No Priority:
                                      "); PrintPriority(NoPriority);
```

```
Page 8-16 **
                            Display.c
                                                                   **
                       DisplayCacheArguments
                                                                   **
                            continued
                                                                   ++
    -----
printf("\nMemory Access Time: "); PrintTime(MemoryAccessTime);
printf(" ");
printf("Trace:
                                 "); PrintYesNo(Trace);
printf("\nMemory Transfer Time: "); PrintTime(MemoryTransferTime);
printf("
           ");
printf("Check:
                                 "); PrintYesNo(Check);
printf("\nBuffer Cache Access Time: "); PrintTime(BufferCacheAccessTime);
printf("Test:
                                 "); PrintYesNo(Test);
printf("\nRead Buffer Size:
                                 "); PrintBufferSize(ReadBufferSize);
printf("
printf("Key Board IO:
                                 "); PrintYesNo(KeyBoardIO);
printf("\nWrite Buffer Size:
                                 "); PrintBufferSize(WriteBufferSize);
printf("
printf("Data File Name:
                                 %s", DataFileName);
printf("\nBlock Replacement Policy: ");
  PrintReplacementPolicy(BlockReplacementPolicy);
printf("
           ");
printf("Screen History Max Index: ");
  PrintHistogramIndex(ScreenHistogramMaxIndex);
printf("\nWrite Policy
                                 "); PrintWritePolicy(WritePolicy);
printf(" ");
printf("File History Max Index:
   PrintHistogramIndex(FileHistogramMaxIndex);
printf("\nWrite Miss Policy: ");
  PrintWriteMissPolicy(WriteMissPolicy);
printf("\n");
}
```

•

```
*********
                                                          Page 8-17 **
                               Display.c
                                                                       **
                              DisplayHelp
                                                                       **
            void DisplayHelp()
  {
  system(ClearScreen);
                                   Help Menu
  printf("
                                                                      ");
  printf("\n");
  printf("\n [T] Trace Display:
                                                                      ");
  printf("\n Displays current request, status of memory, and contents ");
  printf("\n
               of buffers.
                                                                      ");
  printf("\n");
  printf("\n [R] Results Display:
                                                                      ");
  printf("\n Displays a break down of read and write cache hits, and ");
  printf("\n
               buffer hits, including a timing analysis.
                                                                      ");
  printf("\n");
  printf("\n [S] Stall Timing Display:
                                                                      ");
  printf("\n Displays a histogram of the time spent on each stall.
                                                                      ");
  printf("\n Stalls represent time delays in completing a request
                                                                      ");
  printf("\n");
  printf("\n [C] Cache Arguments Display:
                                                                      ");
  printf("\n Displays input arguments to SACS.
                                                                      ");
  printf("\n");
  printf("\n [G] Go: Go to end of run.
printf("\n [G #] Go To: Go to Time #.
printf("\n [#] Step: Increment Time By #.
                                                                      ");
                                                                      ");
                                                                      ");
  printf("\n [-#] Back Step: Decrement Time By #.
                                                                      ");
  printf("\n [H] Help: Displays this help menu.
                                                                      ");
  printf("\n
                                                                      ");
  }
```

```
Page 8-18 **
                                   Display.c
                              DisplayTestingHeader
void DisplayTestingHeader()
   {
   printf("\n");
   system(ClearScreen);
   printf("\n\n");
printf("\n\n
                                ");
                             Testing SACS");
   printf("
   printf("\n\n
                                ");
   printf("Total number of loads and stores tested %lu.",
           TotalNumberOfAccesses);
   printf("\n\n
                               ");
   printf("
                       Test Cases chosen ... ");
   printf("\r.\n");
   }
```

```
/*********************
* *
                                                          Page 8-19 **
                              Display.c
                                                                     **
                                                                     **
                        Print Enumeration Stings
      *******************
void PrintYesNo(Value)
  YesNoType Value;
  printf("%s", YesNoString[Value]);
void PrintRequest (Value)
  RequestType Value;
  printf("%s", RequestString[Value]);
void PrintReplacementPolicy(Value)
  BlockReplacementPolicyType Value;
  printf("%s", ReplacementPolicyString[Value]);
void PrintWritePolicy(Value)
  WritePolicyType Value;
  printf("%s", WritePolicyString[Value]);
void PrintWriteMissPolicy(Value)
  WriteMissPolicyType Value;
  printf("%s", WriteMissPolicyString[Value]);
void PrintWaitingFor(Value)
  CacheWaitingForType Value;
  printf("%s", CacheWaitingForString[Value]);
void PrintMemoryWaitingFor(Value)
  MemoryWaitingForType Value;
  printf("%s", MemoryWaitingForString[Value]);
void PrintBlockWaitingFor(Value)
  BlockWaitingForType Value;
  printf("%s",BlockWaitingForString(Value));
```

```
/************************************
**
                                                            Page 8-20 **
                                Display.c
                                                                        ++
                                                                        ++
                             Print Routines
               void PrintTime(Time)
  TimeType Time;
  if
          (Time>=10000000) printf("%8lu", Time);
  else if (Time>=1000000 ) printf("%7lu ",Time);
  else if (Time>=100000 ) printf("%6lu ",Time);
  else if (Time>=10000 ) printf("%5lu
                                         ", Time);
  else if (Time>=1000 ) printf("%4lu else if (Time>=100 ) printf("%3lu
                                          ", Time);
  else if (Time>=100
                                           ", Time);
  else if (Time>=10
                       ) printf("%2lu
                                            ", Time);
                         printf("%11u
                                            ", Time);
  else
void PrintTimeCentered(Time)
  TimeType Time;
  if
          (Time>=1000000) printf("%8lu", Time);
  else if (Time>=10000 ) printf("%7lu ",Time);
                     ) printf("%6lu ",Time);
  else if (Time>=100
                         printf("%5lu ",Time);
  else
void PrintScoreCentered(Score)
  ScoreType Score;
          (Time>=1000000) printf("%8lu", Score);
   if
  else if (Time>=10000 ) printf("%71u ",Score);
  else if (Time>=100 ) printf("%6lu ",Score);
  else
                         printf("%5lu ",Score);
   }
void PrintAddress(Address)
  AddressType Address;
  printf("%081X", Address);
void PrintCacheSize(CacheSize)
  CacheSizeType CacheSize;
  printf("%08lu", CacheSize);
void PrintSize(Size)
  SizeType Size;
  printf("%05u", Size);
void PrintSize2(Size)
  SizeType Size;
  printf("%02u", Size);
```

```
*******
**
                                                     Page 8-21 **
                            Display.c
                                                                **
                          Print Routines
                           continued
       *************************
void PrintBufferSize(BufferSize)
  BufferSizeType BufferSize;
  printf("%02u", BufferSize);
void PrintPriority(Priority)
  PriorityType Priority;
  printf("%02u",Priority);
void PrintAssociativity(Associativity)
  AssociativityType Associativity;
  printf("%02u", Associativity);
void PrintHistogramIndex(HistogramIndex)
  HistogramIndexType HistogramIndex;
  printf("%04u", HistogramIndex);
```

```
/**********************************
                                                           Page 8-22 **
                               Display.c
                            Print Routines
                              continued
void PrintBit(Bit)
  YesNoType Bit;
  printf("%01u",Bit);
void PrintPercent (Numerator, Denominator)
  ScoreType Numerator;
  ScoreType Denominator;
  if (Denominator>0)
     printf("%6.21f",(100.0*Numerator)/Denominator);
     printf("%");
  else
     printf(" ");
void PrintAveAccess(TotalTime, TotalNumberofAccesses)
  TimeType TotalTime;
  ScoreType TotalNumberofAccesses;
  if (TotalNumberofAccesses>0)
     printf("%8.61f",(1.0*TotalTime)/TotalNumberofAccesses);
  else
     printf("
                    ");
   }
```

Page 9-0 \*\* Record.c \*\* \*\* Part Of SACS 1.0 \*\* (StillAnother Cache Simulator) \*\* Program Modified: 3/17/94 File Modified: 3/17/94 \*\* \*\* Author: William G. Smith \*\* Address: Electrical Engineering Department \*\* Naval Postgraduate School \*\* Monterey, CA 93940 \*\* \*\* Copyright 1994, William G. Smith \*\* \*\* \*\* \*\* Permission to use, copy, modify, and distribute this software and \*\* its documentation for any purpose and without fee is hereby granted provided that the above copyright notice appears in all copies. No \*\* modified version of this program should be redistributed without the \*\* authors consent. William G. Smith makes no warranty or \*\* representation, promise of guarantee, either expressed or implied, \* \* with respect to this software's ability to produce valid results. \* \* This program is provided "as is" any financial, personal or property \*\* \*\* damage caused by the use of this program is the responsibility of the \*\* user.

\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*

/**	***************	***			
**	Page 9-1	**			
**	Record.c	**			
**		**			
**	Description:	**			
**	•	**			
**		**			
**	Record.c contains all functions that relate to the recording of	**			
**	time for requests, and waiting fors, as well as a procedure for saving	**			
**	the data in a file using a format that Matlab(TM) could read.	**			
**		**			
**	Table of Contents	**			
**		**			
**	Cover Page Page 9- 1	**			
**	List of Record.c Function Declarations Page 9-2	**			
**	RecordRequest() Page 9- 3	**			
**	RecordStall() Page 9-5	**			
**	RecordForMatlab() Page 9-7	**			
**		**			
***	***********************				

#include "Global.h"

```
/*************************
                                                   Page 9-2 **
**
**
                           Record.c
**
                                                             **
**
               List of Record.c Function Declarations
                                                             **
**
** Description:
                                                             **
                                                             **
** This is a list of function declarations within the file scope
** of "Record.c".
                                                            **
void RecordRequest();
void RecordStall();
void RecordForMatlab();
                                                  /* Page 9-3 */
/* Page 9-5 */
/* Page 9-7 */
```

```
************
                                                           Page 9-3 **
                                                                     **
                               Record.c
                                                                     **
                             Record Request
**
   Description:
* *
                                                                     **
**
        RecordRequest records the time spent on a particular request and
   stores the result in RequestTimeHistogram.
**
                                                                     **
**
**************
void RecordRequest (Req)
  RequestType Req;
  static TimeType LastTime=1;
static TimeType Lastdt=0;
  static RequestType LastReq=NumberOfRequestsAvailable;
         TimeType     dt=Time-LastTime;
   if (Req==NumberOfRequestsAvailable)
     LastTime=1;
     Lastdt=0;
     LastReq=Req;
   else if (Req==LastReq)
     TotalRequestTime[LastReq]-=Lastdt;
     if (Lastdt>FileHistogramMaxIndex-1) Lastdt=FileHistogramMaxIndex-1;
     RequestTimeHistogram[LastReq][Lastdt]--;
   else if (LastReq!=NumberOfRequestsAvailable)
     LastTime=Time;
     dt=0;
     NumberOfCacheHits[LastReq]+=CacheHit;
     NumberOfBufferHits[LastReq]+=BufferHit;
   LastReq=Req;
```

```
Page 9-4 **
                                Record.c
                            Record Request
                               continued
if (Req!=NumberOfRequestsAvailable)
  TotalRequestTime(Req)+=dt;
  Lastdt=dt;
  if (dt>FileHistogramMaxIndex-1) dt=FileHistogramMaxIndex-1;
  if (Time>=LastTime)
     RequestTimeHistogram[Req][dt]++;
  else
     printf("\n\nError [RecordRequest] caculated a time less than 0");
     printf("\n\n
                   Time = "); PrintTime(Time);
     printf("\n\nLastTime = "); PrintTime(LastTime);
     printf("\n\n");
     DiscrepancyFound=Yes;
     }
   }
}
```

```
/*************************
**
                                                     Page 9-5 **
                            Record.c
**
                            RecordStall
                                                               **
                                                               **
** Description:
                                                               **
**
**
       RecordStall records the time spent on a particular waiting for and **
** stores the result in StallTimeHistogram.
**
void RecordStall(CurrentWaitingFor)
  CacheWaitingForType CurrentWaitingFor;
  static CacheWaitingForType PastWaitingFor=None;
        TimeType
                        dt=Time-PastTime;
  if (CurrentWaitingFor==NumberOfCacheWaitingForsAvailable)
    PastTime=1;
    Pastdt=0;
    PastWaitingFor=CurrentWaitingFor;
  else if (CurrentWaitingFor==PastWaitingFor)
     TotalStallTime[PastWaitingFor] -= Pastdt;
     if (Pastdt>FileHistogramMaxIndex-1) Pastdt=FileHistogramMaxIndex-1;
     StallTimeHistogram[PastWaitingFor][Pastdt]--;
  else if (PastWaitingFor!=NumberOfCacheWaitingForsAvailable)
     PastTime=Time;
     dt=0;
  PastWaitingFor=CurrentWaitingFor;
```

```
Page 9-6 **
                            Record.c
                            RecordStall
                             continued
if (CurrentWaitingFor!=NumberOfCacheWaitingForsAvailable)
    TotalStallTime(CurrentWaitingFor)+=dt;
    Pastdt=dt;
    if (dt>Fi eHistogramMaxIndex-1) dt=FileHistogramMaxIndex-1;
    if (Time>=PastTime)
       StallTimeHistogram[CurrentWaitingFor][dt]++;
    else
       printf("\n\nError [RecordStall] calculated a time less than 0");
       printf("\n\n Time = "); PrintTime(Time);
       printf("\n\nPastTime = "); PrintTime(PastTime);
       printf("\n\n");
       DiscrepancyFound=Yes;
       }
    }
```

```
/*****************************
                                                             Page 9-7 **
                                 Record.c
                              RecordForMatlab
   Description:
        RecordForMatlab saves the RequestTimeHistogram, and
  StallTimeHistograms in a format that Matlab(TM) reconizes.
**********************************
void RecordForMatlab()
  {
  CacheWaitingForType StallIndex;
                     RequestIndex;
  RequestType
  int
                     Column,
                     NumberOfColumns=2;
  HistogramIndexType HistogramIndex;
  FILE *MatlabOut;
  if ((MatlabOut=fopen("timing.m", "w")) == NULL)
     printf('Can not open matlab output file.");
   for (RequestIndex=0; RequestIndex<NumberOfRequestsAvailable; RequestIndex++)</pre>
     fprintf(MatlabOut, "%s=[", RequestString[RequestIndex]);
     fprintf(MatlabOut, " %08lu", RequestTimeHistogram[kequestIndex][0]);
     Column=1;
     for (HistogramIndex=1;
          HistogramIndex<FileHistogramMaxIndex;</pre>
          HistogramIndex++)
        Column++;
        if (Column>NumberOfColumns)
           Column=1;
           fprintf(MatlabOut, ", \n ");
        else
           fprintf(MatlabOut, ", ");
        fprintf(MatlabOut, " %08lu",
                RequestTimeHistogram[RequestIndex][HistogramIndex]);
        }
     fprintf(MatlabOut,"];\n\n");
```

```
**********
**
                                                             Page 9-8 **
                                 Record.c
                              RecordForMatlab
                                 Continued
  for (StallIndex=0;StallIndex<NumberOfCacheWaitingForsAvailable;StallIndex++)</pre>
     fprintf(MatlabOut, "%s=[", CacheWaitingForString[StallIndex]);
     fprintf(MatlabOut, " %08lu", StallTimeHistogram[StallIndex][0]);
     Column=1;
     for (HistogramIndex=1;
          HistogramIndex<FileHistogramMaxIndex;</pre>
          HistogramIndex++)
        Column++;
        if (Column>NumberOfColumns)
           Column=1;
           fprintf(MatlabOut, ", \n
                                                               ");
        else
           fprintf(MatlabOut, ", ");
        fprintf(MatlabOut, " %08lu",
                StallTimeHistogram[StallIndex][HistogramIndex]);
        }
     fprintf(MatlabOut,"];\n\n");
     }
  fclose (MatlabOut);
  }
```

Page 10- 0 \*\* Buffer.c \* \* Part Of SACS 1.0 (StillAnother Cache Simulator) \*\* \*\* Program Modified: 3/17/94 File Modified: 3/17/94 \*\* Author: William G. Smith \*\* Address: Electrical Engineering Department \*\* Naval Postgraduate School \*\* Monterey, CA 93940 \*\* \*\* Copyright 1994, William G. Smith \*\* Permission to use, copy, modify, and distribute this software and \*\* its documentation for any purpose and without fee is hereby granted \* \* provided that the above copyright notice appears in all copies. No modified version of this program should be redistributed without the authors consent. William G. Smith makes no warranty or representation, promise of guarantee, either expressed or implied, with respect to this software's ability to produce valid results. This program is provided "as is" any financial, personal or property \*\* damage caused by the use of this program is the responsibility of the \*\* \*\* user. \*\*

.

/**	***	***
**	Page 10- 1	**
**	Buffer.c	**
**		**
**	Description:	**
**	•	**
**	Buffer.c contains all functions that relate to the management of	**
**	the Read, Write, and Block Buffers.	**
**		**
**	Table of Contents	**
**		**
**	Cover Page Page 10- 1	**
**	List of Cache.c Function Declarations Page 10- 2	**
**	Push() Page 10- 3	**
**	Pop() Page 10- 4	**
**	ChangeTopMemoryRequest() Page 10- 5	**
**	Append() Page 10- 6	**
**	View() Page 10- 7	**
**	Clear() Page 10- 8	**
**	Order() Page 10- 9	**
**	Splice() Page 10-10	^ ^
**	Search() Page 10-12	**
**	UpdatingReadBuffer() Page 10-13	**
**	RemoveZeroSizes() Page 10-15	**
**	NoRequestsLeft() Page 10-16	**
**		**

#include "Global.h"

```
/*********************
                                              Page 10- 2 **
**
                          Buffer.c
                                                          **
                                                          **
              List of Buffer.c Function Declarations
                                                          **
                                                          **
**
** Description:
                                                          **
**
                                                          **
**
                                                          **
      This is a list of functions declarations within the file scope
** of "Buffer.c".
                                                          **
                                                          **
*****************
                                               /* Page 10- 3 */
             Push();
void
MemoryRequestType Pop();
                                               /* Page 10- 4 */
void
            ChangeTopMemoryRequest();
                                              /* Page 10- 5 */
void
                                              /* Page 10- 6 */
             Append();
MemoryRequestType View();
                                               /* Page 10- 7 */
            Clear();
                                               /* Page 10- 8 */
void
/* Page 10- 9 */
                                               /* Page 10-10 */
                                               /* Page 10-12 */
                                               /* Page 10-13 */
                                               /* Page 10-15 */
                                               /* Page 10-16 */
```

```
/**********************************
**
                                                        Page 10- 3 **
                              Buffer.c
                                Push
** Description:
**
**
      Push adds a new record to the top of the buffer.
**
*****************************
void Push(Buffer, MemoryRequest)
  BufferType *Buffer;
  MemoryRequestType *MemoryRequest;
  {
  BufferSizeType i;
  if (Buffer->Full)
     CacheWaitingFor=Buffer->WaitingForFlag;
  else
     for (i=Buffer->Next; i>0; i--)
       Buffer->MemoryRequest[i]=Buffer->MemoryRequest[i-1];
     Buffer->Next++;
     Buffer->MemoryRequest[0]=*MemoryRequest;
     if (Buffer->Next>Buffer->Max) Buffer->Full=Yes;
     Buffer->Empty=No;
     if (CacheWaitingFor==Buffer->WaitingForFlag) CacheWaitingFor=Nothing;
  }
```

```
/*************************
**
                                                     Page 10- 4 **
**
                             Buffer.c
                                                               **
**
                                                               **
                              Pop
**
  Description:
**
**
     Pop removes a record from the top of the buffer, and returns it to
  the caller of the function.
                                                               **
MemoryRequestType Pop(Buffer)
  BufferType *Buffer;
                   MemoryRequest;
  MemoryRequestType
  BufferSizeType i;
  if (Buffer->Empty || Buffer->Next==0)
    printf("\n\n Tryed to Pop an empty buffer!\n\n");
    exit(1);
  else
     MemoryRequest=Buffer->MemoryRequest[0];
     for (i=0; i<Buffer->Next; i++)
       Buffer->MemoryRequest[i]=Buffer->MemoryRequest[i+1];
    Buffer->Next--;
     if (Buffer->Next==0) Buffer->Empty=Yes;
    Buffer->Full=No;
     }
  return (MemoryRequest);
  }
```

```
/****************************
                                               Page 10-5 **
                         Buffer.c
                     ChangeTopMemoryRequest
** Description:
    Push adds a new record to the top of the buffer.
void ChangeTopMemoryRequest(Buffer, MemoryRequest)
  BufferType *Buffer;
  MemoryRequestType *MemoryRequest;
  if (Buffer->Empty==No && Buffer->Next>0)
    Buffer->MemoryRequest[0]-*MemoryRequest;
  else
    printf("\n\n Tryed to Pop an empty buffer!\n\n");
    exit(1);
  }
```

---

```
Page 10- 6 **
                               Buffer.c
**
                                Append
**
** Description:
**
      Append adds a new record to the bottom of the buffer.
**
**********************
void Append(Buffer, MemoryRequest)
  BufferType *Buffer;
  MemoryRequestType *MemoryRequest;
  {
  if (Buffer->Full)
     CacheWaitingFor=Buffer->WaitingForFlag;
  else
     Buffer->MemoryRequest[Buffer->Next]=*MemoryRequest;
     Buffer->Next++;
     if (Buffer->Next>Buffer->Max) Buffer->Full=Yes;
     Buffer->Empty=No;
     if (CacheWaitingFor==Buffer->WaitingForFlag) CacheWaitingFor=Nothing;
   }
```

```
Page 10- 7 **
                          Buffer.c
                           View
** Description:
* *
     View returns a copy of the top record in the buffer without
** altering the buffer.
****************************
MemoryRequestType View(Buffer)
  BufferType *Buffer;
  {
  MemoryRequestType MemoryRequest;
  if (Buffer->Empty)
    printf("\n\ Tryed to View an empty buffer!\n\);
    exit(1);
  else
    MemoryRequest=Buffer->MemoryRequest[0];
  return (MemoryRequest);
  }
```

```
Page 10- 9 **
                               Buffer.c
                                Order
  Description:
       Order sorts all of the entries in the buffer by priority such
  that the highest priority (lowest priority number) is at the top.
                                                                     **
          **********
oid Order (Buffer)
 BufferType *Buffer;
 MemoryRequestType TmpMemoryRequest;
  YesNoType
             Change=Yes;
  BufferSizeType
  while (!(Buffer->Empty) && Change)
    Change=No;
    for (i=Buffer->Next-1; i>0; i--)
       if (Buffer->MemoryRequest[i].Priority
           Buffer->MemoryRequest[i-1].Priority)
          TmpMemoryRequest=Buffer->MemoryRequest[i];
          Buffer->MemoryRequest[i]=Buffer->MemoryRequest[i-1];
          Buffer->MemoryRequest[i-1]=TmpMemoryRequest;
          Change=Yes;
       }
     }
```

```
Page 10-10 **
                                  Buffer.c
                                   Splice
** Description:
                                                                           **
        Splice is buffer utility that takes a one byte memory request and
** enters it into a buffer if the buffer does not already have the byte.
                                                                          **
** Splice will first searchthe ReadBuffer for the byte if it can't find a
** request in the buffer that contains the byte then it will search for a
** memory request that has data from the same block. If one is found
                                                                          **
** then the request is modified to include the new read byte request.
** If no suitable request can be found then Splice will add a one byte
** memory request to the Buffer.
                                                                          . .
void Splice(Buffe , Address, RequiredSize, Block, Priority)
  BufferType
                *Buffer;
  AddressType Address;
  SizeType RequiredSize; SizeType Block;
  PriorityType Priority;
   {
  BufferSizeType BufferIndex;
  YesNoType FoundByte=No;
AddressType FrontAddress;
AddressType BackAddress;
AddressType CurrentBlockAddress=BlockAddress(Address);
  SizeType
                  NextSize;
  MemoryRequestType MemoryRequest;
                                      = Address;
  MemoryRequest.Address
  MemoryRequest.Size
                                      = 1;
  MemoryRequest.RequiredSize
                                     = 0;
  MemoryRequest.Block
                                     = Block;
  MemoryRequest.Priority
                                     = Priority;
                                   = No;
= 0;
  MemoryRequest.AccessInProgress
  MemoryRequest.TimeToExecute
  MemoryRequest.CompletionTimeEstimate = 0;
   if (RequiredSize>0) MemoryRequest.RequiredSize=1;
```

```
Page 10-11
                                Buffer.c
                                 Splice
                                continued
if (!(Buffer->Empty))
   for (BufferIndex=0; BufferIndex<Buffer->Next; BufferIndex++)
      if (BlockAddress(Buffer->MemoryRequest[BufferIndex].Address) ==
          CurrentBlockAddress)
         NextSize=1;
         FrontAddress=Buffer->MemoryRequest[BufferIndex].Address;
         BackAddress =FrontAddress;
         while (FoundByte==No && NextSize<=BlockSize &&
                NextSize<=(Buffer->MemoryRequest[BufferIndex].Size+1))
            if (BackAddress==Address)
               if (NextSize>Buffer->MemoryRequest[BufferIndex].Size)
                  Buffer->MemoryRequest[BufferIndex].Size=NextSize;
               if (RequiredSize>0)
                  Buffer->MemoryRequest[BufferIndex].RequiredSize=NextSize;
               if (Buffer->MemoryRequest[BufferIndex].Priority>Priority)
                  Buffer->MemoryRequest [BufferIndex].Priority=Priority;
               FoundByte=Yes;
            if (FrontAddress==Address &&
                Buffer->MemoryRequest [BufferIndex] .AccessInProgress==No)
               Buffer->MemoryRequest[BufferIndex].Size=NextSize;
               if (RequiredSize>0)
                   Buffer->MemoryRequest[BufferIndex].RequiredSize++;
               if (Buffer->MemoryRequest[BufferIndex].Priority>Priority)
                   Buffer->MemoryRequest [BufferIndex].Priority=Priority;
               FoundByte=Yes;
            NextSize++;
            if (NextSize>Buffer->MemoryRequest[BufferIndex].Size)
               FrontAddress--;
            BackAddress++;
            if (BlockAddress(FrontAddress)!=CurrentBlockAddress)
               FrontAddress+=BlockSize;
            if (BlockAddress(BackAddress) !=CurrentBlockAddress)
               BackAddress-=BlockSize;
         if (Buffer->MemoryRequest[BufferIndex].Size==BlockSize &&
             Buffer->MemoryRequest [BufferIndex] .AccessInProgress==No)
            Buffer->MemoryRequest(BufferIndex).Address=RequestAddress;
            Buffer->MemoryRequest[BufferIndex].RequiredSize=RequestSize;
            }
      }
if (FoundByte==No) Append(Buffer,&MemoryRequest);
```

```
/**********************
++
                                                         Page 10-12 **
                               Buffer.c
                                Search
   Description:
        Search checks a buffer to see if it contains a byte addressed by
**
                                                                    **
   Address.
                                                                    **
    *************
YesNoType Search (Buffer, Address)
                *Buffer;
  BufferType
  AddressType
                Address;
  BufferSizeType BufferIndex;
  AddressType ByteAddress;
               CurrentBlockAddress=BlockAddress(Address);
  AddressType
               NoBytes;
  SizeType
  YesNoType
               FoundByte=No;
  if (!(Buffer->Empty))
     for (BufferIndex=0; BufferIndex<Buffer->Next; BufferIndex++)
        if (BlockAddress(Buffer->MemoryRequest[BufferIndex].Address) ==
           CurrentBlockAddress)
          ByteAddress=Buffer->MemoryRequest[BufferIndex].Address;
           for (NoBytes=0;
               NoBytes<Buffer->MemoryRequest[BufferIndex].Size;
               NoBytes++)
             if (ByteAddress==Address) FoundByte=Yes;
             ByteAddress++;
             if (BlockAddress(ByteAddress)!=CurrentBlockAddress)
                ByteAddress-=BlockSize;
             }
           }
        }
     }
  return (FoundByte);
   ł
```

```
/**************************
**
                                                          Page 10-13 **
                                Buffer.c
                           UpdatingReadBuffer
                                                                      **
** Description:
                                                                      **
**
        UpdatingReadBuffer takes a byte of data provided by a CPU write
** request and checks to see if it is needed in the read buffer. If the
** byte is needed then the MemoryRequest is modified so that the byte
                                                                     **
                                                                     **
** is no longer in the request.
                                                                     **
YesNoType UpdatingReadBuffer(Address)
  AddressType Address;
  {
  AddressType ByteAddress;
AddressType CurrentBlockAddress = BlockAddress(Address);
  BufferSizeType BufferIndex;
                                 = No;
  YesNoType FoundByte
```

ر ن پاست

```
Page 10-14
                               Buffer.c
                          UpdatingReadBuffer
                              continued
if (!(ReadBuffer.Empty))
  for (BufferIndex=0; BufferIndex<ReadBuffer.Next; BufferIndex++)</pre>
     if (BlockAddress(ReadBuffer.MemoryRequest[BufferIndex].Address) ==
            CurrentBlockAddress
         if (ReadBuffer.MemoryRequest[BufferIndex].Size>0)
           ByteAddress=ReadBuffer.MemoryRequest[BufferIndex].Address +
                       ReadBuffer.MemoryRequest[BufferIndex].Size
           if (ByteAddress==Address)
              ReadBuffer.MemoryRequest[BufferIndex].Size--;
              if (ReadBuffer.MemoryRequest[BufferIndex].RequiredSize>
                  ReadBuffer.MemoryRequest[BufferIndex].Size)
                  ReadBuffer.MemoryRequest[BufferIndex].RequiredSize=
                     ReadBuffer.MemoryRequest[BufferIndex].Size;
              FoundByte=Yes;
        if (ReadBuffer.MemoryRequest[BufferIndex].Size>0)
           if (ReadBuffer.MemoryRequest[BufferIndex].Address==Address)
              ReadBuffer.MemoryRequest[BufferIndex].Address++;
              if (BlockAddress(ReadBuffer.MemoryRequest[BufferIndex].Address)
                  !=CurrentBlockAddress)
                 ReadBuffer.MemoryRequest[BufferIndex].Address-=BlockSize;
              if (ReadBuffer.MemoryRequest[BufferIndex].Size >0)
                  ReadBuffer.MemoryRequest[BufferIndex].Size--;
              if (ReadBuffer.MemoryRequest[BufferIndex].RequiredSize>0)
                  ReadBuffer.MemoryRequest[BufferIndex].RequiredSize--;
              FoundByte=Yes;
           }
        }
RemoveZeroSizes(&ReadBuffer);
return (FoundByte);
```

```
/*********************************
                                                    Page 10-15 **
                            Buffer.c
                                                              **
                          RemoveZeroSizes
                                                               **
** Description:
                                                               **
**
       RemoveZeroSizes removes all entrees that have a zero size from
** the buffer.
                                                               **
                                                              **
void RemoveZeroSizes(Buffer)
  BufferType *Buffer;
  {
  BufferSizeType i=0;
  BufferSizeType j=0;
  while (j<Buffer->Next)
     if (Buffer->MemoryRequest[j].Size==0 &&
        !Buffer->MemoryRequest[j].AccessInProgress)
       j++;
       Buffer->Full=No;
     else
       Buffer->MemoryRequest[i]=Buffer->MemoryRequest[j];
       1++;
       j++;
     }
  Buffer->Next=i;
  if (Buffer->Next==0) Buffer->Empty=Yes;
  }
```

```
/***********************
                                            Page 10-16 **
                        Buffer.c
                      NoRequestsLeft
** Description:
      NoRequestsLeft returns Yes if there are no more requests left
** in the buffer.
YesNoType NoRequestsLeft(Buffer)
  BufferType *Buffer;
  ſ
  BufferSizeType i;
  for (i=0; i<Buffer->Next; i++)
    if (Buffer->MemoryRequest[i].RequiredSize>0) return(No);
  return (Yes);
  }
```

/\* \*\* Page 11- 0 \*\* Array.c Part Of SACS 1.0 (StillAnother Cache Simulator) \*\* \*\* Program Modified: 3/17/94 \*\* File Modified: 3/17/94 \*\* \*\* Author: William G. Smith \*\* Address: Electrical Engineering Department \*\* Naval Postgraduate School \*\* \*\* Monterey, CA 93940 \*\* \* \* Copyright 1994, William G. Smith \*\* Permission to use, copy, modify, and distribute this software and \*\* its documentation for any purpose and without fee is hereby granted \*\* \*\* provided that the above copyright notice appears in all copies. No \*\* \*\* modified version of this program should be redistributed without the \*\* \*\* authors consent. William G. Smith makes no warranty or \*\* \*\* representation, promise of quarantee, either expressed or implied, \* \* \*\* with respect to this software's ability to produce valid results. \*\* \*\* This program is provided "as is" any financial, personal or property \*\* \*\* damage caused by the use of this program is the responsibility of the \*\*

\*\*

user.

/**********************					
**	Page 11- 1	**			
**	Array.c	**			
**		**			
**	Description:	**			
**		**			
**	Array.c contains all functions that relate to definition and	**			
**	freeing, or allocation, and deallocation of arrays.	**			
**		**			
**	Table of Contents	**			
**		**			
**	Cover Page Page 11- 1	**			
**	List of Array.c Function Declarations Page 11- 2	**			
**	DefineArray1D() Page 11- 3	**			
**	DefineArray2D() Page 11- 4	**			
**	FreeArraylD() Page 11- 5	**			
**	FreeArray2D() Page 11- 6	**			
* *		**			
***************************************					

```
Page 11- 2 **
                                       Array.c
                                                                                   **
                                                                                    **
                    List of Array.c Function Declarations
** Description:
                                                                                     **
                                                                                     **
**
          This is a list of function declarations within the file scope
                                                                                   **
** of "Array.c".
                                                                                    **
                                                                     /* Page 11- 3 */
/* Page 11- 4 */
/* Page 11- 5 */
int *DefineArraylD();
int **DefineArray2D();
void FreeArray1D();
void FreeArray2D();
                                                                     /* Page 11- 6 */
```

```
Page 11- 3 **
                           Array.c
                         DefineArraylD
** Description:
       DefineArray1D allocates memory large enough for a 1 dimensional
** array of length Xmax, where each element has "size" bytes.
                                                            **
                                                            **
int *DefineArray1D(Xmax, size)
 unsigned Xmax;
 unsigned size;
 int *Array;
 Array=(int*) calloc(Xmax, size);
 return(Array);
 }
```

```
**
                                                       Page 11- 4 **
**
                              Array.c
                                                                  **
**
                           DefineArray2D
                                                                  **
** Description:
                                                                  **
**
**
       DefineArray2D allocates memory large enough for a 2 dimensional
** array Xmax, by Ymax, where each element has "size" bytes.
                                                                  **
int **DefineArray2D(Xmax, Ymax, size)
 unsigned Xmax;
 unsigned Ymax;
 unsigned size;
 {
 int **Array;
 unsigned x;
 Array=(int**) calloc(Xmax, size);
 for (x=0; x<Xmax; x++) Array[x]=(int*) calloc(Ymax, size);</pre>
 return(Array);
 }
```

--

```
Page 11- 6 **
                           Array.c
                          FreeArray2D
** Description:
**
      FreeArray2D deallocates the memory assigned to the 2 dimensional **
** array.
void FreeArray2D(Array, Xmax, Ymax)
 int
       **Array;
 unsigned Xmax;
 unsigned Ymax;
 unsigned x;
 for (x=0; x<Xmax; x++) free(Array[x]);</pre>
 free(Array);
 }
```

.

Page 12- 0 \*\* \*\* TestSACS.c \*\* Part Of SACS 1.0 (StillAnother Cache Simulator) \*\* \*\* Program Modified: 3/17/94 \*\* \*\* File Modified: 3/17/94 \*\* \*\* \*\* \*\* Author: William G. Smith \* \* Address: Electrical Engineering Department \*\* Naval Postgraduate School \*\* \*\* Monterey, CA 93940 \*\* ++ \*\* Copyright 1994, William G. Smith \*\* \*\* \*\* Permission to use, copy, modify, and distribute this software and \* \* its documentation for any purpose and without fee is hereby granted \*\* \*\* \*\* provided that the above copyright notice appears in all copies. No \*\* \*\* modified version of this program should be redistributed without the \*\* authors consent. William G. Smith makes no warranty or representation, promise of guarantee, either expressed or implied, with respect to this software's ability to produce valid results. This program is provided "as is" any financial, person or property damage caused by the use of this program is the responsibility of the \*\* user.

\*

```
***********
                                                      Page 12- 1 **
                             TestSACS.c
   Description:
**
**
       TestSACS randomly creates instructions and writes them to
** "SACS.Dat". The instrcutions are generated by first choosing
** NoTestCases. The Number of test cases to be used will always
** be less than MaxNoTestCases. Then the TestCaseChoosen is picked
** from TestCases. TestCases represent different possible ways in
** which an address trace could procede. PredictedNoRead, HitsInTest,
                                                                 **
**
   and PredictedNoWriteHitsInTest, tells TestSACS how many hits it can
   expect because, it used a specific test.
                                                                 **
**
                                                                 ++
**
      Example:
**
**
         main()
* *
           {
**
           unsigned long int NoLoadHits;
**
           unsigned long int NoLoadRequests;
                                                                 ++
* *
                                                                 **
* *
           TestSACS(NumberOfRequests, NumberOfHits);
**
**
           printf("\n\nNumber of read hits=%ul", NoReadHits);
           printf("\n\nNumber of read requests=%ul", NoReadRequests);
**
           printf("\n\nNumber of write hits=%ul", NoWriteHits);
**
           printf("\n\..Number of write requests=%ul", NoWriteRequests);
**
**
           }
                                                                 **
                          Table of Contents
**
                                                                 **
**
          Cover Page ..... Page 12- 1
**
          List of definitions ...... Page 12- 2
**
          List of TestSACS.c Function Declarations .. Page 12- 3
                                                                 * *
          TestCases ..... Page 12- 4
                                                                 **
**
         PredictedNoReadHits ..... Page 12-5
                                                                 **
**
         PredictedNoWriteHits ..... Page 12- 5
**
         ChangeArguments() ..... Page 12-6
                                                                 **
**
         TestSACS() ..... Page 12- 8
* *
            CreateInstructionSets() ...... Page 12- 9
                                                                 **
               Creating One Instruciton at a Time .. Page 12-10
                                                                 **
**
            ShufflingInstructionSets() ..... Page 12-12
                                                                 * *
               CanBeSwitched() ..... Page 12-14
            WriteInstructionSet() ...... Page 12-15
                                                                 **
                                                                 **
      ****************************
```

```
#include<time.h>
```

#include "Global.h"

```
**
                                          Page 12- 3 **
**
                       TestSACS.c
           List of TestSACS.c Function Declarations
** Description:
                                                   **
                                                   **
      This is a list of functions declarations within the file scope
** of "TestSACS.c".
                                                   **
void ChangeArguments();
void TestSACS();
                                         /* Page 12- 6 */
                                         /* Page 12- 8 */
/* Page 12- 9 */
                                         /* Page 12-12 */
/* Page 12-14 */
/* Page 12-15 */
```

```
{ 1, 1, 1, 1, 2, 2, 1}, { 1, 1, 1, 1, 2, 2, 2},
{ 1, 1, 1, 2, 1, 1, 1}, { 1, 1, 1, 2, 1, 1, 2},
{ 1, 1, 1, 2, 1, 2, 1}, { 1, 1, 1, 2, 1, 2, 2},
\{1, 1, 1, 2, 2, 1, 1\}, \{1, 1, 1, 2, 2, 1, 2\}.
\{1, 1, 1, 2, 2, 2, 1\}, \{1, 1, 1, 2, 2, 2, 2\},\
{ 1, 1, 2, 1, 1, 1, 1}, { 1, 1, 2, 1, 1, 1, 2},
\{1, 1, 2, 1, 1, 2, 1\}, \{1, 1, 2, 1, 1, 2, 2\},\
{ 1, 1, 2, 1, 2, 1, 1}, { 1, 1, 2, 1, 2, 1, 2},
\{1, 1, 2, 1, 2, 2, 1\}, \{1, 1, 2, 1, 2, 2, 2\},\
\{1, 1, 2, 2, 1, 1, 1\}, \{1, 1, 2, 2, 1, 1, 2\},\
{ 1, 1, 2, 2, 1, 2, 1}, { 1, 1, 2, 2, 1, 2, 2},
{ 1, 1, 2, 2, 2, 1, 1}, { 1, 1, 2, 2, 2, 1, 2},
{ 1, 1, 2, 2, 2, 2, 1}, { 1, 1, 2, 2, 2, 2, 2},
{ 1, 2, 1, 1, 1, 1, 1}, { 1, 2, 1, 1, 1, 1, 2},
{ 1, 2, 1, 1, 1, 2, 1}, { 1, 2, 1, 1, 1, 2, 2},
{ 1, 2, 1, 1, 2, 1, 1}, { 1, 2, 1, 1, 2, 1, 2},
\{1, 2, 1, 1, 2, 2, 1\}, \{1, 2, 1, 1, 2, 2, 2\},\
{ 1, 2, 1, 2, 1, 1, 1}, { 1, 2, 1, 2, 1, 1, 2},
{ 1, 2, 1, 2, 1, 2, 1}, { 1, 2, 1, 2, 1, 2, 2},
{ 1, 2, 1, 2, 2, 1, 1}, { 1, 2, 1, 2, 2, 1, 2},
{ 1, 2, 1, 2, 2, 2, 1}, { 1, 2, 1, 2, 2, 2, 2},
{ 1, 2, 2, 1, 1, 1, 1}, { 1, 2, 2, 1, 1, 1, 2},
{ 1, 2, 2, 1, 1, 2, 1}, { 1, 2, 2, 1, 1, 2, 2},
{ 1, 2, 2, 1, 2, 1, 1}, { 1, 2, 2, 1, 2, 1, 2},
{ 1, 2, 2, 1, 2, 2, 1}, { 1, 2, 2, 1, 2, 2, 2},
{ 1, 2, 2, 2, 1, 1, 1}, { 1, 2, 2, 2, 1, 1, 2},
{ 1, 2, 2, 2, 1, 2, 1}, { 1, 2, 2, 2, 1, 2, 2},
{ 1, 2, 2, 2, 2, 1, 1}, { 1, 2, 2, 2, 2, 1, 2},
{ 1, 2, 2, 2, 2, 2, 1}, { 1, 2, 2, 2, 2, 2}
};
```

\_

```
Page 12- 5 **
                                 TestSACS.c
               PredictedNoReadHits, and PredictedNoWriteHits
** Description:
       No Hits Predicted for each test case.
*************************
  int PredictedNoReadHitsInTest[NoTestCaseChoices] =
     6, 5, 5, 4,
     5, 4, 4, 3,
     5, 4, 4, 3,
     4, 3, 3, 2,
     5, 4, 4, 3,
     4, 3, 3, 2,
     4, 3, 3, 2,
     3, 2, 2, 1,
     5, 4, 4, 3,
     4, 3, 3, 2,
     4, 3, 3, 2,
     3, 2, 2, 1,
     4, 3, 3, 2,
     3, 2, 2, 1,
     3, 2, 2, 1,
     2, 1, 1, 0
     };
   int PredictedNoWriteHitsInTest(NoTestCaseChoices)=
      0, 0, 0, 1,
     0, 1, 1, 2,
      0, 1, 1, 2,
     1, 2, 2, 3,
      0, 1, 1, 2,
      1, 2, 2, 3,
     1, 2, 2, 3,
2, 3, 3, 4,
0, 1, 1, 2,
     1, 2, 2, 3,
      1, 2, 2, 3,
      2, 3, 3, 4,
      1, 2, 2, 3,
      2, 3, 3, 4,
```

2, 3, 3, 4, 3, 4, 4, 5

};

and the contract of the contract of the contract of the sectors and sectors and contract of

```
Page 12- 6 **
                              TestSACS.c
                             ChangeArguments
**
** Description:
**
**
        ChangeArguments, change the global variables in SACS that the
   user can change.
  *************
void ChangeArguments()
   1
  SizeType
                   WordSizeLimit
                                         * 8;
                                      = 4;
                   WordsPerSubBlock
  SizeType
                   NumberOfSubBlocksLimit = 4;
  SizeType
  SizeType
                 NumberOfBlocksLimit = 32;
  AssociativityType AssociativityLimit
                                         = 8;
                                         = 8;
  BufferSizeType BufferSizeLimit
TimeType TimeLimit
                                         = 8;
  WordSize
                              = (rand()%(WordSizeLimit-1))+1;
   SubBlockSize
                             = WordSize*((rand()%WordsPerSubBlock)+1);
                              = SubBlockSize
  BlockSize
                               *((rand()%NumberOfSubBlocksLimit)+1);
                              = (rand() %AssociativityLimit) +2;
  Associativity
  CacheSize
                              = BlockSize*Associativity*
                                ((rand()%NumberOfBlocksLimit)+1);
  ReadCacheAccessTime
                             = rand() %TimeLimit;
  ReadCacheHitTime
                              = rand()%TimeLimit;
  ReadCacheMissTime
                              = rand()%TimeLimit;
  WriteCacheAccessTime
                             = rand() %TimeLimit;
  WriteCacheHitTime
                             = rand()%TimeLimit;
  WriteCacheMissTime
                            = rand()%TimeLimit;
  MemoryAccessTime
                            = rand()%TimeLimit;
  MemoryTransferTime
                            = rand()%TimeLimit;
  BufferCacheAccessTime
                            = rand()%TimeLimit;
  ReadBufferSize
                            = (rand() %BufferSizeLimit)+1;
  WriteBufferSize
                             = (rand() %BufferSizeLimit)+1;
  BlockReplacementPolicy = rand()%NumberOfReplacementPoliciesAvailable;
  WritePolicy
                             = rand()%NumberOfWritePoliciesAvailable;
  WriteMissPolicy
                             = rand()%NumberOfWriteMissPoliciesAvailable;
                             = rand() %Unknown;
  ReadForward
   CPUWaitsForCacheWrites
                           = rand()%Unknown;
   SearchBlockBuffer
                             = rand()%Unknown;
  UpdateReadBuffer
                             = rand()%Unknown;
  RemoveReadDuplicates
                            = rand() %Unknown;
  RemoveWriteDuplicates
                             = rand()%Unknown;
                             = (rand()%(NoPriority-1))+1;
  ReadPriority
                           = (rand()%(NoPriority-1))+1;
   WritePriority
  ReadForWriteAllocatePriority = (rand()%(NoPriority-1))+1;
  WriteDirtyBlockPriority = (rand()%(NoPriority-1))+1;
```

```
/***

** TestSACS.c **

** ChangeArguments continued **

** Description: **

** Ensuring that the new arguments are valid combinations. **

** if (SearchBlockBuffer==No) RemoveReadDuplicates=No;

if (UpdateReadBuffer ==Yes) WordSize=SubBlockSize;

}
```

--

```
/************************
                                                          Page 12- 8 **
                                                                     **
                              TestSACS.c
                                                                     **
                                                                     **
                               TestSACS
   Description:
**
**
        TestSACS will create a test set, shuffle the instructions, and
   write them out to "SACS.Dat".
************************
void TestSACS(NumberOfRequests, NumberOfHits)
  ScoreType *NumberOfRequests;
  ScoreType *NumberOfHits;
  {
  char
             Request
                                [MaxNoOfTestCases*NoTestCaseChoices+1];
  AddressType DataAddress
                                [MaxNoOfTestCases*NoTestCaseChoices+1];
                                [MaxNoOfTestCases*NoTestCaseChoices+1];
  SizeType
            Size
  TimeType
             TimeUntilNextRequest[MaxNoOfTestCases*NoTestCaseChoices+1];
             Imax=0;
  int
  DisplayTestingHeader();
  CreateInstructionSets(Request, DataAddress, Size, TimeUntilNextRequest,
                       &Imax,
                      NumberOfRequests, NumberOfHits);
  ShufflingInstructionSets (Request, DataAddress, Size, TimeUntilNextRequest,
                         Imax);
  rewind(DataFile);
  WriteInstructionSet (Request, DataAddress, Size, TimeUntilNextRequest,
                     Imax);
  rewind (DataFile);
  EndOfDataFile=No;
  }
```

```
/**********************************
                                                           Page 12- 9 **
                              TestSACS.c
                                                                      ++
                                                                      **
                           CreateInstructionSets
                                                                      **
   Description:
                                                                      **
                                                                      **
**
        The instructions are created from a set of test cases. The
                                                                      **
**
   the number of predicted hits for each case is stored in
**
   PredictedNoHitsInTest. CreateInstructionsSets randomly chooses the
                                                                      **
**
   NoOfTestCases to be used, and randomly selects the individual
                                                                      **
** TestCases. The BlockAddressChoices for each test case is also chosen
                                                                      **
** randomly. The DataAddress, and Size of each instuction is chosen
                                                                      **
** randomly such that they are within the block chosen. The NoLoadHits
                                                                      **
** is predicted by summing up all of the PredictedNoHitsInTest.
                                                                      **
     ************************
void CreateInstructionSets(Request,
                         DataAddress,
                         Size,
                         TimeUntilNextRequest,
                         Imax,
                         NumberOfRequests,
                         NumberOfHits)
              *Request;
  char
  AddressType *DataAddress;
  SizeType *Size;
  TimeType
              *TimeUntilNextRequest;
  int
              *Imax;
  ScoreType *NumberOfRequests;
  ScoreType *NumberOfHits;
   {
             MaxTimeUntilNextRequest = 101;
  TimeType
  AddressType BlockAddressChoices[NumberOfRequestsAvailable];
  SizeType SetChosen;
   int TestCaseIndex;
   int LoadIndex;
   int NoOfTestCases;
   int TestCaseChosen;
   int i, j, k;
   time t t;
/* srand((unsigned) time(&t)); */ /* Uncomment to randomize each test run */
                                 /* otherwise every test run will be
                                                                      */
                                 /* identical. Leaving the seed
                                                                       */
                                 /* commented out allows any errors
                                 /* found by -test to be revisited.
                                                                      */
  NumberOfRequests[Read ]=0;
  NumberOfRequests(Write)=0;
  NumberOfHits [Read ]=0;
  NumberOfHits [Write]=0;
```

```
Page 12-10 **
                                TestSACS.c
                           CreatedInstrutionSets
**
                                 Continued
** Description:
**
**
        Creating one instruction at a time.
  ********************
   *Imax=0;
  NoOfTestCases=rand()%MaxNoOfTestCases+1;
  for (TestCaseIndex=0; TestCaseIndex<NoOfTestCases; TestCaseIndex++)</pre>
      TestCaseChosen=rand() %NoTestCaseChoices;
      SetChosen=rand() %NumberOfSets;
     BlockAddressChoices[Read] =
                     ( ( (lrand() / (NoOfTestCases*NumberOfSets*BlockSize) )
                        *NoOfTestCases+TestCaseIndex)
                    *NumberOfSets + SetChosen) * BlockSize;
     BlockAddressChoices[Write] = BlockAddressChoices[Read];
      if (rand()%2)
        BlockAddressChoices[Write] =
                     ( ( (lrand() / (NoOfTestCases*NumberOfSets*BlockSize) )
                         *NoOfTestCases+TestCaseIndex)
                        *NumberOfSets + SetChosen) * BlockSize;
      if (BlockAddress(BlockAddressChoices[Read])!=BlockAddressChoices[Read])
         printf("Read is not a BlockAddress");
      if (BlockAddress(BlockAddressChoices[Write])!=BlockAddressChoices[Write])
        printf("Write is not a BlockAddress");
      if (Set(BlockAddressChoices[Read])!=SetChosen)
        printf("Read is not a good Set");
      if (Set(BlockAddressChoices[Write])!=SetChosen)
         printf("Write is not a good Set");
      if (BlockAddressChoices[Read] == BlockAddressChoices[Write])
        printf("%4dE", TestCaseChosen);
      else
        printf("%4dN", TestCaseChosen);
      if (TestCaseIndex%15==14) printf("\n");
```

```
Page 12-11
**
                                TestSACS.c
                                                                           **
                           CreatedInstrutionSets
                                                                           **
                                 Continued
                                                                           **
      ************************
     if (BlockAddressChoices[Read] == BlockAddressChoices[Write])
        NumberOfHits[Read] +=PredictedNoReadHitsInTest[TestCaseChosen];
        NumberOfHits[Write]+=PredictedNoWriteHitsInTest[TestCaseChosen];
        LoadIndex=0;
        while (TestCases[TestCaseChosen][LoadIndex]==Write &&
               WriteMissPolicy!=WriteAllocate
               LoadIndex<NoLoadStoresInTestCases)
           NumberOfHits[Write]--;
           LoadIndex++;
        if (TestCases[TestCaseChosen][0]==Read && TestCaseChosen!=0)
           NumberOfHits[Write]++;
        if (TestCases[TestCaseChosen][0]==Write &&
            WriteMissPolicy==WriteAllocate)
           NumberOfHits[Read]++;
     else
        NumberOfHits[Read] +=PredictedNoReadHitsInTest[TestCaseChosen];
        if (WriteMissPolicy==WriteAllocate)
           NumberOfHits(Write)+=PredictedNoWriteHitsInTest(TestCaseChosen);
     for (LoadIndex=0; LoadIndex<NoLoadStoresInTestCases; LoadIndex++)</pre>
        if (TestCases[TestCaseChosen][LoadIndex]==Read)
           Request (*Imax)='r';
           NumberOfRequests[Read]++;
        else
           Request[*Imax]='w';
           NumberOfRequests[Write]++;
        DataAddress[*Imax] =
           BlockAddressChoices[TestCases[TestCaseChosen][LoadIndex]];
         Size[*Imax]=lrand()%BlockSize+1;
         if (Size[*Imax]<BlockSize)</pre>
           DataAddress[*Imax] += lrand()%(BlockSize-Size[*Imax])+1;
         TimeUntilNextRequest[*Imax]=lrand()%MaxTimeUntilNextRequest;
         (*Imax)++;
       }
    }
```

```
Page 12-12 **
                           TestSACS.c
                      ShufflingInstructionSets
  Description:
**
       Shuffling Instruction Sets.
void ShufflingInstructionSets(Request,
                        DataAddress,
                        Size,
                        TimeUntilNextRequest,
                        Imax)
  char
            *Request;
  AddressType *DataAddress;
  SizeType *Size;
           *TimeUntilNextRequest;
  TimeType
  int
            Imax;
  {
             Jump;
  int
  char
             RequestTemp;
  AddressType AddressTemp;
           SizeTemp;
  SizeType
  TimeType
            TimeTemp;
  int i, j, k;
```

```
Page 12-13 **
                             TestSACS.c
                       ShufflingInstructionSets
                             continued
                   ***********
for (i=1; i<Imax; i++)</pre>
  Jump=Yes;
  for (j=i; j>0 && Jump==Yes; j--)
     if (BlockAddress(DataAddress[j-1]) ==BlockAddress(DataAddress[j-1]))
         Jump=No;
      if ((rand()%(Associativity*NoLoadStoresInTestCases))==0)
         Jump=No; /* Gives Uniform distrabution. */
      if (Jump==Yes)
         Jump=CanBeSwitched(DataAddress, j, Imax);
      if (Jump==Yes)
        RequestTemp=Request[j-1];
        Request[j-1]=Request[j];
        Request[j]=RequestTemp;
        AddressTemp=DataAddress[j-1];
        DataAddress[j-1]=DataAddress[j];
        DataAddress[j]=AddressTemp;
         SizeTemp=Size[j-1];
         Size[j-1]=Size[j];
         Size[j]=SizeTemp;
         TimeTemp=TimeUntilNextRequest[j-1];
         TimeUntilNextRequest[j-1]=TimeUntilNextRequest[j];
         TimeUntilNextRequest[j]=TimeTemp;
      }
```

```
Page 12-14 **
                                                                             **
**
                                CanBeSwitched
                                                                             **
**
   DESCRIPTION:
                                                                             **
**
                                                                             * *
* *
         Can InstructionAddress[i] be switched with Instruction[i-1].
                                                                             * *
   If so return Yes, else return No.
                                                                             **
   <u>*********************************</u>
YesNoType CanBeSwitched (DataAddress, Io, Imax)
   unsigned long int *DataAddress;
   int
                     Io;
                     Imax;
   int
   {
   int
                     i,j;
   YesNoType
                     Jump=Yes;
                     NoJumped;
   YesNoType
   YesNoType
                     JumpedBefore;
   unsigned long int AddressJumped[100];
   Jump=Yes;
   NoJumped=1;
   AddressJumped[0]=BlockAddress(DataAddress[Io]);
   while (i>=0 && NoJumped<Associativity &&
          BlockAddress(DataAddress[i])!=BlockAddress(DataAddress[Io-1]))
      JumpedBefore=No;
      for (j=0; j<NoJumped; j++)</pre>
         if (AddressJumped[j]==BlockAddress(DataAddress[i])) JumpedBefore=Yes;
      if (JumpedBefore==No && NoJumped<Associativity)</pre>
         AddressJumped[NoJumped++]=BlockAddress(DataAddress[i]);
   if (NoJumped>=Associativity) Jump=No;
   NoJumped=1;
   AddressJumped[0]=BlockAddress(DataAddress[Io-1]);
   i=Io+1;
   while (!<Imax && NoJumped<Associativity &&
          BlockAddress(DataAddress[i])!=BlockAddress(DataAddress[Io]))
      JumpedBefore=No;
      for (j=0; j<NoJumped; j++)</pre>
         if (AddressJumped[j]==BlockAddress(DataAddress[i])) JumpedBefore=Yes;
      if (JumpedBefore==No && NoJumped<Associativity)</pre>
         AddressJumped[NoJumped++]=BlockAddress(DataAddress[i]);
      1++;
   if (NoJumped>=Associativity) Jump=No;
   return (Jump);
   }
```

```
/*****************
                                                             Page 12-15 **
                               TestSACS.c
                                                                        **
                           WriteInstructionSet
                                                                        **
                                                                        **
   Description:
                                                                        **
        Write SACS.Dat one line at a time.
                                                                        **
***********************
void WriteInstructionSet(Request,
                        DataAddress,
                        Size,
                        TimeUntilNextRequest,
                        Imax)
   char
              *Request;
   AddressType *DataAddress;
              *Size;
   SizeType
              *TimeUntilNextRequest;
   TimeType
   int
              Imax;
   {
   int i;
   for (i=0; i<Imax; i++)
     fprintf(DataFile, "%c "
                            ,Request[i]);
     fprintf(DataFile, "%08lX ", DataAddress[i]);
     fprintf(DataFile,"%2u " ,Size[i]);
fprintf(DataFile,"%1u" ,TimeUntilNextRequest[i]);
      fprintf(DataFile, "\n");
   fprintf(DataFile, "End Of Trace\n\n");
   fprintf(DataFile,"If any instructions follow\n");
   fprintf(DataFile, "they were not used for the\n");
   fprintf(DataFile, "last run.
                                             \n");
   fprintf(DataFile, "\n");
```

}

\*\*\*\*\*\*\*\*\*\*\*\*\* Page 13- 0 \*\* \*\* Checking.c \*\* \*\* Part Of SACS 1.0 \*\* (StillAnother Cache Simulator) \*\* \*\* \*\* Program Modified: 3/17/94 \*\* File Modified: 3/17/94 \*\* \*\* Author: William G. Smith \*\* Address: Electrical Engineering Department \*\* Naval Postgraduate School \*\* Monterey, CA 93940 \*\* \*\* Copyright 1994, William G. Smith \*\* \*\* Permission to use, copy, modify, and distribute this software and \*\* its documentation for any purpose and without fee is hereby granted \*\* \*\* provided that the above copyright notice appears in all copies. No \*\* \*\* modified version of this program should be redistributed without the \*\* \*\* authors consent. William G. Smith makes no warranty or representation, promise of guarantee, either expressed or implied, with respect to this software's ability to produce valid results. \*\* \*\* This program is provided "as is" any financial, personal or property damage caused by the use of this program is the responsibility of the \*\* \*\* \*\* \*\*

\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*

/**	**************	***
**	Page 13- 1	* 1
**	Checking.c	**
**		* *
**	Description:	* 1
**		**
**	Checking.c contains all of the functions that relate to error	**
**	checking. Note that an error could be raised anywhere. The error	* 1
**	mesage will contain the procedure name in square brackets. This	* 1
**	section contains the functions spicifically designed to check variable	* 1
**	to see if they are consitant with each other, and if they are within	* 1
**	set boundarys.	* 1
**		* 1
**	Table of Contents	* 1
**		* 1
**	Cover Page Page 13- 1	* 1
**	List of Cache.c Function Declarations Page 13- 2	*1
**	Checking() Page 13- 3	* 1
**	CheckingConstants() Page 13- 4	* 1
**	PrintConstError() Page 13-11	* 1
**	CheckingForValuesOutOfBounds() Page 13-12	* 1
**	PrintTimeBoundaryError(); Page 13-15	* 1
**	<pre>PrintScoreBoundaryError(); Page 13-16</pre>	* 1
**	<pre>PrintSizeBoundaryError(); Page 13-17</pre>	* 1
**	PrintEnumBoundaryError(); Page 13-18	**
**	CheckingForInconsistencies() Page 13-19	* 1
**	PrintTotalTimeError() Page 13-21	* 1
**	<pre>PrintTotalScoreError() Page 13-22</pre>	* 1
**	CheckingPredictions() Page 13-23	* 1
**	PrintScorePredictionError() Page 13-24	* 1
**	PrintTimePredictionError() Page 13-25	* 1
**		* 1

#include "Global.h"

```
Page 13- 2 **
**
                                 Checking.c
                                                                       **
                                                                        **
**
                  List of Checking.c Function Declarations
                                                                        **
                                                                        **
** Description:
                                                                        **
**
                                                                        **
**
        This is a list of function declarations within the file scope
                                                                        **
** of "Checking.c".
                                                                       **
************************************
                                                           /* Page 13- 3 */
void Checking();
                                                           /* Page 13- 4 */
void CheckingConstants();
/* Page 13-11 */
                                                          /* Page 13-12 */
                                                          /* Page 13-15 */
                                                          /* Page 13-16 */
                                                          /* Page 13-17 */
                                                          /* Page 13-18 */
                                                          /* Page 13-19 */
void PrintTotalTimeError();
void PrintTotalScoreError();
                                                          /* Page 13-21 */
                                                          /* Page 13-22 */
                                                          /* Page 13-23 */
/* Page 13-24 */
void CheckingPredictions();
void PrintScorePredictionError();
void PrintTimePredictionError();
                                                          /* Page 13-25 */
```

```
Page 13- 3 **
                            Checking.c
                                                             **
                             Checking
                                                             **
** Description:
                                                             **
                                                             **
       Checking checks the global variables to insure that constants
** remain constant, and Values are in bounds, als that there are no
                                                             **
                                                             **
  inconsistencies.
                                                             **
void Checking()
  {
  CheckingConstants(No);
  CheckingForValuesOutOfBounds();
  CheckingForInconsistencies();
  }
```

```
/**********************
                                                                  Page 13- 4 **
**
                                                                              **
                                    Checking.c
                                                                               **
                                 CheckingConstants
** Description:
**
         Checking global constants to insure that they do not change,
** unless they are being Reset.
***********************
void CheckingConstants(Reset)
   YesNoType Reset;
                                CacheSizeCopy;
BlockSizeCopy;
SubBlockSizeCopy;
AssociativityCopy;
WordSizeCopy;
   static CacheSizeType
   static SizeType
   static SizeType
   static AssociativityType
   static SizeType
   static TimeType
                                    ReadCacheAccessTimeCopy;
                                    ReadCacheHitTimeCopy;
   static TimeType
                                   ReadCacheMissTimeCopy;
WriteCacheAccessTimeCopy;
WriteCacheHitTimeCopy;
   static TimeType
   static TimeType
   static TimeType
                                      WriteCacheMissTimeCopy;
   static TimeType
                                    MemoryAccessTimeCopy;
MemoryTransferTimeCopy;
   static TimeType
   static TimeType
   static TimeType
                                     BufferCacheAccessTimeCopy;
   static BufferSizeType
                                    ReadBufferSizeCopy;
   static BufferSizeType
                                      WriteBufferSizeCopy;
   static BlockReplacementPolicyType BlockReplacementPolicyCopy;
   CPUWaitsForCacheWritesCopy;
SearchBlockBufferCopy;
UpdateReadBufferCopy;
RemoveReadDuplicatesCopy;
   static YesNoType
   static YesNoType
   static YesNoType
   static YesNoType
   static YesNoType
                                     RemoveWriteDuplicatesCopy;
                                 ReadPriorityCopy;
   static PriorityType
static PriorityType
static PriorityType
                                      WritePriorityCopy;
                                      ReadForWriteAllocatePriorityCopy;
   static PriorityType
                                      WriteDirtyBlockPriorityCopy;
   static PriorityType
                                      NoPriorityCopy;
                                      CheckCopy;
   static YesNoType
                                      KeyBoardIOCopy;
   static YesNoType
                                       *DataFileNameCopy;
   static char
   static HistogramIndexType
static HistogramIndexType
                                      ScreenHistogramMaxIndexCopy;
                                      FileHistogramMaxIndexCopy;
```

```
Page 13- 5 **
                                Checking.c
                             CheckingConstants
                                 continued
   *************
                            NumberOfBlocksCopy;
static SizeType
static SizeType
static SizeType
                            NumberOfSubBlocksCopy;
                          NumberOfSetsCopy;
static AddressType
                           *CacheBlockAddressCopy;
                            *LastCacheBlockAccessTimeCopy;
static TimeType
                            *CacheNextBlockCopy;
static SizeType
                            **CacheValidBitCopy;
static YesNoType
static YesNoType
                            **CacheDirtyBitCopy;
static TimeType
                            **RequestTimeHistogramCopy;
                            **StallTimeHistogramCopy;
static TimeType
static TimeType
                            *TotalRequestTimeCopy;
static TimeType
                            *TotalStallTimeCopy;
                         *NumberOfAccessesCopy;

*NumberOfCacheHitsCopy;

*NumberOfBufferHitsCopy;

*PredictedNumberOfAccessesCopy;
static ScoreType
static ScoreType
static ScoreType
static ScoreType
                           *PredictedNumberOfHitsCopy;
static ScoreType
```

\*DataFileCopy;

static FILE

```
****
                                                          Page 13- 6 **
                                                                       **
                               Checking.c
                                                                       **
                            CheckingConstants
                                continued
      <u>***************************</u>
if (Reset)
                                 = CacheSize;
= BlockSize;
  CacheSizeCopy
  BlockSizeCopy
                                 = SubBlockSize;
  SubBlockSizeCopy
                                 = Associativity;
  AssociativityCopy
                                  = WordSize;
  WordSizeCopy
  ReadCacheAccessTimeCopy
ReadCacheHitTimeCopy
ReadCacheMissTimeCopy
WriteCacheAccessTimeCopy
                              = ReadCacheAccessTime;
                                  = ReadCacheHitTime;
                               = ReadCacheMissTime;
= WriteCacheAccessTime;
                                  = WriteCacheHitTime;
  WriteCacheHitTimeCopy
WriteCacheMissTimeCopy
                                  = WriteCacheMissTime;
  MemoryAccessTimeCopy
MemoryTransferTimeCopy
BufferCacheAccessTimeCopy
                                 = MemoryAccessTime;
                                 = MemoryTransferTime;
                                  = BufferCacheAccessTime;
                                  = ReadBufferSize;
  ReadBufferSizeCopy
                                  = WriteBufferSize;
   WriteBufferSizeCopy
  BlockReplacementPolicyCopy
                                 = BlockReplacementPolicy;
                                 = WritePolicy;
   WritePolicyCopy
   WriteMissPolicyCopy
                                  = WriteMissPolicy;
                                  = ReadForward;
   ReadForwardCopy
   CPUWaitsForCacheWritesCopy = CPUWaitsForCacheWrites;
SearchBlockBufferCopy = SearchBlockBuffer;
UpdateReadBufferCopy = UpdateReadBuffer;
  = ReadPriority;
   ReadPriorityCopy
                                  = WritePriority;
   WritePriorityCopy
   ReadForWriteAllocatePriorityCopy = ReadForWriteAllocatePriority;
   WriteDirtyBlockPriorityCopy = WriteDirtyBlockPriority;
   NoPriorityCopy
                                   = NoPriority;
                                  = Check;
   CheckCopy
                                  = KeyBoardIO;
   KeyBoardIOCopy
                                  = DataFileName;
   DataFileNameCopy
```

/\* Page 13- 7 \*\* Checking.c CheckingConstants continued NumberOfBlocksCopy NumberOfSubBlocksCopy = NumberOfBlocks; = NumberOfBlocks; = NumberOfSubBlocks; = NumberOfSots: = NumberOfSets; NumberOfSetsCopy CacheBlockAddressCopy = CacheBlockAddress; LastCacheBlockAccessTimeCopy = LastCacheBlockAccessTime; CacheNextBlockCopy = CacheNextBlock; CacheValidBitCopy = CacheValidBit; CacheDirtyBitCopy = CacheDirtyBit; RequestTimeHistogramCopy = RequestTimeHistogram; StallTimeHistogramCopy = StallTimeHistogram; TotalRequestTimeCopy
TotalStallTimeCopy = TotalRequestTime; = TotalStallTime; NumberOfAccessesCopy = NumberOfAccesses; NumberOfCacheHitsCopy = NumberOfCacheHits; NumberOfBufferHitsCopy = NumberOfBufferHits; PredictedNumberOfAccessesCopy = PredictedNumberOfAccesses;
PredictedNumberOfHitsCopy = PredictedNumberOfHits;

= DataFile;

DataFileCopy

}

\*\*

```
Page 13- 8 **
                               Checking.c
                            CheckingConstants
                                continued
    **********
if (!(Reset))
   {
                                       != CacheSize)
  if( CacheSizeCopy
      PrintConstError("CacheSize");
                                       != BlockSize)
  if ( BlockSizeCopy
      PrintConstError("BlockSize");
                                       != SubBlockSize)
   if( SubBlockSizeCopy
       PrintConstError("SubBlockSize");
                                       != Associativity)
   if ( AssociativityCopy
       PrintConstError("Associativity");
   if ( WordSizeCopy
                                       != WordSize)
       PrintConstError("WordSize");
   if( ReadCacheAccessTimeCopy
                                       != ReadCacheAccessTime)
       PrintConstError("ReadCacheAccessTime");
   if( ReadCacheHitTimeCopy
                                       != ReadCacheHitTime)
       PrintConstError("ReadCacheHitTime");
   if( ReadCacheMissTimeCopy != ReadCacheMissTime)
       PrintConstError("ReadCacheMissTime");
   if(WriteCacheAccessTimeCopy
                                       != WriteCacheAccessTime)
       PrintConstError("WriteCacheAccessTime");
                                       != WriteCacheHitTime)
   if( WriteCacheHitTimeCopy
       PrintConstError("WriteCacheHitTime");
   if( WriteCacheMissTimeCopy
                                       != WriteCacheMissTime)
       PrintConstError("WriteCacheMissTime");
   if( MemoryAccessTimeCopy
                                       != MemoryAccessTime)
       PrintConstError("MemoryAccessTime");
   if( MemoryTransferTimeCopy
                                       != MemoryTransferTime)
       PrintConstError("MemoryTransferTime");
   if ( BufferCacheAccessTimeCopy
                                       != BufferCacheAccessTime)
       PrintConstError("BufferCacheAccessTime");
   if( ReadBufferSizeCopy
                                       != ReadBufferSize)
       PrintConstError("ReadBufferSize");
                                       != WriteBufferSize)
   if( WriteBufferSizeCopy
       PrintConstError("WriteBufferSize");
                                       != BlockReplacementPolicy)
   if ( BlockReplacementPolicyCopy
       PrintConstError("BlockReplacementPolicy");
   if ( WritePolicyCopy
                                       != WritePolicy)
       PrintConstError("WritePolicy");
                                       != WriteMissPolicy)
   if( WriteMissPolicyCopy
       PrintConstError("WriteMissPolicy");
                                       != ReadForward)
   if( ReadForwardCopy
       PrintConstError("ReadForward");
                                       != CPUWaitsForCacheWrites)
   if ( CPUWaitsForCacheWritesCopy
       PrintConstError("CPUWaitsForCacheWrites");
   if( SearchBlockBufferCopy
                                       != SearchBlockBuffer)
       PrintConstError("SearchBlockBuffer");
   if( UpdateReadBufferCopy
                                       != UpdateReadBuffer)
       PrintConstError("UpdateReadBuffer");
```

```
/************************************
                                                          Page 13- 9 **
                               Checking.c
                                                                     **
                             CheckingConstants
                                continued
*************************
     if ( RemoveReadDuplicatesCopy
                                      != RemoveReadDuplicates)
        PrintConstError("RemoveReadDuplicates");
     if( RemoveWriteDuplicatesCopy != RemoveWriteDuplicates)
        PrintConstError("RemoveWriteDuplicates");
     if( ReadPriorityCopy
                                       != ReadPriority)
        PrintConstError("ReadPriority");
                                       != WritePriority)
     if( WritePriorityCopy
        PrintConstError("WritePriority");
     if( ReadForWriteAllocatePriorityCopy != ReadForWriteAllocatePriority)
         PrintConstError("ReadForWriteAllocatePriority");
     if( WriteDirtyBlockPriorityCopy != WriteDirtyBlockPriority)
        PrintConstError("WriteDirtyBlockPriority");
     if( NoPriorityCopy
                                      != NoPriority)
         PrintConstError("NoPriority");
     if ( CheckCopy
                                       != Check)
         PrintConstError("Check");
     if( KeyBoardIOCopy
                                       != KeyBoardIO)
         PrintConstError("KeyBoardIO");
     if ( DataFileNameCopy
                                       != DataFileName)
         PrintConstError("DataFileName");
     if ( ScreenHistogramMaxIndexCopy
                                      != ScreenHistogramMaxIndex)
         PrintConstError("ScreenHistogramMaxIndex");
     if( FileHistogramMaxIndexCopy != FileHistogramMaxIndex)
         PrintConstError("FileHistogramMaxIndex");
```

\* \*

```
Page 13-10
                            Checking.c
                         CheckingConstants
                             continued
  *********
                                    != NumberOfBlocks)
if( NumberOfBlocksCopy
   PrintConstError("NumberOfBlocks");
                                    != NumberOfSubBlocks)
if ( NumberOfSubBlocksCopy
   PrintConstError("NumberOfSubBlocks");
                                    != NumberOfSets)
if ( NumberOfSetsCopy
   PrintConstError("NumberOfSets");
                                    != CacheBlockAddress)
if( CacheBlockAddressCopy
   PrintConstError("CacheBlockAddress");
if( LastCacheBlockAccessTimeCopy
                                    != LastCacheBlockAccessTime)
   PrintConstError("LastCacheBlockAccessTime");
                                    != CacheNextBlock)
if( CacheNextBlockCopy
   PrintConstError("CacheNextBlock");
                                    != CacheValidBit)
if( CacheValidBitCopy
    PrintConstError("CacheValidBit");
if( CacheDirtyBitCopy
                                    != CacheDirtyBit)
    PrintConstError("CacheDirtyBit");
                                    != RequestTimeHistogram)
if( RequestTimeHistogramCopy
   PrintConstError("RequestTimeHistogram");
                                    != StallTimeHistogram)
if( StallTimeHistogramCopy
   PrintConstError("StallTimeHistogram");
if( TotalRequestTimeCopy
                                    != TotalRequestTime)
   PrintConstError("TotalRequestTime");
if( TotalStallTimeCopy
                                    != TotalStallTime)
    PrintConstError("TotalStallTime");
                                    != NumberOfAccesses)
if( NumberOfAccessesCopy
    PrintConstError("NumberOfAccesses");
                                    != NumberOfCacheHits)
if ( NumberOfCacheHitsCopy
    PrintConstError("NumberOfCacheHits");
if( NumberOfBufferHitsCopy
                                    != NumberOfBufferHits)
    PrintConstError("NumberOfBufferHitsCopy");
if( PredictedNumberOfAccessesCopy != PredictedNumberOfAccesses)
    PrintConstError("PredictedNumberOfAccesses");
if( PredictedNumberOfHitsCopy
                                    != PredictedNumberOfHits)
    PrintConstError("PredictedNumberOfHits");
if( DataFileCopy
                                    != DataFile)
    PrintConstError("Datafile");
}
```

}

```
Page 13-11 **

Checking.c **

PrintConstError **

roid PrintConstError(VariableName)

char *VariableName;

{

printf("\n\nError in [CheckingConstants]");

printf(" \n%s did not remain constant.\n", VariableName);

exit(0);

}
```

```
Page 13-12 **
                                                                            **
                                   Checking.c
                                                                            **
                          CheckingForValuesOutOfBounds
                                                                            **
                                                                            **
                                                                            **
  Description:
**
                                                                            **
**
        CheckingForValuesOutOfBounds checks all bounded global variables
   to see if they fall within their prescribed boundaries.
   ****************************
void CheckingForValuesOutOfBounds()
   TimeType MaxTime =10000000001;
   ScoreType MaxScore=10000000001;
                    BlockIndex;
SubBlockIndex;
   SizeType
   SizeType
   SizeType
                     SetIndex;
  RequestType RequestIndex;
   CacheWaitingForType StallIndex;
   if (Time<0
      || Time>MaxTime)
     PrintTimeBoundaryError("Time", Time, 01, MaxTime);
   if ( CacheWaitingFor<Nothing</pre>
      | CacheWaitingFor>NumberOfCacheWaitingForsAvailable)
     PrintEnumBoundaryError ("CacheWaitingFor", CacheWaitingFor,
                             Nothing, NumberOfCacheWaitingForsAvailable);
   if ( MemoryWaitingFor<NothingTwo</pre>
      | | MemoryWaitingFor>NumberOfMemoryWaitingForsAvailable)
      PrintEnumBoundaryError("MemoryWaitingFor", MemoryWaitingFor,
                             NothingTwo, NumberOfMemoryWaitingForsAvailable);
   if ( BlockWaitingFor<NothingThree
      | | BlockWaitingFor>NumberOfBlockWaitingForsAvailable)
     PrintEnumBoundaryError ("BlockWaitingFor", BlockWaitingFor,
                             NothingThree, NumberOfBlockWaitingForsAvailable );
   if ( CacheHit<No
      || CacheHit>Unknown)
     PrintEnumBoundaryError("CacheHit", CacheHit, No, Unknown);
   if ( CacheBusy<No
      | | CacheBusy>Yes)
     PrintEnumBoundaryError("CacheBusy", CacheBusy, No, Yes);
   if ( Request<None</pre>
      | | Request>NumberOfRequestsAvailable)
      PrintEnumBoundaryError("Request", Request,
                             None, NumberOfRequestsAvailable);
   if ( LastRequest<None</pre>
      | | LastRequest>NumberOfRequestsAvailable)
      PrintEnumBoundaryError("LastRequest", Request,
                             None, NumberOfRequestsAvailable);
```

```
Page 13-13 **
                                Checking.c
                       CheckingForValuesOutOfBounds
                                continued
         ***************************
if ( RequestSize<0
   || RequestSize>BlockSize)
  PrintSizeBoundaryError("RequestSize", RequestSize, 0, BlockSize);
if ( RequestBlockNumber<0
   | | RequestBlockNumber>=NumberOfBlocks)
  PrintSizeBoundaryError("RequestBlockNumber", RequestBlockNumber,
                           0, NumberOfBlocks);
   }
if ( TimeOfNextRequest<0</pre>
   || TimeOfNextRequest>MaxTime)
   PrintT: meBoundaryError ("TimeOfNextRequest", TimeOfNextRequest,
                          01, MaxTime);
for (SetIndex=0; SetIndex<NumberOfSets; SetIndex++)</pre>
   if ( CacheNextBlock[SetIndex]<0</pre>
      !| CacheNextBlock[SetIndex]>=NumberOfBlocks)
      PrintSizeBoundaryError("CacheNextBlock", CacheNextBlock[SetIndex],
                             0, NumberOfBlocks);
for (BlockIndex=0; BlockIndex<NumberOfBlocks; BlockIndex++)</pre>
   for (SubBlockIndex=0; SubBlockIndex<NumberOfSubBlocks; SubBlockIndex++)</pre>
      if ( CacheValidBit[BlockIndex][SubBlockIndex]<0</pre>
         || CacheValidBit [BlockIndex] [SubBlockIndex]>1)
         PrintEnumBoundaryError ("CacheValidBit",
                                 CacheValidBit(BlockIndex)(SubBlockIndex),
      if ( CacheDirtyBit[BlockIndex][SubBlockIndex]<0</pre>
         || CacheDirtyBit[BlockIndex][SubBlockIndex]>1)
         PrintEnumBoundaryError("CacheDirtyBit",
                                 CacheDirtyBit[BlockIndex][SubBlockIndex],
                                 0,1);
      }
for (RequestIndex=0; RequestIndex<NumberOfRequestsAvailable; RequestIndex++)
   if ( TotalRequestTime[RequestIndex]<0</pre>
      || TotalRequestTime(RequestIndex)>Time)
      PrintTimeBoundaryError("TotalRequestTime",
                              TotalRequestTime[RequestIndex],
                              01, Time);
```

```
/*************************
                                                            Page 13-14 **
                                 Checking.c
                        CheckingForValuesOutOfBounds
                                                                        **
                                 continued
                                                                        **
  for (StallIndex=0;
       StallIndex<NumberOfCacheWaitingForsAvailable;
       StallIndex++)
     if ( TotalStallTime[StallIndex]<0</pre>
        || TotalStallTime[StallIndex]>Time)
        PrintTimeBoundaryError ("TotalStallTime",
                              TotalStallTime[StallIndex],
                              01, Time);
  if ( TotalNumberOfAccesses<0</pre>
     | | TotalNumberOfAccesses>MaxScore)
     PrintScoreBoundaryError("TotalNumberOfAccesses", TotalNumberOfAccesses,
                            01, MaxScore);
  if ( TOA<0
     | TOA>MaxTime)
     PrintTimeBoundaryError("TOA", TOA, 01, MaxTime);
  if ( TOD<0
     || TOD>MaxTime)
     PrintTimeBoundaryError("TOD", TOD, 01, MaxTime);
  }
```

```
Page 13-15 **
                                  Checking.c
                             PrintTimeBoundaryError
void PrintTimeBoundaryError(VariableName, Value, LowLimit, HighLimit)
  char *VariableName;
  TimeType Value;
  TimeType LowLimit;
  TimeType HighLimit;
  {
  printf("\n\nError found in [CheckingForValuestOutOfBounds]");
  printf(" \n%s is out of prescribed bounds.", VariableName);
  printf("\n\n
                   The value was .....");
  PrintTime(Value);
  printf(" \n
                  The low limit was ......");
  PrintTime (LowLimit);
  printf(" \n
                   The high limit was ......");
  PrintTime(HighLimit);
  printf("\n\n");
  DiscrepancyFound=Yes;
  }
```

```
Page 13-16 **
                               Checking.c
                                                                     **
                           PrintScoreBoundaryError
                                                                     **
        ********************
void PrintScoreBoundaryError (VariableName, Value, LowLimit, HighLimit)
            *VariableName;
  char
  ScoreType Value;
  ScoreType LowLimit;
  ScoreType HighLimit;
  {
  printf("\n\nError found in [CheckingForValuestOutOfBounds]");
  printf(" \n%s is out of prescribed bounds.", VariableName);
                  The value was .....");
  printf("\n\n
  PrintScoreCentered(Value);
  printf(" \n
                  The low limit was ......");
  PrintScoreCentered(LowLimit);
                  The high limit was ..... ");
  printf(" \n
  PrintScoreCentered(HighLimit);
  printf("\n\n");
  DiscrepancyFound=Yes;
   }
```

```
Page 13-17 **
                               Checking.c
**
                                                                   **
                          PrintSizeBoundaryError
*****************************
void PrintSizeBoundaryError(VariableName, Value, LowLimit, HighLimit)
  char *VariableName;
  SizeType Value;
  SizeType LowLimit;
  SizeType HighLimit;
  printf("\n\nError found in [CheckingForValuestOutOfBounds]");
  printf(" \n%s is out of prescribed bounds.", VariableName);
  printf("\n\n
                The value was .....");
  PrintSize(Value);
  printf(" \n
                The low limit was ......");
  PrintSize(LowLimit);
  printf(" \n The high limit was .....");
  PrintSize(HighLimit);
  printf("\n\n");
  DiscrepancyFound=Yes;
  }
```

```
Page 13-18 **
                               Checking.c
**
                         PrintEnumBoundaryError
**
void PrintEnumBoundaryError(VariableName, Value, LowLimit, HighLimit)
  char *VariableName;
  int Value;
int LowLimit;
int HighLimit;
  printf("\n\nError found in [CheckingForValuestOutOfBounds]");
  printf(" \n%s is out of prescribed bounds.", VariableName);
  printf("\n\n
                 The value was .....");
  printf("%d", Value);
  printf(" \n
                 The low limit was ......");
  printf("%d", LowLimit);
  printf(" \n
                 The high limit was ...... ");
  printf("%d", HighLimit);
  printf("\n\n");
  DiscrepancyFound=Yes;
  }
```

```
Page 13-19
                                 Checking.c
                        CheckingForInconsistencies()
            ****************
void CheckingForInconsistencies()
   CacheWaitingForType CacheWaitingForIndex;
                     RequestIndex;
  RequestType
   TimeType
                     TotalTime;
                    SumOfAccesses;
   ScoreType
  HistogramIndexType HistogramIndex;
   ScoreType
                    PredictedNumberOfWordsReadFromMemory;
   TotalTime=0;
   for (CacheWaitingForIndex=Nothing;
       CacheWaitingForIndex<NumberOfCacheWaitingForsAvailable;</pre>
       CacheWaitingForIndex++)
      TotalTime+=TotalStallTime[CacheWaitingForIndex];
   if (TotalTime!=Time)
     PrintTotalTimeError(Time, TotalTime, "Stalls");
```

```
Page 13-20 **
                                 Checking.c
                         CheckingForInconsistencies()
***************
  TotalTime=0;
  for (RequestIndex=Nothing;
       RequestIndex<NumberOfRequestsAvailable;</pre>
       RequestIndex++)
     TotalTime+=TotalRequestTime[RequestIndex];
  if (TotalTime!=Time)
     PrintTotalTimeError(Time, TotalTime, "Requests");
  for (RequestIndex=Read;
       RequestIndex<NumberOfRequestsAvailable;</pre>
       RequestIndex++)
     SumOfAccesses = 0;
     for (HistogramIndex=0;
          HistogramIndex<FileHistogramMaxIndex;</pre>
          HistogramIndex++)
        SumOfAccesses+=RequestTimeHistogram[RequestIndex][HistogramIndex];
     if (SumOfAccesses!=NumberOfAccesses[RequestIndex])
        PrintTotalScoreError(NumberOfAccesses[RequestIndex],
                             SumOfAccesses,
                             RequestString[RequestIndex]);
     }
  if (CacheWaitingFor==Nothing && ReadBuffer.Empty==Yes &&
      UpdateReadBuffer==No && SearchBlockBuffer==No &&
      RemoveReadDuplicates==Yes && WriteMissPolicy==WriteAround )
     PredictedNumberOfWordsReadFromMemory=
        (NumberOfAccesses [Read]
         -NumberOfCacheHits[Read]
         -NumberOfBufferHits[Read]) *BlockSize/WordSize;
     if (PredictedNumberOfWordsReadFromMemory!=
         TotalNumberOfWordsReadFromMemory)
        PrintTotalScoreError (PredictedNumberOfWordsReadFromMemory,
                             TotalNumberOfWordsReadFromMemory,
                             "Read Misses");
     }
  }
```

```
/***********************
                                                             Page 13-21 **
**
                                 Checking.c
                             PrintTotalTimeError
                                                                        **
void PrintTotalTimeError(TimeValue, TotalTimeValue, VariableName)
   TimeType TimeValue;
   TimeType TotalTimeValue;
   char *VariableName;
   1
  printf("\n\nError found in [CheckingForInconsistencies] the total sum");
  printf(" \nof %s times does not equal the actual time.", VariableName);
  printf("\n\n
                  Total time was equal to ... ");
  PrintTime(TimeValue);
  printf(" \n The sumation of %s", VariableName);
printf(" \n times was .....");
  PrintTime (TotalTimeValue);
  printf("\n\n");
  DiscrepancyFound=Yes;
   }
```

```
Page 13-22 **
                              Checking.c
                                                                 **
                                                                 **
                         PrintTotalScoreError
                                                                 **
****************************
void PrintTotalScoreError(TotalScoreValue, SumScoreValue, VariableName)
  ScoreType TotalScoreValue;
  ScoreType SumScoreValue;
  char
        *VariableName;
  printf("\n\nError found in [CheckingForInconsistencies] the total for");
  printf(" \n%s does not equal the summation.", VariableName);
  printf("\n\n Total number of %s accesses", VariableName);
printf(" \n was equal to .....");
  PrintScoreCentered(TotalScoreValue);
  PrintScoreCentered(SumScoreValue);
  printf("\n\n");
  DiscrepancyFound=Yes;
  }
```

```
************
                                                              Page 13-23
                                  Checking.c
                             CheckingPredictions
void CheckingPredictions()
   1
  if (PredictedNumberOfAccesses[Read]!=NumberOfAccesses[Read])
     PrintScorePredictionError (PredictedNumberOfAccesses [Read],
                               NumberOfAccesses [Read],
                               "Read Accesses");
  if (PredictedNumberOfAccesses[Write]!=NumberOfAccesses[Write])
     PrintScorePredictionError (PredictedNumberOfAccesses [Write],
                              NumberOfAccesses[Write],
                              "Write Accesses");
   if (DiscrepancyFound==No)
      if (PredictedNumberOfHits[Read] != NumberOfCacheHits[Read]
                                      + NumberOfBufferHits[Read] &&
         BlockReplacementPolicy==LRU
         SearchBlockBuffer==Yes && RemoveReadDuplicates==Yes)
        PrintScorePredictionError(PredictedNumberOfHits[Read],
                                  NumberOfCacheHits[Read]
                                  +NumberOfBufferHits[Read],
                                  "Read Hits");
      if (PredictedNumberOfHits[Write] != NumberOfCacheHits[Write]
                                       + NumberOfBufferHits[Write] &&
         BlockReplacementPolicy==LRU && WriteMissPolicy==WriteAllocate &&
         WritePolicy==WriteThrough)
        PrintScorePredictionError (PredictedNumberOfHits[Write],
                                  NumberOfCacheHits[Write]
                                  +NumberOfBufferHits[Write],
                                  "Write Hits");
      }
   }
```

.\_\_

```
/***********************
* *
                                                   Page 13-24 **
**
                            Checking.c
                                                             **
                        PrintPredictionError
      void PrintScorePredictionError(PredictedValue, ActualValue, VariableName)
  ScoreType PredictedValue;
  ScoreType ActualValue;
  char *VariableName;
  1
  printf("\n\nError found in [CheckingPredictions] when trying to predict %s",
       VariableName);
  printf("\n\n The predicted value was ... ");
  PrintScoreCentered(PredictedValue);
  printf(" \n The actual value was ..... ");
  PrintScoreCentered(ActualValue);
  printf("\n\n");
  DiscrepancyFound=Yes;
```

}

```
Page 13-25
                                Checking.c
                          PrintTimePredictionError
        ************************
void PrintTimePredictionError(PredictedValue,
                            ActualValue,
                            RequestName,
                            ProcedureName)
  TimeType PredictedValue;
  TimeType ActualValue;
          *RequestName;
  char
  char
           *ProcedureName;
  {
  printf("\n\nError found in [%s] when trying to predict time to complete %s",
         ProcedureName, RequestName);
  printf("\n\n
                  The predicted value was ... ");
  PrintScoreCentered(PredictedValue);
  printf(" \n
                  The actual value was ..... ");
  PrintScoreCentered(ActualValue);
  printf("\n\n");
  DiscrepancyFound=Yes;
  }
```

, ,,,

## **BIBLIOGRAPHY**

- 1. Jouppi, N.P., "Improving Direct-Mapped Cache Performance by the Addition of a Small Fully-Associative Cache and Prefetch Buffers," *The 17th Annual Symposium on Computer Architecture*, IEEE Computer Society Press, p. 364-373, May, 1990.
- 2. Hill, M. D., Aspects of Cache Memory and Instruction Buffer Performance. Ph.D. Thesis, University of California, Berkeley, 1987.
- 3. Smith, A. J., "Bibliography and Readings on CPU Cache Memories," Computer Architecture News v. 14-1, p. 22-42, January 1986.
- 4. Smith, A. J., "Second Bibliography on Cache Memories," v. 19-4, p. 154-182, June 1991.

## **INITIAL DISTRIBUTION LIST**

1.	Defense Technical Information Center Cameron Station Alexandria, VA 22304-6145	2
2.	Dudley Knox Library, Code 52 Naval Postgraduate School Monterey, CA 93943	2
3.	Chairman, Code EC Electrical and Computer Engineering Department Naval Postgraduate School Monterey, CA 93943	1
4.	Douglas J. Fouts, Code EC/Fs Electrical and Computer Engineering Department Naval Postgraduate School Monterey, CA 93943	2
5.	Shridhar B. Shukla, Code EC/Sh Electrical and Computer Engineering Department Naval Postgraduate School Monterey, CA 93943	1
6.	Amr M. Zaky, Code CS/Za Computer Science Department Naval Postgraduate School Monterey, CA 93943	1
7.	Diane Beckman PO Box 252 James Town, NY 14702	3